

Draft Construction Health and Safety Plan

April 13, 2022

Quality information

Prepared by	Checked by	Verified by	Approved by
			
Cary Friedman Senior Geologist	Dale "Pete" Wray, CSP SH&E Manager, ENV East	Alfred Lopilato Senior Program Manager	

Revision History

Revision	Revision date	Details	Authorized	Name	Position

Distribution List

# Hard Copies	PDF Required	Association / Company Name

Prepared for:

Battery Park City Authority
200 Liberty Street, 24th floor
New York, NY 10281

Prepared by:

AECOM
125 Broad Street
New York, NY 10004
aecom.com

Copyright © 2022 by AECOM

All rights reserved. No part of this copyrighted work may be reproduced, distributed, or transmitted in any form or by any means without the prior written permission of AECOM.

Table of Contents

- 1. Introduction 6
 - 1.1 Scope and Applicability of the Site Health and Safety Plan 6
 - 1.2 Visitors 7
 - 1.3 Project Scope of Work 7
- 2. Identification of Health and Safety Personnel 8
- 3. Hazard Assessment 9
 - 3.1 Summary 9
 - 3.2 Physical Hazards 9
 - 3.3 Chemical Hazards 9
 - 3.4 Fire and Explosion Hazard 9
 - 3.5 Environmental Hazards 10
 - 3.6 Utilities 10
- 4. Personnel Training Requirements 11
 - 4.1 Pre-Assignments and Annual Refresher Training 11
 - 4.2 Site Supervisors Training 11
 - 4.3 Respirator Fit Testing and Training 11
 - 4.4 Training and Briefing Topics 11
- 5. PERSONNEL PROTECTIVE EQUIPMENT (PPE) TO BE USED 12
 - 5.1 Levels of Protection 12
 - 5.2 Level A Personnel Protective Equipment 12
 - 5.3 Level B Personnel Protective Equipment 12
 - 5.4 Level C Personnel Protective Equipment 13
 - 5.5 Level D Personnel Protective Equipment 13
 - 5.6 Reassessment of Protection Program 13
 - 5.7 Work Duration 14
 - 5.8 Specific Levels of Protection Planned 14
- 6. MEDICAL SURVEILLANCE REQUIREMENTS 15
 - 6.1 Baseline of Pre-Assignment Monitoring 15
 - 6.2 Periodic Monitoring 15
 - 6.3 Site Specific Medical Monitoring 15
- 7. Air Monitoring and Personnel Air Sampling 16
 - 7.1 Community Air Monitoring Program (CAMP) 16
 - 7.2 Personal Sampling 16
 - 7.3 Action Levels 16
- 8. Site Control Measures 17
 - 8.1 Buddy System 17
 - 8.2 Site Communications Plan 17
 - 8.3 Work Zone Definitions 17
- 9. DECONTAMINATION PLAN 18
 - 9.1 Standard Operation Procedures for Minimizing Contact with Contamination 18
 - 9.2 Levels of Decontamination Protection Required for Personnel 18
 - 9.3 Equipment Decontamination 18
 - 9.4 Disposition of Decontamination Waste 18
- 10. EMERGENCY RESPONSE/CONTINGENCY PLAN 19
 - 10.1 Pre-Emergency Planning 19
 - 10.2 Chain of Command 19

10.3 Emergency Recognition and Prevention 19

10.4 Evacuation Routes and Procedures/Safe Distances 19

10.5 Site Security and Control 20

10.6 Emergency Decontamination Procedures 20

10.7 Emergency Contacts and Emergency Communications..... 20

10.8 Emergency Medical Treatment..... 20

10.9 Fire or Explosion Emergency Response Procedures 21

10.10 Spill or Leaks Response Procedures..... 21

11. CONFINED SPACE ENTRY PROCEDURES 22

11.1 Confined Space Entry..... 22

11.2 Permit Required Confined Space 22

11.3 Non-Permit Required Confined Space 22

11.4 Confined Space Observer 22

12. Spill Containment Program..... 23

Tables

Table 1 Air Monitoring Instrumentation and Action Levels

Table 2 Action Levels for Changes in Levels of Protection

Figures

Figure 1 Hospital Map and Directions

Appendices

Appendix A CHASP Acknowledgement Form

Appendix B Daily Safety Meeting Form

Appendix C Chemical Safety Data Sheets (SDS)

Appendix D SOPs – Cold Stress, Heat Stress, Wildlife, Plants and Insects

Appendix E Instrument Calibration Sheet and Air Monitoring Data Sheet

1. Introduction

This Construction Health and Safety Plan (CHASP) has been prepared by AECOM for general guidance and compliance with federal and state health and safety requirements for the South Battery Park City Resiliency Project (SBCPR) on behalf of the Battery Park City Authority (BPCA). The SBCPR project would provide flood protection for portions of Battery Park City including Wagner Park, Pier A Plaza and The Battery. The flood alignment is composed of multiple different integrated features such as flip-up deployable gates (flip-up deployables), glass-topped floodwalls, buried floodwalls underneath terraced slopes, exposed floodwalls, and bermed floodwalls. The term “flood alignment” is used to differentiate the combination of flood control measures represented by the SBPCR Project from a traditional freestanding flood wall for risk reduction. In addition, interior drainage improvements are proposed for the SBPCR Project, including the isolation of the existing underground sewer manholes and connected chambers.

To meet projected design flood elevations (DFE)s for coastal surge, Wagner Park would be elevated 10 to 12 feet, and the buried floodwall would be constructed beneath the raised park, maximizing the amount of protected open space within the park, while maintaining views to the waterfront. The buried floodwall also allows users to fully occupy the lawn, garden, and public park, in contrast to a traditional floodwall design which would bisect the space. Additionally, an existing Wagner Park Pavilion Building will be demolished and a new one constructed. The location of the proposed Pavilion (the Pavilion) would be similar to the existing structure, but with a slightly smaller footprint and elevated approximately 11 to 12 feet above ground level and set back closer to Battery Place. The new Pavilion would have three (3) levels: a ground, first and second level.

The Project Area covers multiple properties from 1st place and the Museum of Jewish Heritage, through Robert F. Wagner Park across Pier A Plaza, and then along the north side of the Battery Bikeway in the Battery to higher ground near the intersection of State Street and Battery Place.

1.1 Scope and Applicability of the Site Health and Safety Plan

The purpose of the CHASP is to outline best management practices and procedures, including equipment to be utilized by the construction contractors during construction. The goal of these practices is to guide the contractors throughout the duration of construction to protect the health and safety of all on-site personnel and nearby public.

This document will establish minimum standards and levels of protection that will be used by on-site personnel while performing various construction tasks and all activities that disturb existing site soil/fill and/or dewatering.

This CHASP is based on safety standards set by various agencies including:

- 29 CFR Part 1910.120 (Occupational Safety Health Administration (OSHA)) and 40 CFR Part 311 (United States Environmental Protection Agency (USEPA))
- OSHA/National Institutes Of Safety and Health (NIOSH)/USEPA/United States Coast Guard (USCG) Occupational Health and Safety Guidelines
- USEPA, Office of Emergency and Remedial Response, Standard Operating Safety Guides
- NIOSH/OSHA Pocket Guide to Chemical Hazards
- American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values

All work outlined in this CHASP is subject to the NYCDEP-approved Remedial Action Plan (RAP) prepared

by AECOM for the Site. This CHASP is not intended to address potential mechanical or structural safety concerns, such as shoring and bracing of excavations, and does not replace or supersede any OSHA regulation and/or local and state construction codes or regulations.

All contractors and subcontractors are required to develop their own health and safety related procedures and programs required for work activities that include the minimum standards included in this CHASP. All employees who work on the

construction of the project that involves potential exposure to chemicals and/or contamination will receive a copy of this CHASP for their review/use and will sign an acknowledgement form confirming they have reviewed this plan. A copy of this form is attached to this plan in Appendix A. Health and safety requirements for visitors are included in this CHASP.

1.2 Visitors

All visitors entering the Project Area will be required to sign in upon entering and leaving the site. All visitors will comply with all OSHA requirements relevant to the task they have been assigned including, but not limited to, personal protective equipment (PPE), training, medical monitoring, and respiratory protection. Visitors who are not compliant with the provisions of this CHASP will be required to leave the restricted work areas of the site and all non-compliance incidents will be recorded in a logbook. Restricted work areas are defined as work areas with potential chemical exposures which include all ground intrusive activities.

All workers who require entry to a restricted work area will undergo a safety briefing prior to entering which will identify potential hazards. The safety briefing will also include direction about identifying hazards, provide information on how to perform work with minimal risk to health and safety, provide information on the use or the limitation of safety related equipment, and provide instruction on emergency procedures. The Site Safety Officer (SSO) or their designee will be charged with ensuring all visitors and workers have had the required site safety training. A copy of a typical safety meeting documentation form is provided in Appendix B.

1.3 Project Scope of Work

This CHASP covers construction-related field activities which have the potential to disturb, contaminated soils, involve dewatering, or have the potential to aerosolize dust particulates. These activities include:

- Building demolition and pavement removal activities
- Site excavation activities for construction of below grade flood protection barriers or new utilities
- Material import activities to raise the elevation of selected parts of the Project Area

2. Identification of Health and Safety Personnel

The contractor will be charged with designating a Site Safety Officer (SSO) who will be responsible with implementing and documenting compliance with this CHASP. They will be trained to meet the OSHA requirements specified in 29 CFR Part 1910. The SSO will have full stop-work authority which they will exercise if they identify an imminent safety hazard. If the SSO is absent for any reason they will designate a qualified replacement that has reviewed this CHASP and the (RAP) for this project.

Prior to the start of construction, the SSO will record the following key personnel, their responsibilities, and record the chain of command as established by on-site personnel. The personnel will also be specifically identified in this CHASP which will be re-issued at that time to reflect the following information:

Title	Responsibilities	Phone #	Email
Project Manager			
Site Supervisor			
Site Safety Officer			
Alternate Site Safety Officer			

**Include all other key members*

The SSO (or designee) will be responsible for the following safety related activities:

1. Establish site work zones
2. Determining the protection levels and equipment required to ensure the safety of personnel
3. Ensure that all personnel in the work zone are wearing proper PPE
4. Evaluating on-site conditions (i.e., weather and chemical hazard information)
5. Make recommendations to the project manager and/or the field coordinator regarding protection levels or modifications to planned work for safety related considerations
6. Monitoring for compliance with the required safety procedures
7. Notifying emergency authorities (police, fire and ambulance) as needed including the number of site workers, their location/task, and any/all chemical storage at the site that may have the potential to impact emergency responders
8. Ensuring that all personnel have been trained in proper site safety procedures and the use of PPE, and have read and signed the Acknowledgement Forms provided in Appendix D
9. Conducting daily briefings as necessary
10. Halting work if necessary
11. Ensuring strict adherence to the CHASP
12. Reviewing personnel medical monitoring participation and health and safety training.

3. Hazard Assessment

3.1 Summary

The project scope of work will include intrusive activities that will disturb contaminated soil and groundwater. Known contaminants of concern (COCs) at the Site include pesticides, polychlorinated biphenyls (PCBs), polycyclic aromatic hydrocarbons (PAHs), chloroform, and metals. The presence of these contaminants has been attributed to historic/urban fill or historical site operations/activities.

3.2 Physical Hazards

Project employees may be exposed to physical hazards associated with the use of heavy equipment during construction activities. Other physical hazards may include:

- Heavy car and truck traffic
- Falling or flying objects
- Noise levels exceeding 90 DBA
- Getting caught or pinched in moving parts of equipment
- Slips, trips, and falls
- Hazards associated with all heavy machinery
- Hazards associated with excavation
- Hazards associated with on-Site vehicles

The Site SSO will conduct initial and periodic inspections to hazards and implement corrective actions as necessary including hazard elimination (if possible), mitigation (use of PPE or other safety equipment), and good housekeeping practices. Other best practices to be encouraged on-site include:

- Staying out of the range of motion of moving equipment
- Making eye contact with machine operators when entering a work zone
- Avoid wearing loose clothing near moving or rotating equipment
- Use of PPE appropriate with the task or work area

3.3 Chemical Hazards

Contaminants detected in soil and groundwater at the Site are known to include pesticides, polychlorinated biphenyls (PCBs), polycyclic aromatic hydrocarbons (PAHs), chloroform, and metals. Safety Data Sheets (SDS) for these contaminants that may be encountered during construction activities are included in Appendix C

3.4 Fire and Explosion Hazard

No known fire or explosion hazards are anticipated during construction activities. A utility survey will be conducted prior to intrusive activities to identify the location of subsurface utilities. If a fire or explosion hazard is identified during construction, work will be halted until the hazard has been eliminated. During work stoppage, monitoring will be conducted in the work area and work will not continue until monitoring indicates levels are below the following:

Parameter	Action Levels
Explosive Levels	>=10% of the LEL in the work area perimeter breathing zone
PID Reading	>1 unit above background (sustained in work area perimeter breathing zone for 15 minutes)

Oxygen	<19.5% or >23.5% by volume in the work area perimeter breathing zone
--------	--

3.5 Environmental Hazards

Hazards related to the work environment have the potential to impact on-site workers. They include the following:

Weather: If electrical storm activity appears to be within the immediate area, operations will be discontinued, and personnel will seek shelter in a building or a rubber-tired vehicle. Work will not resume until electrical activity has not been observed for a minimum of 30 minutes.

Heat Stress: The risk of heat stress is directly influenced by the weather, type of activity, and the amount of PPE worn. PPE can add bulk weight, restrict the body’s ability to cool itself via evaporation, convection, and radiation and increases the amount of energy needed to complete a task. On days of extreme heat or if a task requires high energy output while wearing restrictive PPE, additional measures including frequent breaks and increased fluid intake will be encouraged by the SSO to reduce the risk of heat stress. Additional information regarding heat stress symptoms and preventative measures are included as Appendix D.

Cold Stress: Personnel working outdoors for even a short time during winter months have an increased risk of cold stress. Cold stress risks include frostbite and hypothermia. Exposed parts of the body and extremities including the face, fingers, toes, and ears are the most likely to be affected. On days of extreme cold, warming breaks can be taken to mitigate the risk of cold stress. Additional information regarding cold stress symptoms and preventative measures are included in Appendix D.

Noise: The use of heavy or energized equipment and hand tools creates the potential for exposure to noise levels above OSHA guidelines. All project personnel will wear hearing protection sufficient for their task when working on the site. Audiometric examinations will be conducted as part of the medical monitoring program.

Other Potential Environmental Hazards: Poisonous plants (e.g. poison ivy), snakes, ticks, bees, and other insects, wild mammals, and pigeons may be encountered during construction All project employees will be required to follow the protective measures listed in Appendix D

3.6 Utilities

Underground utilities will be present in the vicinity of proposed construction activities. A utility survey will be conducted prior to initiating construction activities. New York 811 (One Call – 800-272-4480) will also be contacted. This work will be done a minimum of 2 weeks prior contractor mobilization to the site.

4. Personnel Training Requirements

In accordance with OSHA's standard covering hazardous waste operations and emergency response (29 CFR Part 1910.120), all personnel who will be working on-site will be trained in accordance with the standard. In addition, all personnel will participate in a medical surveillance program. Copies of training certifications and proof of participation in a medical surveillance program will be maintained by the SSO.

4.1 Pre-Assignments and Annual Refresher Training

All project personnel who may be required to perform work, defined as hazardous waste operation in 29 CFR Part 1910.120(a), that expose or potentially expose workers to hazardous substances and health hazards must have completed the initial 40-hour training. If the 40-hour training was completed more than 12 months prior to the project start-up, then an additional 8-hour refresher training must have been provided to the employee. Proof of this training is required, and training records will be maintained by the SSO.

4.2 Site Supervisors Training

Consistent with OSHA 29 CFR 1910.120(e)(4), individuals designated as Site supervisors will have completed an additional eight hours of specialized training.

4.3 Respirator Fit Testing and Training

All project employees who may be required to use respiratory protection will be required to participate in a respirator training program, which covers respirator selection, fit testing, cleaning, maintenance, and storage of respirators.

The respiratory protection for this project should be selected based on the following criteria:

- The nature of the contaminant (i.e. gas, vapor, mist, dust or fume)
- The warning properties of known or suspected contaminants (i.e. odor, taste, irritation)
- The permissible exposure limits
- The potential for immediately dangerous to life or health (IDLH) conditions in the work zones
- Quality estimates of contaminant concentrations in work zone air
- Air Monitoring results
- The nature of the work being performed for which respiratory protection is being required

4.4 Training and Briefing Topics

All project personnel, including subcontractors and visitors, will be briefed on project specific health and safety hazards that may be encountered during daily safety meetings. Personnel will also be given the opportunity to review this CHASP. Daily safety meeting topics may include:

- Review of task specific hazards
- Appropriate task-specific PPE
- Personal and/or equipment decontamination
- Emergency procedures.

5. PERSONNEL PROTECTIVE EQUIPMENT (PPE) TO BE USED

Whenever potential chemical exposures or physical hazards cannot be eliminated or mitigated by engineering controls or work practices, worker protection may be controlled through the use of PPE.

5.1 Levels of Protection

The level of protection selected is based on the following evaluation:

- The type of chemical substance, its toxicity, and its known concentration in the ambient air
- Potential for exposure to substances in air, splashing of liquids, or other direct contact with hazardous materials based on the task being performed
- Knowledge of chemicals being used or stored on-site
- Monitoring results, as described in Section 7 of this CHASP

If a situation occurs where the chemical or physical hazard are not known or defined, the level of protection will be based on professional judgement until the hazards can be better defined.

5.2 Level A Personnel Protective Equipment

Level A PPE provides the greatest level of skin, respiratory, and eye protection. If Level A conditions are encountered, all personnel will be evacuated from the area and the situation will be reviewed with the SSO.

The specific PPE for this level of protection must consist of the following:

- NIOSH and/or Mine Safety Health Association (MSHA) approved pressure demand full face self-contained breathing apparatus (SCBA), or positive pressure demand supplied air respirator with escape SCBA
- Hooded chemical resistant clothing
- Chemical resistant outer gloves
- Chemical resistant inner gloves
- Chemical resistant outer boots
- Inner boots with steel toe and shank
- Hard Hat
- Two-way radio (optional, if the situation warrants)
- Long cotton underwear (optional during cold weather)

5.3 Level B Personnel Protective Equipment

Level B provides the highest level of respiratory protection and a lesser level of skin protection as compared to Level A. If Level B conditions are encountered, all personnel will be evacuated from the area and the situation will be reviewed with the SSO.

The specific PPE for this level of protection must consist of the following:

- NIOSH and/or MSHA approved pressure demand full face SCBA, or positive pressure demand supplied air respirator with escape SCBA
- Hooded chemical resistant clothing
- Chemical resistant outer gloves
- Chemical resistant inner gloves
- Chemical resistant outer boots

- Inner boots with steel toe and shank
- Hard Hat
- Two-way radio (optional, if the situation warrants)
- Long cotton underwear (optional during cold weather)

5.4 Level C Personnel Protective Equipment

Level C is necessary when the concentrations and the type of airborne contaminants are known and the criteria for using air purifying respirators are met, and/or the chemical hazards are unknown.

The specific PPE for this level of protection must consist of the following:

- NIOSH and/or MSHA approved full face air purifying respirator equipped with dual cartridges for protection against chemical vapors, dusts, mists, or fumes
- Chemical resistant clothing (such as coveralls, two-piece chemical splash suit, disposable chemical resistant coveralls)
- Chemical resistant outer gloves
- Inner chemical resistant gloves
- Chemical resistant outer boots
- Inner boots with steel toe and shank
- Hard Hat
- Two-way radio (optional, if the situation warrants)
- Long cotton underwear (optional during cold weather)

5.5 Level D Personnel Protective Equipment

Level D PPE consists of the following:

- Disposable or non-disposable coveralls (when handling waste or product)
- Safety glasses
- Chemical resistant gloves
- Safety boots with steel toe and shank, and chemical resistant soles
- Hard Hat (when working around heavy equipment or equipment above shoulder level)
- Hearing protection (as necessary)

5.6 Reassessment of Protection Program

The level of protection provided by the PPE selection may be upgraded or downgraded by the SSO based on changes in Site conditions and/or the findings of air monitoring. If a change in the scope-of-work occurs, hazards will be reassessed. Some changes that result in the need for reassessment include:

- Start of a new phase of work
- Change in job tasks during a work phase
- Changes in season/weather
- When temperature extremes or individual medical considerations limit the effectiveness of the PPE
- When contaminants other than those previously identified are encountered
- Change in ambient levels of contaminants, as determined by on-Site monitoring

- Changes in the scope-of-work that affects the degree of, or potential for contact with, contaminated materials

5.7 Work Duration

Before workers begin work, particularly in Level C protection or higher, the anticipated duration of work should be established. Several factors limiting the duration of work include:

- Air supply consumption (SCBA use)
- Suit/ensemble permeation and penetration rates of chemicals
- Ambient temperature and weather conditions (heat stress, cold stress)
- Capacity/ability of personnel to work in PPE

The SSO will be responsible to select the level of protection necessary for each task.

5.8 Specific Levels of Protection Planned

Level D PPE is anticipated for the duration of the project.

6. MEDICAL SURVEILLANCE REQUIREMENTS

6.1 Baseline of Pre-Assignment Monitoring

All project personnel required to potentially work in restricted areas will participate in a Medical Surveillance Program and will undergo a baseline medical examination in accordance with 29 CFR 1910.120(f). Documentation of monitoring and any health-related restrictions will be provided to the SSO.

6.2 Periodic Monitoring

Periodic medical monitoring will be conducted as follows:

- All project personnel will undergo a medical examination at least once every twelve months, unless the attending physician believes a longer interval (but not greater than biennially) is appropriate.
- A medical examination will also be conducted at the termination of employment or reassignment to an area where the employee would not be covered if the employee has not had an examination within the previous six months.
- A medical examination will be conducted as soon as possible after an employee has developed signs or symptoms indicating possible overexposure to hazardous substances or other health hazards, or if the employee has been injured or exposed above the permissible exposure limits.
- A medical examination will be conducted on a more frequent basis if the attending physician determines it to be medically necessary.

6.3 Site Specific Medical Monitoring

No Site-specific medical monitoring is anticipated for this project.

7. Air Monitoring and Personnel Air Sampling

The location, frequency and type of monitoring for the identified project tasks will be assessed once the project begins and protocols will be set for the remainder of the project. Air monitoring will be conducted during all intrusive activities. The purpose of the air monitoring program includes the following methodology:

- Work areas and activities that require the use of engineering or work practice controls, or that requires the use of PPE
- To provide data to confirm that levels of PPE selected are adequate for the protection of workers
- Provides data for the documentation of employee exposures, or lack thereof
- Provides data to document that all necessary controls and precautions are being taken for the protection of the public and the environment
- Provides data to determine the need to implement emergency control procedures and contingency plans

The project SSO will be responsible for implementing the air-monitoring program. However, the actual air monitoring may be conducted by a health and safety technician. The individual will be trained in the operation, calibration, care and limitations of the instruments they will use to conduct the air monitoring program. This will include any air sampling equipment should it be utilized. The SSO will make sure appropriate air monitoring equipment is available at all times. Instrument calibration, instrument readings, serial numbers, and sample locations will be documented in a logbook.

7.1 Community Air Monitoring Program (CAMP)

A Community Air Monitoring Plan will be implemented during construction to provide a measure of protection for the downwind community (off-site receptors). The CAMP also serves to protect on-site workers from airborne contaminants that have the potential to be released during construction activities.

Direct reading survey instruments will be used to monitor for airborne contaminants and for concentrations of vapors and gases. Direct monitoring will include both workers breathing zone and ambient work zone air. At a minimum, the following air monitoring equipment will be used on this project:

- Photoionization Detector (PID) – equipped with a 11.7 eV lamp.
- Four-Gas Meter – equipped with Lower Explosive Limit (LEL), , Oxygen (O₂), Carbon Monoxide (CO), and Hydrogen Sulfide (H₂S) sensors.
- Aerosol Particulate Monitor – capable of reading particulates at 10 micrometers (PM-10)

The attached Table 1 describes the instrument application, the monitoring locations, the frequency of monitoring for this project, and action levels for VOCs and particulates. Appendix E contains an instrument calibration log and air monitoring data sheet for use during construction.

7.2 Personal Sampling

No personal sampling is proposed for this Site. Should areas of gross contamination be encountered or other unanticipated hazardous materials (such as asbestos), the SSO may determine the need for personal sampling.

7.3 Action Levels

The action levels presented on the attached Table 2 will be used to determine the level of PPE required. It is anticipated that all work will be performed in Level D protection.

8. Site Control Measures

Site controls measures are implemented to protect employees, the public, and the environment from hazards and exposures. These protective measures may include but are not limited to the following measures:

8.1 Buddy System

Most tasks during construction will be performed by one or more employees. At a minimum, no work will occur in known contaminated areas by a lone worker. A buddy or spotter will be used during work in contaminated areas who will be able to provide his/her partner with assistance; observe his/her partner for signs of chemical or heat exposure; periodically check the integrity of his/her partners PPE; and provide notification if emergency help is needed.

8.2 Site Communications Plan

The SSO and site supervisor or project manager will develop a site communications plan to respond to emergencies. The emergency alert communication will consist of verbal, mobile phone communications, and hand signals. The plan will include a chain of command for communication of an emergency.

A listing of emergency contacts is included as Section 10.

8.3 Work Zone Definitions

Three work zones will be established as outlined below:

The exclusion zone is defined as the area that is considered to be contaminated, potentially contaminated, or that could become contaminated. All project personnel who work in the exclusion zone are required to use the appropriate level of PPE for the task, as determined by the SSO. Exclusion zones are typically separated from the project area with fencing, caution tape, and/or traffic cones.

The contamination reduction zone serves as the buffer zone between the exclusion zone and the support zone. Materials and supplies are staged in this zone for the servicing of equipment and project personnel in the exclusion zone. All vehicles, equipment, and project personnel coming out of the exclusion zone will pass through the contamination reduction zone for decontamination. All protective clothing removed by employees coming out of the exclusion zone will be staged in this area for disposal.

The support zone is considered to be uncontaminated. The support zone will be clearly delineated so as to prevent active or passive contamination from the work Site. This area serves as the entry point for Site personnel, equipment, materials, and visitors.

9. DECONTAMINATION PLAN

9.1 Standard Operation Procedures for Minimizing Contact with Contamination

The following practices will be used to minimize contact with hazardous materials and/or contamination:

- Work practices that minimize contact with hazardous substances will be stressed (i.e. not walking through areas of obvious contamination; not directly touching potentially hazardous substances).
- Use of remote sampling, handling, and container opening techniques.
- Protect monitoring and sampling instruments by bagging, leaving openings in the bag sample ports and sensors that must contact potentially contaminated materials.

Wear disposable outer garments and use disposable equipment where appropriate.

9.2 Levels of Decontamination Protection Required for Personnel

All project personnel will be instructed to remove their contaminated work clothing in a specific area and deposit them into designated containers. In addition, the employees will be instructed to use the wash facilities provided before leaving the work area or exclusion zone.

9.3 Equipment Decontamination

All project equipment used for intrusive activities will be decontaminated prior to being moved out of a contaminated zone to another area of the site or off-site. The equipment decontamination will be done in the contamination reduction zone or a separate designated area.

Small equipment will be decontaminated by wiping or spraying the equipment with paper towels dipped in water and laboratory-grade detergent solution followed by a water rinse. Larger equipment will be steam cleaned. Water used for decontamination will be containerized in an appropriate vessel, characterized, and disposed off-site in accordance with all local, state, and federal regulations.

9.4 Disposition of Decontamination Waste

All contaminated clothing and water will be disposed at an authorized facility along with other project- derived wastes, as needed. All construction derived wastes will be handled in accordance with the procedures outlined in the New York State Department of Environmental Conservation (NYSDEC) DER- 10 / Technical Guidance for Site Investigation and Remediation. See the Remedial Action Plan for more information

10. EMERGENCY RESPONSE/CONTINGENCY PLAN

This section is designed to provide guidance in the event of an emergency. This plan is intended as a guide and cannot account for all scenarios.

A form to be used to document the safety meeting is included as Appendix B.

10.1 Pre-Emergency Planning

Pre-emergency planning starts with training for the task at hand. Certain types of training are required to work on the site including OSHA HAZWOPER which includes an emergency response section.

10.2 Chain of Command

The chain of command staff charged with emergency response tasks are discussed in Section 2 of this CHASP. Specific roles will be identified and documented prior to the start of construction. These roles will be re-emphasized during the daily safety briefings. The SSO has the overall authority for the implementation of emergency response procedures and all Site emergency actions. The SSO is also responsible for notifying the appropriate agencies, as outlined in Section 10.7 below.

10.3 Emergency Recognition and Prevention

- Preventing an emergency is the responsibility of all workers and visitors on-site. Following approved procedures, clear lines of communication, and use of PPE, and good housekeeping practices should be part of every workday. Other best practices will be enforced including prohibiting eating and smoking within the work area or exclusion zone. The following measures will also be enforced and monitored by the SSO: Prior to the start of each specific task, such as excavation, evacuation route(s) will be established and communicated with the project personnel during the initial safety meeting.
- To the extent possible, all sources of ignition will be kept away from the work area and fire extinguishers will be maintained on-Site.
- Absorbent materials, shovels, and containers will be kept on-Site to contain a spill or leak.
- Operations will be stopped when inclement or hazardous weather conditions pose a threat to the safety of project personnel or the environment. Examples of such hazardous conditions include treacherous weather conditions or limited visibility.
- Preventative measures will be used to minimize heat stress and cold exposure (see Appendix D).
- Preventative measures for contact with poisonous plants, animals, and insects will be followed (see Appendix D).
- Confined space entry procedures, as outlined in Section 11, will be followed

10.4 Evacuation Routes and Procedures/Safe Distances

In the event of an incident that could potentially expose Site personnel or the public to hazardous materials or conditions, the SSO will be responsible for initiating the following actions:

- Evacuate all personnel from any area on the Site where the potential for exposure exists to a safe area designated prior to the start of work
- Stop Site operations until the added risk is adequately assessed and corrective actions initiated
- Provide for the immediate medical treatment of any injured or exposed personnel
- Notify the appropriate agencies for response to the incident

In the event of an evacuation, safe distances and places of refuge will correlate to the wind direction, topography and type of incident. Personnel will be advised to move to an upwind location at least 300 yards from any fires and/or chemical releases and will be advised to continually monitor wind direction for changes. The SSO is responsible to account for all personnel at the refuge location. If moving upwind from these types of incidents is not possible without encountering the

incident and subsequent exposure potential, personnel will be advised to move cross wind or downwind to a distance necessary to be out of the path of smoke, odors, or releases.

10.5 Site Security and Control

Site security measures typically include fencing with locked gates, security personnel, limiting unauthorized personnel from entering the site, and video surveillance of site perimeters. The specific site controls to be employed at this site will be determined prior to the start of construction.

10.6 Emergency Decontamination Procedures

In the event of an emergency, decontamination procedures will be implemented based on the nature of the emergency. In the event of a medical emergency, decontamination will generally consist of the removal of the outer protective PPE. If the nature of the emergency includes chemical contamination, the victim will be washed/sprayed with water until first responders (police/fire/ambulance personnel) arrive. If the nature of the emergency does not allow other site personnel from getting near the victim until emergency response personnel arrive, decontamination may be postponed, but all emergency response personnel must be informed about any potential exposures to contamination.

10.7 Emergency Contacts and Emergency Communications

Emergency communications will be implemented by the SSO. An emergency contact list is shown below and can be revised and/or updated at any time during the duration of construction. An emergency contact list should also be posted on-site in easily viewable areas.

<u>Organization</u>	<u>Phone Number</u>
Ambulance	911
Police Department	911
Fire Department	911
Hospital*:	New York Presbyterian Lower Manhattan Hospital Emergency Department 83 Gold Street New York, NY 10038 Phone: (212) 312-5070

* Hospital location and directions are provided as Figure 1

Poison Control Center	(800) 222-1222
Chemtrec (chemical information resources)	(800) 262-8200
National Response Center	(800) 424-8802
NYSDEC Hotline	(800) 457-7362
Project Manager (TBD)	(xxx) xxx-xxxx

10.8 Emergency Medical Treatment

In the event of an injury, all personnel will assemble at the decontamination area. If the injured person is immobile, one or more persons will remain nearby to provide the necessary first aid. If medical assistance is required, the SSO will summon the appropriate assistance and arrange for the transportation of the injured to the hospital.

In the event of a chemical exposure, the following will be initiated depending on the nature of the exposure:

- Skin/Eye Contact: Wash exposed skin immediately and flush the affected area for at least 15 minutes. Transport to medical facility.
- Inhalation: Get to fresh air, artificial respiration as necessary, transport to medical facility.
- Ingestion: Transport to medical facility immediately.

The nearest hospital to the project Site area is listed in Section 10.7. The directions to the hospital are depicted on Figure 1.

10.9 Fire or Explosion Emergency Response Procedures

The best way to prevent a fire or explosion is to eliminate possible ignition sources in the vicinity of flammable or explosive materials. That is not always possible based on the work being performed. Typical ignition sources on construction sites include; sparking tools, electric and combustion engines/motors, open flames, static spark, and high heat. These tools and ignition sources should not be used around flammable materials. Smoking will be prohibited on-site.

In the event of fire or explosion, all personnel will be evacuated to the designated assembly area or to a safe area as directed by the SSO. The SSO or their designee will contact emergency personnel.

10.10 Spill or Leaks Response Procedures

In the event of a spill or release of a potentially hazardous material, the following procedures will be implemented:

- Administer first aid (if it is safe to do so) or obtain emergency medical assistance if necessary
- Warn others of the hazard
- If possible and safe to do so, stop the spill or release at the source
- Deploy containment equipment (sorbents) and initiate cleanup activities - for example, if the spill or release is in an unpaved area, the contaminated material can be excavated, segregated, and staged for characterization and off-site disposal in accordance with the RAP
- Notify the SSO and Project Manager

Contact NYSDEC to report a spill (1-800-457-7362). They will request information including your name and affiliation; the location of the spill; the estimated volume; date and time of release; actions taken to address the spill; and what if any media was impacted. Request and record the spill number in the field notebook.

11. CONFINED SPACE ENTRY PROCEDURES

It is not anticipated that site personnel will be required to enter or work in confined spaces. If it is determined during construction that entering or working in a confined space is necessary, only appropriately trained personnel will perform such tasks and will do so in accordance with the procedures outline in this section.

11.1 Confined Space Entry

Confined spaces refer to a space which, by design, has limited openings for entry and exit; has unfavorable natural ventilation which could contain or produce dangerous atmospheres; and which is not intended for continuous occupancy. Confined spaces can include, but are not limited to, storage tanks, process vessels, pits, silos, vats, degreasers, reaction vessels, boilers, ventilation and exhaust ducts, and pipelines.

11.2 Permit Required Confined Space

A permit required confined space is a confined space with one or more of the following characteristics:

- Contains or has the potential to contain a hazardous atmosphere
- Contains or formerly contained a material that has the potential for engulfing an entrant
- Has an internal configuration in which an entrant could become entrapped or asphyxiated by inwardly converging walls
- Contains any other recognized serious safety or health hazard

Personnel are not permitted to enter any permit-required confined space unless specific authorization and training is provided.

11.3 Non-Permit Required Confined Space

A non-permit required confined space is a confined space that meets the definition of a confined space but does not meet the requirements for a permit-required confined space.

Potential hazards associated with confined space entry may include an oxygen deficient atmosphere (less than 19.5% oxygen), high vapor concentrations, or physical entrapment. Initial hazard assessment of potentially confined spaces shall include:

- Assessment of entrapment
- Air Monitoring for vapors and oxygen levels (see Section 7, action levels)
- A ladder must be used for access and egress of any pit or trench greater than 3 feet deep

Personnel are not permitted to enter a confined space without specific authorization and the appropriate training.

11.4 Confined Space Observer

If entry into a non-permit confined space is required, a trained person capable of anticipating, recognizing, and evaluating employee exposure to hazardous substances or other unsafe conditions will remain on the outside of the confined space and will remain in communication with those working inside. Confined space entry work will not be conducted without specific authorization from the AECOM Project Manager.

12. Spill Containment Program

If a spill or release occurs on-site during construction, personnel will notify the SSO who will direct response activities including containment and notifications up the chain of command or to emergency response agencies if necessary.

The SSO will direct designated employees to initiate containment and cleanup activities if possible and safe to do so. The SSO will determine if evacuation is required. The SSO will ensure that areas affected by the release any substances or equipment to be used to initiate containment or cleanup are appropriate to be used in that area or with the substance that has been released. All wastes generated in response to a spill will be disposed of in accordance with all local, state, and federal regulations and the RAP.

The SSO will document the spill or release incident and, if necessary, initiate notification to NYSDEC in accordance with the steps outlined in Section 10.10. If NYSDEC notification is necessary, additional steps will be required after the initial notification. Additional information about next steps after initial spill reporting can be found in the Spill Guidance Manual on the NYSDEC website at the below web address: <https://www.dec.ny.gov/regulations/2634.html>

TABLES

**TABLE 1
INSTRUMENT
APPLICATIONS AND
ACTION LEVELS**

Instrument	Application	Monitoring Location	Frequency
PID with 11.7 eV lamp	Total Organic vapor detection excluding methane	Work area breathing zone	Continuous
Aerosol Particulate Monitor	Total particulate concentrations	Work area breathing zone and downwind of soil disruptive activities	Continuous
Four-Gas Meter	Monitoring of levels of combustible gases (lower explosive limit), oxygen and hydrogen sulfide gases	Work area in breathing zone, particularly within excavation	Continuous

PID: Photo-ionization detector (total organic vapor detection instrument)

Four-Gas Meter: Meter with multiple sensors in one instrument capable of detecting lower explosive limit, carbon monoxide, oxygen, and hydrogen sulfide

Contaminant of Concern	Action Level	Response Action
VOCs	>5 ppm	Work will be temporarily halted and monitoring continued until the organic vapor level decreases below background levels. Work activities may then resume
	>5 ppm over background but less than 25 ppm	Work will be halted and the source of the vapors identified. Corrective actions will be employed to abate the emissions while monitoring continues. Work can resume once the organic vapor level 200ft downwind of the exclusion zone or half the distance to the nearest receptor (but in no case less than 20ft) is below 5 ppm over background for the 15-minute time-weighted average.
	Exceeds 25 ppm	Work activities will be shut down and will not resume until the source of the emissions is abated and readings are less than 25 ppm over background levels.

Note: The ambient air concentration of total organic vapors at the downwind perimeter of the work area of exclusion zone for the 15-minute average, in parts per million (ppm)

**TABLE 1
INSTRUMENT
APPLICATIONS AND
ACTION LEVELS**

Contaminant of Concern	Action Level	Response Action
Particulates	Between 100 mcg/m ³ and 150 mcg/m ³	Dust suppression activities will be employed. Work will continue as long as levels are not 150 mcg/m ³ above the upwind level and no visible dust is migrating out of the work area(s).
	Exceeds 150 mcg/m ³	Work will be halted and work methods will be re-evaluated to determine the proper mitigation techniques. Work will resume when mitigation or elimination measures reduce the particulate concentration to within 150 mcg/m ³ of the upwind concentration and dust is not visibly migrating from the work area.

**Table 2
Action Levels for Changes in Levels of Protection**

Hazard Monitored	Tasks	Action Level	Response/Level of Protection
Organic/Inorganic gases and vapors (known contaminants) Organic/Inorganic gases and vapors (unknown contaminants) (Use PEL/TLV/REL criteria on Table 1 if contaminants are known)	Excavation and construction Excavation and construction	Chemical dependent according to PEL/TLV/REL Background (0-15 units* in ambient air) 15-50 units* in ambient air 50-500 units* in ambient air >500 units* above background	Consult standard references to toxicity data. Action level usually set at 50% of PEL/TLV/REL. When multiple chemicals are present, use lowest published exposure limit. LEVEL D LEVEL C: Personnel will use full-face air-purifying respirator with GME-H cartridges. LEVEL B: Personnel will exit the site if Level B respiratory equipment is required. LEVEL A: Personnel will exit the site if Level A respiratory equipment is required.
Explosive Atmosphere	Excavation and construction	<10% LEL 10-20% LEL >20% LEL	Work with caution. Continue monitoring. Work with extreme caution. Continuous monitoring required. Explosion hazard. Withdraw from area immediately. Note: Combustible gas readings may not be accurate in atmosphere with <19.5% oxygen.
Oxygen	Excavation	<19.5% 19-21% 21.5-25% >25%	Oxygen deficient atmosphere. Level B required. Continue work. Continue work with continuous monitoring. Use extreme caution under oxygen enhanced conditions. Fire potential. Withdraw from work area immediately. Consult a fire safety specialist
Particulates	Excavation and construction	<100 ug/m ³ above background (over 15 minutes) 100-150 ug/m ³ above background >150 ug/m ³ above background	Continue work. Continue work with dust suppression. Stop work and re-evaluate dust suppression techniques.

* = these units are not criteria but are to be used as guidelines only.

FIGURES

Figure 1

HOSPITAL MAP AND DIRECTIONS

From: South Battery Park Resiliency Project (SBPRP)
New York, NY

To: New York Presbyterian Lower Manhattan Hospital Emergency Department 83
83 Gold Street, New York, NY 10038
(212) 312-5070



9 min (1.3 miles)

via Water St
Some traffic, as usual

Museum of Jewish Heritage – A Living Memorial to the Holocaust
36 Battery Pl, New York, NY 10280

- ↑ Head south on Battery Pl toward Battery Park City Esplanade
0.3 mi
- ↪ Battery Pl turns right and becomes State St
0.2 mi
- ↑ Continue onto Water St
0.6 mi
- ↶ Turn left onto Fulton St
0.1 mi
- ↪ Turn right onto Gold St
Destination will be on the left
407 ft

New York-Presbyterian Lower Manhattan Hospital Emergency Department
83 Gold St, New York, NY 10038

aecom.com

APPENDICES

Appendix A

CHASP Acknowledgement Form

Appendix B

Daily Safety Meeting Form

Americas

Daily Tailgate Meeting

S3AM-209-FM5

Instructions: Conduct meeting prior to sending crews to individual tasks. Require attendance of all AECOM employees and subcontractors. Invite personnel from simultaneous operations for coordination purposes. Review scope of work and briefly discuss required and applicable topics. **This meeting is a daily refresher, not a full orientation.** Task-specific discussions associated with Task Hazard Assessment (THA) follow this meeting at the task location immediately before individual task is started.

AECOM Supervisor Name:
Phone Number:
AECOM SH&E Rep. Name:
Phone Number:
Meeting Leader:

DCS Americas - This form may be replaced by the electronic Daily Tailgate Meeting Tool. Link - [Ecosystem Daily Tailgate Meeting App Site](#)

Date:	Project Name/Location:	Project Number:
--------------	-------------------------------	------------------------

Today's Scope of Work:

Muster Point Location:	First Aid Kit Location:	Fire Extinguisher Location:	Spill Kit Location:
-------------------------------	--------------------------------	------------------------------------	----------------------------

1. Required Topics	2. Discuss if Applicable to Today's Work
<p>Fitness for Duty requirements, all sign in / sign out</p> <p>Required training (incl. task specific) completed and current</p> <p>SH&E Plan onsite - understood, reviewed, signed by all (incl. scope, preplanning hazard assessments / risk registers, controls, procedures, requirements, etc.)</p> <p>Task Hazard Assessments (THAs) are to be reviewed and completed for each task immediately prior to conducting</p> <p>STOP WORK Right & Responsibility- all task changes/changed conditions re-assess with THA</p> <p>Requirement to report to supervisor any injury, illness, damage, near miss, unsafe act / condition</p> <p>Emergency Response Plan – including muster point, first aid kit, fire extinguisher, clinic/hospital location</p> <p>Personal Protective Equipment (PPE) - Required items per hazard assessments in good condition / in use by all</p> <p>Equipment/machinery inspected (documented as required) and in good condition - operators properly trained/certified</p> <p>Work area set up and demarcation/ barricades in place to protect workers, site staff, and the public</p> <p>Required checklists/records available, understood (describe):</p> <p>Lessons Learned / SH&E improvements (describe):</p>	<p>Check <input checked="" type="checkbox"/> as reviewed or mark <input type="checkbox"/> as not applicable</p> <p>Biological/ Chemical / Electrical Hazards</p> <p>Ergonomics - Lifting, Body Position</p> <p>Lock Out/ Tag Out</p> <p>Short Service Employees - visual identifier and mentor/ oversight assignment</p> <p>Simultaneous/ Neighbouring Operations</p> <p>Slip/ Trip/ Fall Hazards</p> <p>Specialized PPE Needs</p> <p>Traffic Control</p> <p>Waste Management/ Decontamination</p> <p>Weather Hazards / Heat Stress / Cold Stress</p> <p>Subcontractor Requirements (e.g., JHAs, THAs, procedures, reporting, etc.)</p> <p>Work Permits / Plans required (e.g., Fall Protection, Confined Space, Hot Work, Critical Lifts, etc.); in place, understood (identify/attach):</p> <p>Other Topics (describe/attach):</p> <p>Client specific requirements (describe):</p>

3. Daily Check Out by Site Supervisor	
Describe incidents, near misses, observations or Stop Work interventions from today:	Describe Lessons Learned/ Improvement Areas from today:

The site is being left in a safe condition and work crew checked out as fit unless otherwise specified as above.

Site Supervisor Name	Signature	Date Time (at end of day / shift)
-----------------------------	------------------	--

Worker Acknowledgement / Sign In Sign Out sheets applicable to this meeting are on reverse and, if applicable, attached.

All employees:

- **STOP WORK** if concerned / uncertain about safety / hazard or additional precaution is not recorded on the THA.
- **Be alert and communicate any changes in personnel or conditions at the worksite to the supervisor.**
- **Reassess task, hazards, & mitigations on an ongoing basis; amend the THA if needed.**

SITE WORKERS (including AECOM Contractors and Subcontractors): Your signature below means that you understand:

- * The requirement to participate in creating, reviewing, & updating hazard assessments (THA) applicable to your task(s).
- * The hazards & control measures associated with each task you are about to perform.
- * The permit to work requirements applicable to the work you are about to perform (if it includes permitted activities).
- * That no tasks or work is to be performed without a hazard assessment.
- * Your authority & obligation to “Stop Work” intervene, speak up/ listen up.

Your initials (right columns) certify that you arrived & departed fit for duty, & have reported all incidents/near misses; meaning:

- * You are physically and mentally fit for duty and have inspected your required PPE to ensure satisfactory condition.
- * You are not under the influence of any type of medication, drugs, or alcohol that could affect your ability to work safely.
- * You are aware of your responsibility to immediately report any illness, injury (regardless of where or when it occurred), or impairment/fatigue issue to the AECOM Supervisor.
- * You signed out as fit / uninjured unless you have otherwise informed the AECOM Supervisor.

Print Name & Company	Signature	Initials & Sign In Time	Initials & Sign Out Time
		In & Fit	Out & Fit
		In & Fit	Out & Fit
		In & Fit	Out & Fit
		In & Fit	Out & Fit
		In & Fit	Out & Fit
		In & Fit	Out & Fit
		In & Fit	Out & Fit
		In & Fit	Out & Fit
		In & Fit	Out & Fit
		In & Fit	Out & Fit

(Attach additional Site Worker sign-in/out sheets if needed) Identify number of attached sheets: _____

SITE VISITOR / SITE REPRESENTATIVE

Name	Company Name	Arrival Time	Departure Time	Signature

Appendix C

Chemical Safety Data Sheets (SDS)

Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 11.18.2014

Page 1 of 7

Aluminum Metal Strips

SECTION 1 : Identification of the substance/mixture and of the supplier

Product name : Aluminum Metal Strips

Manufacturer/Supplier Trade name:

Manufacturer/Supplier Article number: S25146

Recommended uses of the product and uses restrictions on use:

Manufacturer Details:

AquaPhoenix Scientific
9 Barnhart Drive, Hanover, PA 17331

Supplier Details:

Fisher Science Education
15 Jet View Drive, Rochester, NY 14624

Emergency telephone number:

Fisher Science Education Emergency Telephone No.: 800-535-5053

SECTION 2 : Hazards identification

Classification of the substance or mixture:

Not classified for physical or health hazards under GHS.

Hazard statements:

Precautionary statements:

If medical advice is needed, have product container or label at hand

Keep out of reach of children

Read label before use

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Protect from moisture

Other Non-GHS Classification:

WHMIS



NFPA/HMIS

Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 11.18.2014

Page 2 of 7

Aluminum Metal Strips



NFPA SCALE (0-4)

Health	0
Flammability	1
Physical Hazard	1
Personal Protection	X

HMS RATINGS (0-4)

SECTION 3 : Composition/information on ingredients

Ingredients:

CAS 7429-90-5	Aluminum	100 %
---------------	----------	-------

Percentages are by weight

SECTION 4 : First aid measures

Description of first aid measures

After inhalation: Move exposed individual to fresh air. Loosen clothing as necessary and position individual in a comfortable position. Seek medical advice if discomfort or irritation persists. If breathing difficult, give oxygen.

After skin contact: Wash affected area with water for at least 15 minutes. Seek medical attention if irritation persists or if concerned.

After eye contact: Protect unexposed eye. Rinse/flush exposed eye(s) gently using water for 15-20 minutes. Remove contact lens(es) if able to do so during rinsing. Seek medical attention if irritation persists or if concerned.

After swallowing: Rinse mouth thoroughly. Do not induce vomiting. Seek medical attention immediately. Have exposed individual drink sips of water.

Most important symptoms and effects, both acute and delayed:

Irritation, Nausea, Headache, Shortness of breath.;

Indication of any immediate medical attention and special treatment needed:

If seeking medical attention, provide SDS document to physician. Treat patient symptomatically.

SECTION 5 : Firefighting measures

Extinguishing media

Suitable extinguishing agents: If in laboratory setting, follow laboratory fire suppression procedures. Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition. Smother with suitable dry powder for extinction. (Pressure from this media may cause severe dusting)

For safety reasons unsuitable extinguishing agents: Do not use water.

Special hazards arising from the substance or mixture:

Combustion products may include metallic oxides or other toxic vapors. Combustible Solid, finely divided dust is easily ignited; may cause explosions.

Advice for firefighters:

Protective equipment: Use NIOSH-approved respiratory protection/breathing apparatus. Wear fire/flame resistant/retardant clothing.

Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 11.18.2014

Page 3 of 7

Aluminum Metal Strips

Additional information (precautions): Use spark-proof tools and explosion-proof equipment.

SECTION 6 : Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Use respiratory protective device against the effects of fumes/dust/aerosol. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Protect from heat. Stop the spill, if possible. Contain spilled material by diking or using inert absorbent. Transfer to a disposal or recovery container.

Environmental precautions:

Prevent from reaching drains, sewer or waterway. Collect contaminated soil for characterization per Section 13

Methods and material for containment and cleaning up:

If in a laboratory setting, follow Chemical Hygiene Plan procedures. Place into properly labeled containers for recovery or disposal. If necessary, use trained response staff/contractor. Avoid contact with skin, eyes and clothing. Vacuum or sweep up material and place into a suitable, dry disposal container. Always obey local regulations.

Reference to other sections:

SECTION 7 : Handling and storage

Precautions for safe handling:

Follow good hygiene procedures when handling chemical materials. Wash thoroughly after handling. Do not eat, drink, smoke, or use personal products when handling chemical substances. If in a laboratory setting, follow Chemical Hygiene Plan. Use only in well ventilated areas. Avoid generation of dust or fine particulate. Dust may form flammable or explosive mixture with air, especially when damp. Wash thoroughly after handling. Avoid contact with skin and eyes. Avoid ingestion and inhalation.

Conditions for safe storage, including any incompatibilities:

Store in a cool location. Avoid storage near extreme heat, ignition sources or open flame. Store away from foodstuffs. Store away from oxidizing agents. Store in cool, dry conditions in well sealed containers. Keep container tightly sealed.

SECTION 8 : Exposure controls/personal protection



Control Parameters:

7429-90-5, Aluminum (as Al) (pyrophoric powder), ACGIH TLV TWA 5 mg/m³
7429-90-5, Aluminum (as Al) (metal dust), ACGIH TLV TWA: 10 mg/m³
7429-90-5, Aluminum (as Al) (respirable), OSHA PEL TWA: 5 mg/m³
7429-90-5, Aluminum (as Al) (total), OSHA PEL TWA: 15 mg/m³
7429-90-5, Aluminum (as Al) (respirable), NIOSH REL: TWA 5 mg/m³
7429-90-5, Aluminum (as Al) (total), NIOSH REL: TWA 10 mg/m³

Appropriate Engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use/handling. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or dusts (total/respirable) below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 11.18.2014

Page 4 of 7

Aluminum Metal Strips

Respiratory protection:	Not required under normal conditions of use. Use suitable respiratory protective device when high concentrations are present. Use suitable respiratory protective device when aerosol or mist is formed. For spills, respiratory protection may be advisable.
Protection of skin:	The glove material has to be impermeable and resistant to the product/ the substance/ the preparation being used/handled. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.
Eye protection:	Safety glasses with side shields or goggles.
General hygienic measures:	The usual precautionary measures are to be adhered to when handling chemicals. Keep away from food, beverages and feed sources. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases/fumes/dust/mist/vapor/aerosols. Avoid contact with the eyes and skin.

SECTION 9 : Physical and chemical properties

Appearance (physical state,color):	Silver-gray solid	Explosion limit lower: Explosion limit upper:	Not determined Not determined
Odor:	Odorless	Vapor pressure:	Not determined
Odor threshold:	Not determined	Vapor density:	Not determined
pH-value:	Not Applicable	Relative density:	2.7 g/cm ³
Melting/Freezing point:	660 °C, 1220°F	Solubilities:	Insoluble in water.
Boiling point/Boiling range:	2327 °C, 4221°F	Partition coefficient (n-octanol/water):	Not determined
Flash point (closed cup):	Not determined	Auto/Self-ignition temperature:	Not determined
Evaporation rate:	Not determined	Decomposition temperature:	Not determined
Flammability (solid,gaseous):	Not determined	Viscosity:	a. Kinematic:Not determined b. Dynamic: Not applicable
Density: Not Determined Molecular Weight: 26.98 Specific Gravity: :2.7020 g/cm ³			

SECTION 10 : Stability and reactivity

Reactivity:Corrodes in contact with acids & other metals.
Chemical stability:No decomposition if used and stored according to specifications.Stable under normal temps and pressures.
Possible hazardous reactions:Combustible Solid, finely divided dust is easily ignited; may cause explosions.
Conditions to avoid:Store away from oxidizing agents, strong acids or bases.Air and moisture sensitive.
Incompatible materials:Strong oxidizers & acids.Halogenated hydrocarbons.
Hazardous decomposition products:Aluminum Oxide.

SECTION 11 : Toxicological information

Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 11.18.2014

Page 5 of 7

Aluminum Metal Strips

Acute Toxicity:	
Oral:	LD50 rat >15900 mg/kg bw
Chronic Toxicity: No additional information.	
Corrosion Irritation: No additional information.	
Sensitization:	No additional information.
Single Target Organ (STOT):	No additional information.
Numerical Measures:	No additional information.
Carcinogenicity:	No additional information.
Mutagenicity:	No additional information.
Reproductive Toxicity:	No additional information.

SECTION 12 : Ecological information

Ecotoxicity

LC50 Fish: Ctenopharyngodon idella (Grass carp, white amur) [AI 7429-90-5]: 260 ug/L/96 hr

LC50 Crustacea: Daphnia magna (Water flea) [AI 7429-90-5]: 2.6 mg/L/24 hr

LC50 Fish: Oncorhynchus mykiss (Rainbow trout) [AI 7429-90-5]: 120 ug/L/96 hr; static

Persistence and degradability:

Bioaccumulative potential: Birds and mammals are most likely exposed through dietary ingestion of soil or Al-contaminated foods.

Mobility in soil:

Other adverse effects:

SECTION 13 : Disposal considerations

Waste disposal recommendations:

Product/containers must not be disposed together with household garbage. Do not allow product to reach sewage system or open water. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Consult federal state/ provincial and local regulations regarding the proper disposal of waste material that may incorporate some amount of this product.

SECTION 14 : Transport information

UN-Number

Not Regulated.

UN proper shipping name

Not Regulated.

Transport hazard class(es)

Packing group: Not Regulated

Environmental hazard:

Transport in bulk:

Special precautions for user:

Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 11.18.2014

Page 6 of 7

Aluminum Metal Strips

SECTION 15 : Regulatory information

United States (USA)

SARA Section 311/312 (Specific toxic chemical listings):

Reactive

SARA Section 313 (Specific toxic chemical listings):

7429-90-5 Aluminum (fume or dust)

RCRA (hazardous waste code):

None of the ingredients is listed

TSCA (Toxic Substances Control Act):

All ingredients are listed.

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act):

None of the ingredients is listed

Proposition 65 (California):

Chemicals known to cause cancer:

None of the ingredients is listed

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed

Chemicals known to cause developmental toxicity:

None of the ingredients is listed

Canada

Canadian Domestic Substances List (DSL):

All ingredients are listed.

Canadian NPRI Ingredient Disclosure list (limit 0.1%):

None of the ingredients is listed

Canadian NPRI Ingredient Disclosure list (limit 1%):

7429-90-5 Aluminum, elemental

SECTION 16 : Other information

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations. Note: The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the user to comply with all applicable laws and regulations applicable to this material.

GHS Full Text Phrases:

Abbreviations and acronyms:

Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 11.18.2014

Page 7 of 7

Aluminum Metal Strips

IMDG: International Maritime Code for Dangerous Goods
PNEC: Predicted No-Effect Concentration (REACH)
CFR: Code of Federal Regulations (USA)
SARA: Superfund Amendments and Reauthorization Act (USA)
RCRA: Resource Conservation and Recovery Act (USA)
TSCA: Toxic Substances Control Act (USA)
NPRI: National Pollutant Release Inventory (Canada)
DOT: US Department of Transportation
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
DNEL: Derived No-Effect Level (REACH)

Effective date : 11.18.2014

Last updated : 03.19.2015

SAFETY DATA SHEET

Version 6.4
Revision Date 01/15/2020
Print Date 07/25/2020**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Antimony

Product Number : 266329
Brand : Aldrich
CAS-No. : 7440-36-0**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheetCompany : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATESTelephone : +1 314 771-5765
Fax : +1 800 325-5052**1.4 Emergency telephone number**Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**Acute toxicity, Oral (Category 3), H301
Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335
For the full text of the H-Statements mentioned in this Section, see Section 16.**2.2 GHS Label elements, including precautionary statements**

Pictogram



Signal word : Danger

Hazard statement(s)

H301 : Toxic if swallowed.
H335 : May cause respiratory irritation.

Precautionary statement(s)	
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: Sb
Molecular weight	: 121.76 g/mol
CAS-No.	: 7440-36-0
EC-No.	: 231-146-5

Component	Classification	Concentration
Antimony		
	Acute Tox. 3; STOT SE 3; H301, H335	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Antimony oxide
Not combustible.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Avoid contact with skin and eyes. Avoid formation of dust and aerosols.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Air sensitive. Moisture sensitive. Handle and store under inert gas. Keep in a dry place.

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Antimony	7440-36-0	TWA	0.5 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	0.5 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.5 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Upper Respiratory Tract irritation Skin irritation		
		PEL	0.5 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N99 (US) or type P2 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---|--|
| a) Appearance | Form: powder |
| b) Odour | No data available |
| c) Odour Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: 630 °C (1166 °F) - lit. |
| f) Initial boiling point and boiling range | 1,635 °C 2,975 °F - lit. |
| g) Flash point | ()Not applicable |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | The product is not flammable. |
| j) Upper/lower flammability or explosive limits | No data available |
| k) Vapour pressure | No data available |
| l) Vapour density | No data available |
| m) Relative density | 6.69 g/cm ³ at 25 °C (77 °F) |
| n) Water solubility | No data available |
| o) Partition coefficient: | Not applicable for inorganic substances |

n-octanol/water

- p) Auto-ignition temperature No data available
- q) Decomposition temperature No data available
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Antimony oxide

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 100 mg/kg

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: CC4025000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC50 - Cyprinodon variegatus (sheepshead minnow) - 6.2 - 8.3 mg/l
- 96.0 h
Remarks: No data available

12.2 Persistence and degradability

Biodegradability Result: - According to the results of tests of biodegradability this product is not readily biodegradable.
Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information**DOT (US)**

UN number: 2871 Class: 6.1 Packing group: III
Proper shipping name: Antimony powder
Reportable Quantity (RQ): 5000 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 2871 Class: 6.1 Packing group: III EMS-No: F-A, S-A
Proper shipping name: ANTIMONY POWDER
Marine pollutant : yes

IATA

UN number: 2871 Class: 6.1 Packing group: III
Proper shipping name: Antimony powder

SECTION 15: Regulatory information**SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Antimony	7440-36-0	2007-07-01

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Antimony	7440-36-0	2007-07-01

	CAS-No.	Revision Date
Antimony		

7440-36-0 2007-07-01

New Jersey Right To Know Components

Antimony

CAS-No.
7440-36-0

Revision Date
2007-07-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Further information

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.


The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.4

Revision Date: 01/15/2020

Print Date: 07/25/2020



Health	3
Fire	1
Reactivity	2
Personal Protection	E

Material Safety Data Sheet

Arsenic MSDS

Section 1: Chemical Product and Company Identification

Product Name: Arsenic

Catalog Codes: SLA1006

CAS#: 7440-38-2

RTECS: CG0525000

TSCA: TSCA 8(b) inventory: Arsenic

CI#: Not applicable.

Synonym:

Chemical Name: Arsenic

Chemical Formula: As

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Arsenic	7440-38-2	100

Toxicological Data on Ingredients: Arsenic: ORAL (LD50): Acute: 763 mg/kg [Rat]. 145 mg/kg [Mouse].

Section 3: Hazards Identification

Potential Acute Health Effects:

Very hazardous in case of ingestion, of inhalation. Slightly hazardous in case of skin contact (irritant), of eye contact (irritant).

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Classified A1 (Confirmed for human.) by ACGIH. **MUTAGENIC EFFECTS:** Not available.

TERATOGENIC EFFECTS: Not available. **DEVELOPMENTAL TOXICITY:** Not available. The substance is toxic to kidneys, lungs, the nervous system, mucous membranes. Repeated or prolonged exposure to the substance can produce target organs damage.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: Not available.

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: Some metallic oxides.

Fire Hazards in Presence of Various Substances: Flammable in presence of open flames and sparks, of heat, of oxidizing materials.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards:

Material in powder form, capable of creating a dust explosion. When heated to decomposition it emits highly toxic fumes.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill: Use appropriate tools to put the spilled solid in a convenient waste disposal container.

Large Spill:

Use a shovel to put the material into a convenient waste disposal container. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Keep locked up.. Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe dust. Wear suitable

protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents, acids, moisture.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area.

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 0.01 from ACGIH (TLV) [United States] [1995] Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid. (Lustrous solid.)

Odor: Not available.

Taste: Not available.

Molecular Weight: 74.92 g/mole

Color: Silvery.

pH (1% soln/water): Not applicable.

Boiling Point: Not available.

Melting Point: Sublimation temperature: 615°C (1139°F)

Critical Temperature: Not available.

Specific Gravity: 5.72 (Water = 1)

Vapor Pressure: Not applicable.

Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Insoluble in cold water, hot water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Not available.

Incompatibility with various substances: Reactive with oxidizing agents, acids, moisture.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity: Not available.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Inhalation. Ingestion.

Toxicity to Animals: Acute oral toxicity (LD50): 145 mg/kg [Mouse].

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified A1 (Confirmed for human.) by ACGIH. Causes damage to the following organs: kidneys, lungs, the nervous system, mucous membranes.

Other Toxic Effects on Humans:

Very hazardous in case of ingestion, of inhalation. Slightly hazardous in case of skin contact (irritant).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are as toxic as the original product.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Section 14: Transport Information

DOT Classification: CLASS 6.1: Poisonous material.

Identification: : Arsenic UNNA: UN1558 PG: II

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information

Federal and State Regulations:

California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Arsenic California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Arsenic Pennsylvania RTK: Arsenic Massachusetts RTK: Arsenic TSCA 8(b) inventory: Arsenic

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications:**WHMIS (Canada):**

CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC). CLASS D-2A: Material causing other toxic effects (VERY TOXIC).

DSCL (EEC):

R22- Harmful if swallowed. R45- May cause cancer.

HMIS (U.S.A.):

Health Hazard: 3

Fire Hazard: 1

Reactivity: 2

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 3

Flammability: 1

Reactivity: 2

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Safety glasses.

Section 16: Other Information**References:**

-Hawley, G.G.. The Condensed Chemical Dictionary, 11e ed., New York N.Y., Van Nostrand Reinold, 1987. -Liste des produits purs tératogènes, mutagènes, cancérogènes. Répertoire toxicologique de la Commission de la Santé et de la Sécurité du Travail du Québec. -Material safety data sheet emitted by: la Commission de la Santé et de la Sécurité du Travail du Québec. -SAX, N.I. Dangerous Properties of Industrial Materials. Toronto, Van Nostrand Reinold, 6e ed. 1984. -The Sigma-Aldrich Library of Chemical Safety Data, Edition II. -Guide de la loi et du règlement sur le transport des marchandises dangereuses au Canada. Centre de conformité international Ltée. 1986.

Other Special Considerations: Not available.

Created: 10/09/2005 04:16 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.

SAFETY DATA SHEET

Version 4.10
Revision Date 08/10/2016
Print Date 06/22/2019

1. PRODUCT AND COMPANY IDENTIFICATION**1.1 Product identifiers**

Product name : Cadmium

Product Number : 265330
Brand : Aldrich
Index-No. : 048-002-00-0

CAS-No. : 7440-43-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Acute toxicity, Inhalation (Category 2), H330
Germ cell mutagenicity (Category 2), H341
Carcinogenicity (Category 1B), H350
Reproductive toxicity (Category 2), H361
Specific target organ toxicity - repeated exposure (Category 1), H372
Acute aquatic toxicity (Category 1), H400
Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H330 Fatal if inhaled.
H341 Suspected of causing genetic defects.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284	Wear respiratory protection.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula	: Cd
Molecular weight	: 112.41 g/mol
CAS-No.	: 7440-43-9
EC-No.	: 231-152-8
Index-No.	: 048-002-00-0

Hazardous components

Component	Classification	Concentration
Cadmium Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)		
	Acute Tox. 2; Muta. 2; Carc. 1B; Repr. 2; STOT RE 1; Aquatic Acute 1; Aquatic Chronic 1; H330, H341, H350, H361, H372, H410	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed
No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Air sensitive.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
	Remarks	Substance listed; for more information see OSHA document 1910.1027		
Cadmium	7440-43-9	TWA	0.1 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.5-1970 This standard applies to any operations or sectors for which the		

		Cadmium standard, 1910.1027, is stayed or otherwise not in effect.		
		TWA	0.2 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.5-1970 This standard applies to any operations or sectors for which the Cadmium standard, 1910.1027, is stayed or otherwise not in effect.		
		CEIL	0.3 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.5-1970 This standard applies to any operations or sectors for which the Cadmium standard, 1910.1027, is stayed or otherwise not in effect.		
		CEIL	0.6 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.5-1970 This standard applies to any operations or sectors for which the Cadmium standard, 1910.1027, is stayed or otherwise not in effect.		
		Potential Occupational Carcinogen See Appendix A		
		TWA	0.01 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Kidney damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Suspected human carcinogen varies		
		TWA	0.002 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Kidney damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Suspected human carcinogen varies		
		PEL	0.005 mg/m3	OSHA Specifically Regulated Chemicals/Carcinogens
		1910.1027 This standard applies to all occupational exposures to cadmium and cadmium compounds, in all forms, and in all industries covered by the Occupational Safety and Health Act, except the construction-related industries, which are covered under 29 CFR 1926.63. OSHA specifically regulated carcinogen		
		PEL	0.005 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		see Sections 1532 & 5207		

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Cadmium	7440-43-9	cadmium	5 µg/l	In blood	ACGIH - Biological Exposure Indices (BEI)
	Remarks	Not critical			
		cadmium	5µg/g creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
		Not critical			

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- | | |
|--|---|
| a) Appearance | Form: granular
Colour: light grey |
| b) Odour | odourless |
| c) Odour Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: 320.9 °C (609.6 °F) - lit. |
| f) Initial boiling point and boiling range | 765 °C (1,409 °F) - lit. |
| g) Flash point | Not applicable |

- | | | |
|----|--|---|
| h) | Evaporation rate | No data available |
| i) | Flammability (solid, gas) | No data available |
| j) | Upper/lower flammability or explosive limits | No data available |
| k) | Vapour pressure | No data available |
| l) | Vapour density | No data available |
| m) | Relative density | 8.65 g/cm ³ at 25 °C (77 °F) |
| n) | Water solubility | 0.0023 g/l at 20 °C (68 °F) |
| o) | Partition coefficient: n-octanol/water | No data available |
| p) | Auto-ignition temperature | No data available |
| q) | Decomposition temperature | No data available |
| r) | Viscosity | No data available |
| s) | Explosive properties | No data available |
| t) | Oxidizing properties | No data available |

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Oxidizing agents, acids

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Cadmium/cadmium oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 2,330 mg/kg

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: 1 - Group 1: Carcinogenic to humans (Cadmium)

NTP: Known to be human carcinogen The reference note has been added by TD based on the background information of the NTP. (Cadmium)

OSHA: OSHA specifically regulated carcinogen (Cadmium)

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: EU9800000

Damage to the lungs., Kidney injury may occur., prolonged or repeated exposure can cause:, Vomiting, Diarrhoea, Lung irritation

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION**12.1 Toxicity**

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 0.001 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 0.024 mg/l - 48 h

Toxicity to algae static test EC50 - Selenastrum capricornutum (green algae) - 0.023 mg/l - 72 h (OECD Test Guideline 201)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Bioaccumulation Oncorhynchus mykiss (rainbow trout) - 72 d - 1.27 µg/l

Bioconcentration factor (BCF): 55

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Very toxic to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3288 Class: 6.1 Packing group: II
Proper shipping name: Toxic solid, inorganic, n.o.s. (Cadmium)
Reportable Quantity (RQ): 10 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 3288 Class: 6.1 Packing group: II EMS-No: F-A, S-A
Proper shipping name: TOXIC SOLID, INORGANIC, N.O.S. (Cadmium)
Marine pollutant:yes

IATA

UN number: 3288 Class: 6.1 Packing group: II
Proper shipping name: Toxic solid, inorganic, n.o.s. (Cadmium)

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Cadmium	7440-43-9	2007-07-01

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Cadmium	7440-43-9	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Cadmium	7440-43-9	2007-07-01

New Jersey Right To Know Components

	CAS-No.	Revision Date
Cadmium	7440-43-9	2007-07-01

California Prop. 65 Components

WARNING! This product contains a chemical known to the State of California to cause cancer.

	CAS-No.	Revision Date
Cadmium	7440-43-9	2009-02-01

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

	CAS-No.	Revision Date
Cadmium	7440-43-9	2009-02-01

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
H330	Fatal if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

HMIS Rating

Health hazard:	4
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

NFPA Rating

Health hazard:	4
Fire Hazard:	0
Reactivity Hazard:	0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 4.10

Revision Date: 08/10/2016

Print Date: 06/22/2019

SAFETY DATA SHEET

Version 6.3
Revision Date 04/05/2019
Print Date 06/28/2019**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Chromium

Product Number : 374849
Brand : Aldrich
CAS-No. : 7440-47-3**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheetCompany : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATESTelephone : +1 314 771-5765
Fax : +1 800 325-5052**1.4 Emergency telephone number**

Emergency Phone # : +1-703-527-3887

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Not a hazardous substance or mixture.

2.2 GHS Label elements, including precautionary statements

Not a hazardous substance or mixture.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none**SECTION 3: Composition/information on ingredients****3.1 Substances**Formula : Cr
Molecular weight : 52.00 g/mol
CAS-No. : 7440-47-3
EC-No. : 231-157-5

Component	Classification	Concentration
-----------	----------------	---------------

Chromium	
	<= 100 %

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

In case of skin contact

Wash off with soap and plenty of water.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Chromium oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapours, mist or gas.
For personal protection see section 8.

6.2 Environmental precautions

No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Storage class (TRGS 510): 13: Non Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Chromium	7440-47-3	PEL	0.5 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
	Remarks	see Sections 1532.2, 5206 & 8359		
		TWA	1 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.5 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		Upper Respiratory Tract irritation Skin irritation Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Not classifiable as a human carcinogen varies		

8.2 Exposure controls

Appropriate engineering controls

General industrial hygiene practice.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|--------------------|-----------------------------------|
| a) Appearance | Form: chips
Colour: light grey |
| b) Odour | odourless |
| c) Odour Threshold | No data available |
| d) pH | No data available |

e) Melting point/freezing point	Melting point/range: 1,857 °C (3,375 °F) - lit.
f) Initial boiling point and boiling range	2,672 °C 4,842 °F - lit.
g) Flash point	()Not applicable
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapour pressure	No data available
l) Vapour density	No data available
m) Relative density	7.14 g/mL at 25 °C (77 °F)
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong acids, Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Chromium oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: GB4200000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Aldrich - 374849

Page 6 of 8

Toxicity to fish LC50 - Cyprinus carpio (Carp) - 14.3 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 0.07 mg/l - 48 h

12.2 Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

Bioaccumulation Oncorhynchus mykiss (rainbow trout) - 30 d
- 50 µg/l(Chromium)

Bioconcentration factor (BCF): 1.03 - 1.22

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s. ()
Reportable Quantity (RQ): 5000 lbs
Reportable Quantity (RQ): 10 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. ()
Marine pollutant : yes

IATA

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s. ()

Further information

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

SECTION 15: Regulatory information**SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Chromium	7440-47-3	2007-07-01

SARA 311/312 Hazards

Chronic Health Hazard

Reportable Quantity : D007 lbs

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Chromium	7440-47-3	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Chromium	7440-47-3	2007-07-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information**Further information**

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.3

Revision Date: 04/05/2019

Print Date: 06/28/2019

SAFETY DATA SHEET

Version 6.1
Revision Date 03/12/2019
Print Date 06/22/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Copper

Product Number : 31284
Brand : Aldrich
CAS-No. : 7440-50-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

2.2 GHS Label elements, including precautionary statements

Not a hazardous substance or mixture.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : Cu
Molecular weight : 63.55 g/mol
CAS-No. : 7440-50-8
EC-No. : 231-159-6

Component	Classification	Concentration
-----------	----------------	---------------

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Store under inert gas. Air sensitive.

Storage class (TRGS 510): 13: Non Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Copper,	7440-50-8	TWA	1 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Irritation Gastrointestinal metal fume fever		
		TWA	0.2 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		Irritation Gastrointestinal metal fume fever		

		TWA	1 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	1 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	1 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.1 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	0.1 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

General industrial hygiene practice.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---|--|
| a) Appearance | Form: Wire
Colour: light red |
| b) Odour | No data available |
| c) Odour Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: 1,083.4 °C (1,982.1 °F) |
| f) Initial boiling point and boiling range | 2,567 °C 4,653 °F |
| g) Flash point | ()No data available |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | No data available |
| k) Vapour pressure | No data available |
| l) Vapour density | No data available |
| m) Relative density | 8.940 g/cm ³ |
| n) Water solubility | No data available |
| o) Partition coefficient: n-octanol/water | No data available |
| p) Auto-ignition temperature | No data available |
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | No data available |

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong acids, Strong oxidizing agents, Acid chlorides, Halogens

10.6 Hazardous decomposition products

Other decomposition products - No data available

Hazardous decomposition products formed under fire conditions. - Copper oxides

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

LD50 Intraperitoneal - Mouse - 3.5 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: GL5325000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information**DOT (US)**

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

SECTION 15: Regulatory information**SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

No SARA Hazards

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

Copper,	CAS-No. 7440-50-8	Revision Date 1993-02-16
---------	----------------------	-----------------------------

Copper,	CAS-No. 7440-50-8	Revision Date 1993-02-16
---------	----------------------	-----------------------------

New Jersey Right To Know Components

Copper,	CAS-No. 7440-50-8	Revision Date 1993-02-16
---------	----------------------	-----------------------------

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information**Further information**

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.1

Revision Date: 03/12/2019

Print Date: 06/22/2019

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 6.0 Revision Date 10.11.2016

Print Date 02.08.2019

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Iron Metal Clinical

Product Number : NIST937

Brand : Sigma-Aldrich

REACH No. : A registration number is not available for this substance as the substance or its uses are exempted from registration, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.2 Label elements

2.3 Other hazards - none

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

4.1 Description of first aid measures

No data available

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

- 5.1 **Extinguishing media**
No data available
- 5.2 **Special hazards arising from the substance or mixture**
No data available
- 5.3 **Advice for firefighters**
No data available
- 5.4 **Further information**
No data available

SECTION 6: Accidental release measures

- 6.1 **Personal precautions, protective equipment and emergency procedures**
For personal protection see section 8.
- 6.2 **Environmental precautions**
No data available
- 6.3 **Methods and materials for containment and cleaning up**
No data available
- 6.4 **Reference to other sections**
For disposal see section 13.

SECTION 7: Handling and storage

- 7.1 **Precautions for safe handling**
For precautions see section 2.2.
- 7.2 **Conditions for safe storage, including any incompatibilities**
No data available
- 7.3 **Specific end use(s)**
Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

- 8.1 **Control parameters**
- 8.2 **Exposure controls**
No data available

SECTION 9: Physical and chemical properties

- 9.1 **Information on basic physical and chemical properties**
 - a) Appearance No data available
 - b) Odour No data available
 - c) Odour Threshold No data available
 - d) pH No data available
 - e) Melting point/freezing point No data available
 - f) Initial boiling point and boiling range No data available
 - g) Flash point No data available
 - h) Evaporation rate No data available
 - i) Flammability (solid, gas) No data available

j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
l)	Vapour density	No data available
m)	Relative density	No data available
n)	Water solubility	No data available
o)	Partition coefficient: n-octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects


Acute toxicity

Skin corrosion/irritation

Serious eye damage/eye irritation

Respiratory or skin sensitisation

Germ cell mutagenicity



Health	1
Fire	0
Reactivity	0
Personal Protection	E

Material Safety Data Sheet

Lead MSDS

Section 1: Chemical Product and Company Identification

Product Name: Lead

Catalog Codes: SLL1291, SLL1669, SLL1081, SLL1459, SLL1834

CAS#: 7439-92-1

RTECS: OF7525000

TSCA: TSCA 8(b) inventory: Lead

CI#: Not available.

Synonym: Lead Metal, granular; Lead Metal, foil; Lead Metal, sheet; Lead Metal, shot

Chemical Name: Lead

Chemical Formula: Pb

Contact Information:

Sciencelab.com, Inc.
14025 Smith Rd.
Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:
1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Lead	7439-92-1	100

Toxicological Data on Ingredients: Lead LD50: Not available. LC50: Not available.

Section 3: Hazards Identification

Potential Acute Health Effects: Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects:

Slightly hazardous in case of skin contact (permeator). **CARCINOGENIC EFFECTS:** Classified A3 (Proven for animal.) by ACGIH, 2B (Possible for human.) by IARC. **MUTAGENIC EFFECTS:** Not available. **TERATOGENIC EFFECTS:** Not available. **DEVELOPMENTAL TOXICITY:** Not available. The substance may be toxic to blood, kidneys, central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation: Not available.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: Not available.

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: Some metallic oxides.

Fire Hazards in Presence of Various Substances: Non-flammable in presence of open flames and sparks, of shocks, of heat.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards: When heated to decomposition it emits highly toxic fumes of lead.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill:

Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Keep locked up.. Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe dust. Wear suitable

protective clothing. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area.

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 0.05 (mg/m³) from ACGIH (TLV) [United States] TWA: 0.05 (mg/m³) from OSHA (PEL) [United States] TWA: 0.03 (mg/m³) from NIOSH [United States] TWA: 0.05 (mg/m³) [Canada] Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid. (Metal solid.)

Odor: Not available.

Taste: Not available.

Molecular Weight: 207.21 g/mole

Color: Bluish-white. Silvery. Gray

pH (1% soln/water): Not applicable.

Boiling Point: 1740°C (3164°F)

Melting Point: 327.43°C (621.4°F)

Critical Temperature: Not available.

Specific Gravity: 11.3 (Water = 1)

Vapor Pressure: Not applicable.

Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Insoluble in cold water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Incompatible materials, excess heat

Incompatibility with various substances: Reactive with oxidizing agents.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Can react vigorously with oxidizing materials. Incompatible with sodium carbide, chlorine trifluoride, trioxane + hydrogen peroxide, ammonium nitrate, sodium azide, disodium acetylide, sodium acetylide, hot concentrated nitric acid, hot concentrated hydrochloric acid, hot concentrated sulfuric acid, zirconium.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Absorbed through skin. Inhalation. Ingestion.

Toxicity to Animals:

LD50: Not available. LC50: Not available.

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified A3 (Proven for animal.) by ACGIH, 2B (Possible for human.) by IARC. May cause damage to the following organs: blood, kidneys, central nervous system (CNS).

Other Toxic Effects on Humans: Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans:

Acute Potential: Skin: Lead metal granules or dust: May cause skin irritation by mechanical action. Lead metal foil, shot or sheets: Not likely to cause skin irritation Eyes: Lead metal granules or dust: Can irritate eyes by mechanical action. Lead metal foil, shot or sheets: No hazard. Will not cause eye irritation. Inhalation: In an industrial setting, exposure to lead mainly occurs from inhalation of dust or fumes. Lead dust or fumes: Can irritate the upper respiratory tract (nose, throat) as well as the bronchi and lungs by mechanical action. Lead dust can be absorbed through the respiratory system. However, inhaled lead does not accumulate in the lungs. All of an inhaled dose is eventually absorbed or transferred to the gastrointestinal tract. Inhalation effects of exposure to fumes or dust of inorganic lead may not develop quickly. Symptoms may include metallic taste, chest pain, decreased physical fitness, fatigue, sleep disturbance, headache, irritability, reduces memory, mood and personality changes, aching bones and muscles, constipation, abdominal pains, decreasing appetite. Inhalation of large amounts may lead to ataxia, delirium, convulsions/seizures, coma, and death. Lead metal foil, shot, or sheets: Not an inhalation hazard unless metal is heated. If metal is heated, fumes will be released. Inhalation of these fumes may cause "fume metal fever", which is characterized by flu-like symptoms. Symptoms may include metallic taste, fever, nausea, vomiting, chills, cough, weakness, chest pain, generalized muscle pain/aches, and increased white blood cell count. Ingestion: Lead metal granules or dust: The symptoms of lead poisoning include abdominal pain or cramps (lead colic), spasms, nausea, vomiting, headache, muscle weakness, hallucinations, distorted perceptions, "lead line" on the gums, metallic taste, loss of appetite, insomnia, dizziness and other symptoms similar to that of inhalation. Acute poisoning may result in high lead levels in the blood and urine, shock, coma and death in extreme cases. Lead metal foil, shot or sheets: Not an ingestion hazard for usual industrial handling.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations**Waste Disposal:**

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: Not a DOT controlled material (United States).

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

Section 15: Other Regulatory Information**Federal and State Regulations:**

California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Lead California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Lead California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Lead California prop. 65 (no significant risk level): Lead: 0.0005 mg/day (value) California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Lead California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Lead Connecticut hazardous material survey.: Lead Illinois toxic substances disclosure to employee act: Lead Illinois chemical safety act: Lead New York release reporting list: Lead Rhode Island RTK hazardous substances: Lead Pennsylvania RTK: Lead

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada): CLASS D-2A: Material causing other toxic effects (VERY TOXIC).

DSCL (EEC):

R20/22- Harmful by inhalation and if swallowed. R33- Danger of cumulative effects. R61- May cause harm to the unborn child. R62- Possible risk of impaired fertility. S36/37- Wear suitable protective clothing and gloves. S44- If you feel unwell, seek medical advice (show the label when possible). S53- Avoid exposure - obtain special instructions before use.

HMIS (U.S.A.):

Health Hazard: 1

Fire Hazard: 0

Reactivity: 0

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 1

Flammability: 0

Reactivity: 0

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Safety glasses.

Section 16: Other Information

References: Not available.

Other Special Considerations: Not available.

Created: 10/10/2005 08:21 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.

SAFETY DATA SHEET

Version 6.1
Revision Date 05/28/2017
Print Date 06/22/2019

1. PRODUCT AND COMPANY IDENTIFICATION**1.1 Product identifiers**

Product name : Magnesium

Product Number : 254118
Brand : Aldrich
Index-No. : 012-001-00-3

CAS-No. : 7439-95-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Pyrophoric solids (Category 1), H250

Substances and mixtures, which in contact with water, emit flammable gases (Category 1), H260

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H250

Catches fire spontaneously if exposed to air.

H260

In contact with water releases flammable gases which may ignite spontaneously.

Precautionary statement(s)

P210

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P222

Do not allow contact with air.

P223

Do not allow contact with water.

P231 + P232	Handle under inert gas. Protect from moisture.
P280	Wear protective gloves/ eye protection/ face protection.
P335 + P334	Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P402 + P404	Store in a dry place. Store in a closed container.
P422	Store contents under inert gas.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Combustible dust

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula	: Mg
Molecular weight	: 24.31 g/mol
CAS-No.	: 7439-95-4
EC-No.	: 231-104-6
Index-No.	: 012-001-00-3

Hazardous components

Component	Classification	Concentration
Magnesium		
	Pyr. Sol. 1; Water-react. 1; H250, H260	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Dry powder

- 5.2 Special hazards arising from the substance or mixture**
Magnesium oxide
- 5.3 Advice for firefighters**
Wear self-contained breathing apparatus for firefighting if necessary.
- 5.4 Further information**
No data available

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures**
Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.
For personal protection see section 8.
- 6.2 Environmental precautions**
Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
- 6.3 Methods and materials for containment and cleaning up**
Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Do not flush with water. Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13).
- 6.4 Reference to other sections**
For disposal see section 13.

7. HANDLING AND STORAGE

- 7.1 Precautions for safe handling**
Further processing of solid materials may result in the formation of combu formation should be taken into consideration before additional processing
Provide appropriate exhaust ventilation at places where dust is formed.Keep away from sources of ignition - No smoking.
For precautions see section 2.2.
- 7.2 Conditions for safe storage, including any incompatibilities**
Keep container tightly closed in a dry and well-ventilated place.
Never allow product to get in contact with water during storage.

Air and moisture sensitive. Store under inert gas.
- 7.3 Specific end use(s)**
Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
Components with workplace control parameters
Contains no substances with occupational exposure limit values.
Hazardous components without workplace control parameters
- 8.2 Exposure controls**
Appropriate engineering controls
Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Personal protective equipment
Eye/face protection
Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Skin protection
Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Protective gloves against thermal risks

Full contact
Material: Nitrile rubber
Minimum layer thickness: 0.11 mm
Break through time: 480 min
Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact
Material: Nitrile rubber
Minimum layer thickness: 0.11 mm
Break through time: 480 min
Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Flame retardant protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If th full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- | | |
|---|---|
| a) Appearance | Form: chips |
| b) Odour | No data available |
| c) Odour Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: 648 °C (1198 °F) - lit. |
| f) Initial boiling point and boiling range | 1,090 °C (1,994 °F) - lit. |
| g) Flash point | ()No data available |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | May form combustible dust concentrations in air. |
| j) Upper/lower flammability or explosive limits | No data available |
| k) Vapour pressure | 1 hPa at 621 °C (1150 °F) |
| l) Vapour density | No data available |
| m) Relative density | 1.74 g/cm ³ at 25 °C (77 °F) |
| n) Water solubility | No data available |
| o) Partition coefficient: n-octanol/water | No data available |
| p) Auto-ignition temperature | The substance or mixture is pyrophoric with the category 1. |

- q) Decomposition temperature No data available
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available

9.2 Other safety information
No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Reacts violently with water.

10.4 Conditions to avoid

Exposure to moisture

10.5 Incompatible materials

Strong oxidizing agents, acids, Acid chlorides, Halogens

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Magnesium oxide

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available(Magnesium)

Inhalation: No data available(Magnesium)

Dermal: No data available(Magnesium)

No data available(Magnesium)

Skin corrosion/irritation

No data available(Magnesium)

Serious eye damage/eye irritation

No data available(Magnesium)

Respiratory or skin sensitisation

No data available(Magnesium)

Germ cell mutagenicity

No data available(Magnesium)

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available(Magnesium)

No data available(Magnesium)

Specific target organ toxicity - single exposure

No data available(Magnesium)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available(Magnesium)

Additional Information

RTECS: OM2100000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(Magnesium)

Liver - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence(Magnesium)

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available(Magnesium)

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

Aldrich- 254118

UN number: 1869 Class: 4.1 Packing group: III
Proper shipping name: Magnesium
Poison Inhalation Hazard: No

IMDG

UN number: 1869 Class: 4.1 Packing group: III EMS-No: F-G, S-G
Proper shipping name: MAGNESIUM

IATA

UN number: 1869 Class: 4.1 Packing group: III
Proper shipping name: Magnesium

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Reactivity Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Magnesium	7439-95-4	1993-04-24

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Magnesium	7439-95-4	1993-04-24

New Jersey Right To Know Components

	CAS-No.	Revision Date
Magnesium	7439-95-4	1993-04-24

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H250 Catches fire spontaneously if exposed to air.
H260 In contact with water releases flammable gases which may ignite spontaneously.

HMIS Rating

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical Hazard 2

NFPA Rating

Health hazard: 2
Fire Hazard: 0
Reactivity Hazard: 2

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956
Version: 6.1

Revision Date: 05/28/2017

Print Date: 06/22/2019

SAFETY DATA SHEET

Version 6.3
Revision Date 04/15/2019
Print Date 06/28/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Manganese

Product Number : 266167
Brand : Aldrich
CAS-No. : 7439-96-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Short-term (acute) aquatic hazard (Category 2), H401

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram none

Signal word none

Hazard statement(s)
H401 Toxic to aquatic life.

Precautionary statement(s)
P273 Avoid release to the environment.
P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : Mn
Molecular weight : 54.94 g/mol
CAS-No. : 7439-96-5
EC-No. : 231-105-1

Component	Classification	Concentration
Manganese	Aquatic Acute 2; H401	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Manganese/manganese oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Moisture sensitive. Handle and store under inert gas.

Storage class (TRGS 510): 13: Non Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Manganese	7439-96-5	C	5 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	Remarks	Ceiling limit is to be determined from breathing-zone air		

		samples.		
		TWA	1 mg/m ³	USA. NIOSH Recommended Exposure Limits
		ST	3 mg/m ³	USA. NIOSH Recommended Exposure Limits
		C	5 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Ceiling limit is to be determined from breathing-zone air samples.		
		PEL	0.2 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	3 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		TWA	0.1 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		Central Nervous System impairment Not classifiable as a human carcinogen varies		
		TWA	0.02 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		Central Nervous System impairment Not classifiable as a human carcinogen varies		

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: chips Colour: grey, brown, silver
b) Odour	odourless
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 1,244 °C (2,271 °F) - lit.
f) Initial boiling point and boiling range	1,962 °C 3,564 °F - lit.
g) Flash point	()Not applicable
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapour pressure	No data available
l) Vapour density	No data available
m) Relative density	7.3 g/mL at 25 °C (77 °F)
n) Water solubility	0.0007 g/l at 20 °C (68 °F)
o) Partition coefficient: n-octanol/water	Not applicable for inorganic substances
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Avoid moisture.

10.5 Incompatible materials

acids, Halogens, Bases, Phosphorus, Sulphur oxides, Hydrogen peroxide, Oxidizing agents, Nitric acid, Sodium Hydroxide, Carbon dioxide (CO₂), Nitryl Flouride, Steam

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Manganese/manganese oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - female - > 2,000 mg/kg

(OECD Test Guideline 420)

LC50 Inhalation - Rat - male and female - 4 h - > 5.14 mg/l

(OECD Test Guideline 403)

Dermal: No data available

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation - 72 h

(OECD Test Guideline 405)

Respiratory or skin sensitisation

- Mouse

Result: Does not cause skin sensitisation.

(OECD Test Guideline 429)

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

Men exposed to manganese dusts showed a decrease in fertility. Chronic manganese poisoning primarily involves the central nervous system. Early symptoms include languor, sleepiness and weakness in the legs. A stolid mask-like appearance of the face, emotional disturbances such as uncontrollable laughter and a spastic gait with tendency to fall in walking are findings in more advanced cases. High incidence of pneumonia has been found in workers exposed to the dust or fume of some manganese compounds., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish	semi-static test NOEC - <i>Oncorhynchus mykiss</i> (rainbow trout) - 3.6 mg/l - 96 h (OECD Test Guideline 203) Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	Immobilization NOEC - <i>Daphnia magna</i> (Water flea) - 1.6 mg/l - 48 h (OECD Test Guideline 202) Remarks: No toxicity at the limit of solubility
Toxicity to algae	Growth inhibition EC50 - <i>Desmodesmus subspicatus</i> (green algae) - 4.5 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	Respiration inhibition EC50 - Sludge Treatment - 1,000 mg/l - 3 h (OECD Test Guideline 209)

12.2 Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Manganese	7439-96-5	2007-07-01

SARA 311/312 Hazards

Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Manganese	7439-96-5	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Manganese	7439-96-5	2007-07-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Further information

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.


The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.3

Revision Date: 04/15/2019

Print Date: 06/28/2019



Health	3
Fire	0
Reactivity	0
Personal Protection	

Material Safety Data Sheet

Mercury MSDS

Section 1: Chemical Product and Company Identification

Product Name: Mercury

Catalog Codes: SLM3505, SLM1363

CAS#: 7439-97-6

RTECS: OV4550000

TSCA: TSCA 8(b) inventory: Mercury

CI#: Not applicable.

Synonym: Quick Silver; Colloidal Mercury; Metallic Mercury; Liquid Silver; Hydragryum

Chemical Name: Mercury

Chemical Formula: Hg

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Mercury	7439-97-6	100

Toxicological Data on Ingredients: Mercury LD50: Not available. LC50: Not available.

Section 3: Hazards Identification

Potential Acute Health Effects:

Very hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Hazardous in case of skin contact (corrosive, permeator). Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Severe over-exposure can result in death. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Potential Chronic Health Effects:

Hazardous in case of skin contact (permeator). **CARCINOGENIC EFFECTS:** Classified A5 (Not suspected for human.) by ACGIH. 3 (Not classifiable for human.) by IARC. **MUTAGENIC EFFECTS:** Not available. **TERATOGENIC EFFECTS:** Not available. **DEVELOPMENTAL TOXICITY:** Not available. The substance may be toxic to blood, kidneys, liver, brain, peripheral nervous system, central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation.

Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. WARM water MUST be used. Get medical attention immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. **WARNING:** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Non-flammable.

Auto-Ignition Temperature: Not applicable.

Flash Points: Not applicable.

Flammable Limits: Not applicable.

Products of Combustion: Not available.

Fire Hazards in Presence of Various Substances: Not applicable.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions: Not applicable.

Special Remarks on Fire Hazards:

When thrown into mercury vapor, boron phosphodiiodide ignites at once. Flame forms with chlorine jet over mercury surface at 200 deg to 300 deg C. Mercury undergoes hazardous reactions in the presence of heat and sparks or ignition.

Special Remarks on Explosion Hazards:

A violent exothermic reaction or possible explosion occurs when mercury comes in contact with lithium and rubidium. CHLORINE DIOXIDE & LIQUID HG, WHEN MIXED, EXPLODE VIOLENTLY. Mercury and Ammonia can produce an

explosive compound. A mixture of the dry carbonyl and oxygen will explode on vigorous shaking with mercury. Methyl azide in the presence of mercury was shown to be potentially explosive.

Section 6: Accidental Release Measures

Small Spill: Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Large Spill:

Corrosive liquid. Poisonous liquid. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Keep locked up.. Keep container dry. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, metals.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area. Do not store above 25°C (77°F).

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Face shield. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves. Boots.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 0.025 from ACGIH (TLV) [United States] SKIN TWA: 0.05 CEIL: 0.1 (mg/m³) from OSHA (PEL) [United States]
Inhalation TWA: 0.025 (mg/m³) [United Kingdom (UK)] Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Liquid. (Heavy liquid)

Odor: Odorless.

Taste: Not available.

Molecular Weight: 200.59 g/mole

Color: Silver-white

pH (1% soln/water): Not available.

Boiling Point: 356.73°C (674.1°F)

Melting Point: -38.87°C (-38°F)

Critical Temperature: 1462°C (2663.6°F)

Specific Gravity: 13.55 (Water = 1)

Vapor Pressure: Not available.

Vapor Density: 6.93 (Air = 1)

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Very slightly soluble in cold water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Incompatible materials

Incompatibility with various substances: Reactive with oxidizing agents, metals.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Ground mixtures of sodium carbide and mercury, aluminum, lead, or iron can react vigorously. A violent exothermic reaction or possible explosion occurs when mercury comes in contact with lithium and rubidium. Incompatible with boron diiodophosphide; ethylene oxide; metal oxides, metals(aluminum, potassium, lithium, sodium, rubidium); methyl azide; methylsilane, oxygen; oxidants(bromine, peroxyformic acid, chlorine dioxide, nitric acid, tetracarbonylnickel, nitromethane, silver perchlorate, chlorates, sulfuric acid, nitrates,); tetracarbonylnickel, oxygen, acetylinic compounds, ammonia, ethylene oxide, methylsilane, calcium,

Special Remarks on Corrosivity:

The high mobility and tendency to dispersion exhibited by mercury, and the ease with which it forms alloys (amalgam) with many laboratory and electrical contact metals, can cause severe corrosion problems in laboratories. Special precautions: Mercury can attack copper and copper alloy materials.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

LD50: Not available. LC50: Not available.

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human.) by ACGIH. 3 (Not classifiable for human.) by IARC. May cause damage to the following organs: blood, kidneys, liver, brain, peripheral nervous system, central nervous system (CNS).

Other Toxic Effects on Humans:

Very hazardous in case of skin contact (irritant), of ingestion, of inhalation. Hazardous in case of skin contact (corrosive, permeator).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

May affect genetic material. May cause cancer based on animal data. Passes through the placental barrier in animal. May cause adverse reproductive effects (paternal effects- spermatogenesis; effects on fertility - fetotoxicity, post-implantation mortality), and birth defects.

Special Remarks on other Toxic Effects on Humans:

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: Class 8: Corrosive material

Identification: : Mercury UNNA: 2809 PG: III

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information

Federal and State Regulations:

California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Mercury California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Mercury Connecticut hazardous material survey.: Mercury Illinois toxic substances disclosure to employee act: Mercury Illinois chemical safety act: Mercury New York acutely hazardous substances: Mercury Rhode Island RTK hazardous substances: Mercury Pennsylvania RTK: Mercury Minnesota: Mercury Massachusetts RTK: Mercury New Jersey: Mercury New Jersey spill list: Mercury Louisiana spill reporting: Mercury California Director's List of Hazardous Substances.: Mercury TSCA 8(b) inventory: Mercury SARA 313 toxic chemical notification and release reporting: Mercury CERCLA: Hazardous substances.: Mercury: 1 lbs. (0.4536 kg)

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada):

CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC). CLASS D-2A: Material causing other toxic effects (VERY TOXIC). CLASS E: Corrosive liquid.

DSCL (EEC):

R23- Toxic by inhalation. R33- Danger of cumulative effects. R38- Irritating to skin. R41- Risk of serious damage to eyes. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. S2- Keep out of the

reach of children. S7- Keep container tightly closed. S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S39- Wear eye/face protection. S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S46- If swallowed, seek medical advice immediately and show this container or label. S60- This material and its container must be disposed of as hazardous waste. S61- Avoid release to the environment. Refer to special instructions/Safety data sheets.

HMIS (U.S.A.):

Health Hazard: 3

Fire Hazard: 0

Reactivity: 0

Personal Protection:

National Fire Protection Association (U.S.A.):

Health: 3

Flammability: 0

Reactivity: 0

Specific hazard:

Protective Equipment:

Gloves. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Face shield.

Section 16: Other Information

References: Not available.

Other Special Considerations: Not available.

Created: 10/10/2005 08:22 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Nickel

Product Number : 577995

Brand : Aldrich

Index-No. : 028-002-01-4

CAS-No. : 7440-02-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832

Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Skin sensitisation (Category 1), H317

Carcinogenicity (Category 2), H351

Specific target organ toxicity - repeated exposure, Inhalation (Category 1), H372

Acute aquatic toxicity (Category 3), H402

Chronic aquatic toxicity (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram	
Signal word	Danger
Hazard statement(s)	
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.
H412	Harmful to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.

P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula	:	Ni
Molecular weight	:	58.69 g/mol
CAS-No.	:	7440-02-0
EC-No.	:	231-111-4
Index-No.	:	028-002-01-4

Hazardous components

Component	Classification	Concentration
Nickel, powder [particle diameter < 1 mm]	Skin Sens. 1; Carc. 2; STOT RE 1; Aquatic Acute 3; Aquatic Chronic 3; H317, H351, H372, H412	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Handle and store under inert gas. Keep in a dry place.

Storage class (TRGS 510): 4.1B: Flammable solid hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Nickel, powder [particle diameter < 1 mm]	7440-02-0	TWA	1.5 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Dermatitis Pneumoconiosis Not suspected as a human carcinogen		

		PEL	0.5 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		TWA	1 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.015 mg/m ³	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen See Appendix A		

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- a) Appearance Form: powder
 Colour: grey

b) Odour	No data available
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point: 1,455 °C (2,651 °F)
f) Initial boiling point and boiling range	2,730 °C (4,946 °F)
g) Flash point	Not applicable
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapour pressure	1 hPa (1 mmHg) at 1,810 °C (3,290 °F)
l) Vapour density	No data available
m) Relative density	8.9 g/cm ³ at 25 °C (77 °F)
n) Water solubility	insoluble
o) Partition coefficient: n-octanol/water	Not applicable for inorganic substances
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

acids, Oxidizing agents, Sulphur compounds, Hydrogen gas, Oxygen, Methanol, organic solvents, Aluminium, Fluorine, Ammonia

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Nickel/nickel oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - > 9,000 mg/kg
(OECD Test Guideline 401)

Dermal: No data available

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h
(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation
(OECD Test Guideline 405)

Respiratory or skin sensitisation

Germ cell mutagenicity

No data available

Carcinogenicity

Limited evidence of carcinogenicity in animal studies

- IARC: 1 - Group 1: Carcinogenic to humans (Nickel, powder [particle diameter < 1 mm])
2B - Group 2B: Possibly carcinogenic to humans (Nickel, powder [particle diameter < 1 mm])
- IARC: 1 - Group 1: Carcinogenic to humans (Nickel, powder [particle diameter < 1 mm])
2B - Group 2B: Possibly carcinogenic to humans (Nickel, powder [particle diameter < 1 mm])
- NTP: RAHC - Reasonably anticipated to be a human carcinogen (Nickel, powder [particle diameter < 1 mm])
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Inhalation - Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

No data available

Additional Information

Repeated dose toxicity Rat - male and female - Inhalation - LOAEL : 0.0001 mg/l - OECD Test Guideline 451

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - 15.3 mg/l - 96 h

12.2 Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3089 Class: 4.1 Packing group: II
Proper shipping name: Metal powders, flammable, n.o.s.
Reportable Quantity (RQ): 100 lbs
Poison Inhalation Hazard: No

IMDG

IATA

UN number: 3089 Class: 4.1 Packing group: II
Proper shipping name: Metal powder, flammable, n.o.s.

15. REGULATORY INFORMATION

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Nickel, powder [particle diameter < 1 mm]	7440-02-0	2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Nickel, powder [particle diameter < 1 mm]	7440-02-0	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Nickel, powder [particle diameter < 1 mm]	7440-02-0	2007-07-01

California Prop. 65 Components

, which is/are known to the State of California to cause cancer.
For more information go to www.P65Warnings.ca.gov.
Nickel, powder [particle diameter < 1 mm]

CAS-No.
7440-02-0

Revision Date
2007-09-28

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

HMIS Rating

Health hazard:	0
Chronic Health Hazard:	*
Flammability:	1
Physical Hazard	0

NFPA Rating

Health hazard:	0
Fire Hazard:	1
Reactivity Hazard:	0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 4.9

Revision Date: 04/24/2018

Print Date: 06/22/2019

1. PRODUCT AND COMPANY IDENTIFICATION**1.1 Product identifiers**

Product name : Silver

Product Number : 484059

Brand : Aldrich

CAS-No. : 7440-22-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheetCompany : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832

Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word : Warning

Hazard statement(s)

H410 : Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P273 : Avoid release to the environment.

P391 : Collect spillage.

P501 : Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substances**

Formula : Ag

Molecular weight : 107.87 g/mol

CAS-No. : 7440-22-4
EC-No. : 231-131-3

Hazardous components

Component	Classification	Concentration
Silver		
	Aquatic Acute 1; Aquatic Chronic 1; H410	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Air sensitive. Handle and store under inert gas. Keep in a dry place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Silver	7440-22-4	TWA	0.010000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.010000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.100000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Argyria		
		TWA	0.010000 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	0.010000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.010000 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	0.100000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Argyria		
		TWA	0.010000 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	0.1 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Argyria		
		TWA	0.01 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	0.01 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- | | |
|---|---|
| a) Appearance | Form: powder |
| b) Odour | No data available |
| c) Odour Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: 960 °C (1,760 °F) - lit. |
| f) Initial boiling point and boiling range | 2,212 °C (4,014 °F) - lit. |
| g) Flash point | No data available |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | No data available |

k) Vapour pressure	No data available
l) Vapour density	No data available
m) Relative density	10.49 g/cm ³
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Oxygen, Strong acids and strong bases

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Silver/silver oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available

LD50 Oral - Rat - male - > 5,000 mg/kg

Inhalation: No data available

Inhalation: No data available

Dermal: No data available

Dermal: No data available

No data available

No data available

Skin corrosion/irritation

No data available

No data available

Serious eye damage/eye irritation

No data available

No data available

Respiratory or skin sensitisation

No data available

No data available

Germ cell mutagenicity

No data available

No data available

Carcinogenicity

Carcinogenicity - Rat - Unreported

Tumorigenic:Tumors at site or application.

Carcinogenicity classification not possible from current data.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

May cause argyria (a slate-gray or bluish discoloration of the skin and deep tissues due to the deposit of insoluble albuminate of silver).

12. ECOLOGICAL INFORMATION**12.1 Toxicity**

No data available

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substances, solid, n.o.s. (Silver)
Reportable Quantity (RQ): 1 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Marine pollutant:yes

IATA

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s.

Further information

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Silver	7440-22-4	1993-04-24

SARA 311/312 Hazards

No SARA Hazards

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Silver	7440-22-4	1993-04-24

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Silver	7440-22-4	1993-04-24

	CAS-No.	Revision Date
Silver	7440-22-4	1993-04-24

New Jersey Right To Know Components

	CAS-No.	Revision Date
--	---------	---------------

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION**Full text of H-Statements referred to under sections 2 and 3.**

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

HMIS Rating

Health hazard:	0
Chronic Health Hazard:	
Flammability:	0
Physical Hazard	0

NFPA Rating

Health hazard:	0
Fire Hazard:	0
Reactivity Hazard:	0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 4.10

Revision Date: 05/10/2017

Print Date: 06/28/2019

SAFETY DATA SHEET

Version 6.1
Revision Date 05/28/2017
Print Date 06/28/2019

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : **Thallium**

Product Number : 277932
Brand : Aldrich
Index-No. : 081-001-00-3

CAS-No. : 7440-28-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 2), H300
Acute toxicity, Inhalation (Category 2), H330
Acute aquatic toxicity (Category 3), H402
Chronic aquatic toxicity (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H300 + H330

Fatal if swallowed or if inhaled

H412

Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P260

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264

Wash skin thoroughly after handling.

P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P284	Wear respiratory protection.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula	:	TI
Molecular weight	:	204.38 g/mol
CAS-No.	:	7440-28-0
EC-No.	:	231-138-1
Index-No.	:	081-001-00-3

Hazardous components

Component	Classification	Concentration
Thallium		
	Acute Tox. 2; Aquatic Acute 3; Aquatic Chronic 3; H300 + H330, H412	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

thallium oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combu formation should be taken into consideration before additional processing Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Thallium	7440-28-0	TWA	0.100000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Alopecia Adopted values or notations enclosed are those for which changes are proposed in the NIC 2010 Revision or addition to the notice of intended changes See Notice of Intended Changes (NIC) Danger of cutaneous absorption		
		TWA	0.020000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Peripheral neuropathy Gastrointestinal damage 2015 Adoption Danger of cutaneous absorption		
		TWA	0.020000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Peripheral neuropathy Gastrointestinal damage		

		Danger of cutaneous absorption varies		
		TWA	0.1 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Skin designation		
		TWA	0.02 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		Peripheral neuropathy Gastrointestinal damage Danger of cutaneous absorption varies		
		TWA	0.1 mg/m ³	USA. NIOSH Recommended Exposure Limits
		Potential for dermal absorption		

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If th full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance

Form: granular

	Colour: light grey
b) Odour	No data available
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 303 °C (577 °F) - lit.
f) Initial boiling point and boiling range	1,457 °C (2,655 °F) - lit.
g) Flash point	()Not applicable
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapour pressure	No data available
l) Vapour density	No data available
m) Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Air sensitive.

10.5 Incompatible materials

Strong acids, Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - thallium oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available(Thallium)
Dermal: No data available(Thallium)
No data available(Thallium)

Skin corrosion/irritation

No data available(Thallium)

Serious eye damage/eye irritation

No data available(Thallium)

Respiratory or skin sensitisation

No data available(Thallium)

Germ cell mutagenicity

No data available(Thallium)

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Possible risk of congenital malformation in the fetus.(Thallium)

No data available(Thallium)

Specific target organ toxicity - single exposure

No data available(Thallium)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available(Thallium)

Additional Information

RTECS: XG3425000

The most characteristic symptom of thallium exposure is alopecia (loss of impairment of nail growth often resulting in the appearance of crescent-s Other symptoms in acute poisoning relate chiefly to the gastrointestinal system. Acute poisoning results in swelling of the feet and legs, arthral the hands and feet, mental confusion, polyneuritis with severe pain in th angina-like pains, nephritis, wasting and weakness, and lymphocytosis and peripheral nervous system abnormalities may persist including ataxia, tre disorders, memory loss, and psychoses may develop., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(Thallium)

Stomach - Irregularities - Based on Human Evidence
Stomach - Irregularities - Based on Human Evidence(Thallium)

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish LC50 - Cyprinodon variegatus (sheepshead minnow) - 21.0 mg/l - 96.0 h(Thallium)
mortality NOEC - Cyprinodon variegatus (sheepshead minnow) - 14.0 mg/l - 96.0 h(Thallium)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available(Thallium)

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chem scrubber.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3288 Class: 6.1 Packing group: II
Proper shipping name: Toxic solid, inorganic, n.o.s. (Thallium)
Reportable Quantity (RQ) : 1000 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 3288 Class: 6.1 Packing group: II EMS-No: F-A, S-A
Proper shipping name: TOXIC SOLID, INORGANIC, N.O.S. (Thallium)

IATA

UN number: 3288 Class: 6.1 Packing group: II
Proper shipping name: Toxic solid, inorganic, n.o.s. (Thallium)

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Thallium	7440-28-0	2007-07-01

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Thallium	7440-28-0	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Thallium	7440-28-0	2007-07-01

New Jersey Right To Know Components

	CAS-No.	Revision Date
Thallium	7440-28-0	2007-07-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H300	Fatal if swallowed.
H300 + H330	Fatal if swallowed or if inhaled
H330	Fatal if inhaled.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

HMIS Rating

Health hazard:	4
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

NFPA Rating

Health hazard:	4
Fire Hazard:	0
Reactivity Hazard:	0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956
Version: 6.1

Revision Date: 05/28/2017

Print Date: 06/28/2019

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 6.0 Revision Date 11.11.2016

Print Date 02.08.2019

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Zinc metal

Product Number : NIST683

Brand : Sigma-Aldrich

REACH No. : A registration number is not available for this substance as the substance or its uses are exempted from registration, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.2 Label elements

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.3 Other hazards - none

SECTION 3: Composition/information on ingredients

3.1 Substances

SECTION 4: First aid measures

4.1 Description of first aid measures

No data available

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

- 4.3 Indication of any immediate medical attention and special treatment needed**
No data available

SECTION 5: Firefighting measures

- 5.1 Extinguishing media**
No data available
- 5.2 Special hazards arising from the substance or mixture**
No data available
- 5.3 Advice for firefighters**
No data available
- 5.4 Further information**
No data available

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures**
For personal protection see section 8.
- 6.2 Environmental precautions**
No data available
- 6.3 Methods and materials for containment and cleaning up**
No data available
- 6.4 Reference to other sections**
For disposal see section 13.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling**
For precautions see section 2.2.
- 7.2 Conditions for safe storage, including any incompatibilities**
No data available
- 7.3 Specific end use(s)**
Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters**
- 8.2 Exposure controls**
No data available

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties**
- | | |
|--|-------------------|
| a) Appearance | Form: solid |
| b) Odour | No data available |
| c) Odour Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | No data available |
| f) Initial boiling point and boiling range | No data available |
| g) Flash point | No data available |
| h) Evaporation rate | No data available |

- | | |
|---|-------------------|
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | No data available |
| k) Vapour pressure | No data available |
| l) Vapour density | No data available |
| m) Relative density | No data available |
| n) Water solubility | No data available |
| o) Partition coefficient: n-octanol/water | No data available |
| p) Auto-ignition temperature | No data available |
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | No data available |

9.2 Other safety information
No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Skin corrosion/irritation

Serious eye damage/eye irritation

Respiratory or skin sensitisation

Germ cell mutagenicity



Safety Data Sheet

Revision Date: 03/05/18

www.restek.com

2 Letter ISO country code/language code: US/EN

1. IDENTIFICATION

Catalog Number / Product Name: 32011 / Aroclor® 1254 Standard
Company: Restek Corporation
Address: 110 Benner Circle
Bellefonte, Pa. 16823
Phone#: 814-353-1300
Fax#: 814-353-1309
Emergency#: 800-424-9300 (CHEMTREC)
703-527-3887 (Outside the US)
Email: www.restek.com
Revision Number: 12
Intended use: For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:

GHS Hazard
Symbols:



GHS Classification: Flammable Liquid Category 2
Skin Corrosion/Irritation Category 2
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2
Hazardous to the aquatic environment - Chronic Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

GHS Signal Word: Danger

GHS Hazard: Highly flammable liquid and vapour.
Causes skin irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
Toxic to aquatic life with long lasting effects.

GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilation and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
Specific treatment see section 4.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use extinguishing media in section 5 for extinction.

Collect spillage.

Storage: Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: Specific target organ toxicity - Single exposure - STOT SE 3: H336 May cause drowsiness or dizziness.

Repeated Exposure Target Organs: Specific target organ toxicity - Repeated exposure - STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. (C >= 5 %; Minimum classification, No information to prove exclusion of certain routes of exposure)

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
hexane	110-54-3	203-777-6	99.9
aroclor® 1254	11097-69-1		0.1

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

5. FIRE- FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire.
Fire and/or Explosion Hazards: Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back
Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.
Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions:	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment
Storage Technical Measures and Conditions:	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

United States:

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
hexane	110-54-3	1100 ppm IDLH (10% LEL)	1000 ppm	50 ppm TWA	500 ppm TWA; 1800 mg/m3 TWA
aroclor® 1254	11097-69-1	5 mg/m3 IDLH	None Known	0.5 mg/m3 TWA	0.5 mg/m3 TWA

Personal Protection:

Engineering Measures:	Local exhaust ventilation is recommended when generating excessive levels of vapours from handling or thermal processing.
Respiratory Protection:	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.
Skin Protection:	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	No data available
Odor:	Mild
Physical State:	Liquid
pH:	Not applicable
Vapor Pressure:	No data available
Vapor Density:	2.97 (air = 1)
Boiling Point (°C):	68.73 °C (HSDB)
Melting Point (°C):	-95 °C Melting Point
Flash Point (°F):	-8
Flammability:	Highly Flammable Extremely Flammable
Upper Flammable/Explosive Limit, % in air:	No data available
Lower Flammable/Explosive Limit, % in air:	No data available
Autoignition Temperature (°C):	No data available deg C
Decomposition Temperature (°C):	No data available
Specific Gravity:	0.672 g/cm3 at 15 °C
Evaporation Rate:	No data available
Odor Threshold:	No data available
Solubility:	Negligible; 0-1%
Partition Coefficient: n-octanol in water:	No data available
VOC % by weight:	0
Molecular Weight:	No data available

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents
Hazardous Decomposition Products:	No data available

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation Contact Absorption Ingestion
Target Organs Potentially Affected By Exposure:	Eyes, Central nervous system stimulation,

Chemical Interactions That Change Toxicity: Respiratory Tract, Skin, Peripheral Nervous System
None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption: May cause irritation and minor systemic damage. Harmful if absorbed through the skin.
Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Harmful if swallowed.
Ingestion Toxicity: Toxic if swallowed. May cause target organ failure and/or death.

Long-Term (Chronic) Health Effects:

Carcinogenicity: No data.
Reproductive and Developmental Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Inhalation: Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption: Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause minor systemic damage.

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Aroclor 1254	11097-69-1	Oral LD50 Rat 1010 mg/kg
n-Hexane	110-54-3	Dermal LD50 Rabbit 3000 mg/kg; Inhalation LC50 Rat 48000 ppm 4 h; Oral LD50 Rat 25 g/kg

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.	
Aroclor 1254	11097-69-1	Present

ACGIH:

Chemical Name	CAS No.	
Chlorodiphenyl (54% chlorine)	11097-69-1	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

NIOSH:

Chemical Name	CAS No.	
Chlorodiphenyl (54% chlorine)	11097-69-1	potential occupational carcinogen

NTP:

Chemical Name	CAS No.
No data available	

IARC:

Chemical Name	CAS No.	Group No.
----------------------	----------------	------------------

12. ECOLOGICAL INFORMATION

Overview: Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.
Mobility: No data
Persistence: No data
Bioaccumulation: No data
Degradability: No data
Ecological Toxicity Data: No data available

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product: Spent or discarded material is a hazardous waste. Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures.

Disposal Methods: Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Waste Disposal of Packaging: Comply with all Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORTATION INFORMATION

United States:
DOT Proper Shipping Name: Hexanes
UN Number: UN1208
Hazard Class: 3
Packing Group: II

International:
IATA Proper Shipping Name: Hexanes
UN Number: UN1208
Hazard Class: 3
Packing Group: II

Marine Pollutant: Yes

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
hexane	110-54-3	Y	N

15. REGULATORY INFORMATION

United States:	Chemical Name	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
	hexane	110-54-3	X	X	-	X
	aroclor® 1254	11097-69-1	X	-	-	-

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
---------------	-------	------------

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
hexane	110-54-3	X	X	X	-
aroclor® 1254	11097-69-1	-	X	X	X

16. OTHER INFORMATION

Prior Version Date: 09/20/16

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.

1 Identification

- **Product identifier**
- **Product Name:** Aroclor 1260
- **Part Number:** PCB-1260
- **Application of the substance / the mixture** Certified Reference Material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SPEX CertiPrep, LLC.
203 Norcross Ave, Metuchen,
NJ 08840 USA
- **Information department:** product safety department
- **Emergency telephone number:**
Emergency Phone Number (24 hours)
CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

n-hexane

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/20/2015

Reviewed on 11/20/2015

Product Name: Aroclor 1260

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

110-54-3	n-hexane	99.98%
----------	----------	--------

- **Chemical identification of the substance/preparation**

11096-82-5	aroclor 1260	0.02%
------------	--------------	-------

4 First-aid measures

- **Description of first aid measures**
- **General information:** Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for Doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Product Name: Aroclor 1260

See Section 13 for disposal information.

(Contd. of page 2)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:	
110-54-3 n-hexane	
PEL	Long-term value: 1800 mg/m ³ , 500 ppm
REL	Long-term value: 180 mg/m ³ , 50 ppm
TLV	Long-term value: 176 mg/m ³ , 50 ppm
	Skin; BEI

Ingredients with biological limit values:	
110-54-3 n-hexane	
BEI	0.4 mg/L
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: 2,5-Hexanedione without hydrolysis

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Product Name: Aroclor 1260

(Contd. of page 3)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour Threshold:	Not applicable.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	69 °C (156 °F)

· Flash point: -26 °C (-15 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 240 °C (464 °F)

· Decomposition temperature: Not applicable.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	1.2 Vol %
Upper:	7.4 Vol %

· Vapor pressure at 20 °C (68 °F): 160 hPa (120 mm Hg)

· Density at 20 °C (68 °F) 0.87912 g/cm³ (7.336 lbs/gal)

· Relative density Not applicable.

· Vapour density Not applicable.

· Evaporation rate Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not applicable.

· Viscosity:

Dynamic:	Not applicable.
Kinematic:	Not applicable.

· Solvent content:

Organic solvents:	100.0 %
VOC content:	100.0 %

· Other information No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

US

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/20/2015

Reviewed on 11/20/2015

Product Name: Aroclor 1260

(Contd. of page 4)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)
--

11096-82-5 aroclor 1260	R
-------------------------	---

· OSHA-Ca (Occupational Safety & Health Administration)
--

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|---|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1208 |
| · UN proper shipping name | |
| · DOT | Hexanes |
| · ADR | 1208 Hexanes, ENVIRONMENTALLY HAZARDOUS |
| · IMDG | HEXANES, MARINE POLLUTANT |
| · IATA | HEXANES |

(Contd. on page 6)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/20/2015

Reviewed on 11/20/2015

Product Name: Aroclor 1260

(Contd. of page 5)

<ul style="list-style-type: none"> · <i>Transport hazard class(es)</i> · <i>DOT</i> 	
	
<ul style="list-style-type: none"> · <i>Class</i> · <i>Label</i> 	<ul style="list-style-type: none"> 3 Flammable liquids 3
<ul style="list-style-type: none"> · <i>ADR, IMDG</i> 	
 	
<ul style="list-style-type: none"> · <i>Class</i> · <i>Label</i> 	<ul style="list-style-type: none"> 3 Flammable liquids 3
<ul style="list-style-type: none"> · <i>IATA</i> 	
	
<ul style="list-style-type: none"> · <i>Class</i> · <i>Label</i> 	<ul style="list-style-type: none"> 3 Flammable liquids 3
<ul style="list-style-type: none"> · <i>Packing group</i> · <i>DOT, ADR, IMDG, IATA</i> 	<ul style="list-style-type: none"> II
<ul style="list-style-type: none"> · <i>Environmental hazards:</i> · <i>Marine pollutant:</i> · <i>Special marking (ADR):</i> 	<ul style="list-style-type: none"> Product contains environmentally hazardous substances: n-hexane Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · <i>Special precautions for user</i> · <i>Danger code (Kemler):</i> · <i>EMS Number:</i> 	<ul style="list-style-type: none"> Warning: Flammable liquids 33 F-E,S-D
<ul style="list-style-type: none"> · <i>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</i> 	<ul style="list-style-type: none"> Not applicable.
<ul style="list-style-type: none"> · <i>Transport/Additional information:</i> 	
<ul style="list-style-type: none"> · <i>ADR</i> · <i>Excepted quantities (EQ)</i> 	<ul style="list-style-type: none"> Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> · <i>IMDG</i> · <i>Limited quantities (LQ)</i> · <i>Excepted quantities (EQ)</i> 	<ul style="list-style-type: none"> 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> · <i>UN "Model Regulation":</i> 	<ul style="list-style-type: none"> UN 1208 HEXANES, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- *Safety, health and environmental regulations/legislation specific for the substance or mixture*
- *Sara*

- *Section 355 (extremely hazardous substances):*

None of the ingredients is listed.

- *Section 313 (Specific toxic chemical listings):*

110-54-3 | n-hexane

- *TSCA (Toxic Substances Control Act):*

110-54-3 | n-hexane

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/20/2015

Reviewed on 11/20/2015

Product Name: Aroclor 1260

(Contd. of page 6)

- **Proposition 65**

- **Chemicals known to cause cancer:**

11096-82-5 aroclor 1260

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

110-54-3 n-hexane

II

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02

GHS07

GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

n-hexane

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** product safety department

- **Contact:**

SPEX CertiPrep, LLC.

1-732-549-7144

- **Date of preparation / last revision** 11/20/2015 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

(Contd. on page 8)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/20/2015

Reviewed on 11/20/2015

Product Name: Aroclor 1260

(Contd. of page 7)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1

US

1. IDENTIFICATION

Catalog Number / Product Name: 32201 / 4,4'-DDD Standard
Company: Restek Corporation
Address: 110 Benner Circle
Bellefonte, Pa. 16823
Phone#: 814-353-1300
Fax#: 814-353-1309
Emergency#: 800-424-9300 (CHEMTREC)
703-527-3887 (Outside the US)
Email: www.restek.com
Revision Number: 7
Intended use: For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:

GHS Hazard
Symbols:



GHS Classification: Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1
Flammable Liquid Category 2
Acute Toxicity - Dermal Category 3
Acute Toxicity - Oral Category 3

GHS Signal Word: Danger

GHS Hazard: Highly flammable liquid and vapour.
Toxic if swallowed or in contact with skin.
Causes damage to organs.

GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilation and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF exposed: Call a POISON CENTER or doctor/physician.
Call a POISON CENTER or doctor/physician if you feel unwell.
Specific treatment see section 4.
Rinse mouth.
Take off immediately all contaminated clothing and wash it before reuse.
In case of fire: Use extinguishing media in section 5 for extinction.

Storage: Keep container tightly closed.

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: Specific target organ toxicity - Single exposure - STOT SE 1: H370 Causes damage to organs. (C >= 10 %; No information to prove exclusion of certain routes of exposure); Specific target organ toxicity - Single exposure - STOT SE 2: H371 May cause damage to organs. (3 % <= C <10 %; Concentration limits for acute toxicity cannot be translated into GHS from the DSD especially when minimum classifications are given)

Repeated Exposure Target Organs: No data available

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
methanol	67-56-1	200-659-6	99.9
4,4'-DDD	72-54-8	200-783-0	0.1

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

5. FIRE- FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire and/or Explosion Hazards: Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions: Toxic or severely irritating material. Avoid contacting and avoid

Storage Technical Measures and Conditions:

breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment
 Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**United States:**

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
methanol	67-56-1	6000 ppm IDLH	250 ppm STEL	200 ppm TWA	200 ppm TWA; 260 mg/m3 TWA

Personal Protection:**Engineering Measures:**

Local exhaust ventilation is recommended when generating excessive levels of vapours from handling or thermal processing.

Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. If an exposure limit is exceeded or if an operator is experiencing symptoms of inhalation overexposure as explained in Section 3, provide respiratory protection.

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	No data available
Odor:	Mild
Physical State:	No data available
pH:	Not applicable
Vapor Pressure:	No data available
Vapor Density:	1.1 (air = 1)
Boiling Point (°C):	64.7 °C at 760 mmHg (HSDB)
Melting Point (°C):	-98 °C
Flash Point (°F):	52
Flammability:	Highly Flammable
Upper Flammable/Explosive Limit, % in air:	36
Lower Flammable/Explosive Limit, % in air:	6
Autoignition Temperature (°C):	464 deg C
Decomposition Temperature (°C):	No data available
Specific Gravity:	0.791 - 0.792 g/cm3 at 20 °C
Evaporation Rate:	No data available
Odor Threshold:	No data available
Solubility:	Moderate; 50-99%
Partition Coefficient: n-octanol in water:	No data available
VOC % by weight:	0
Molecular Weight:	32.04

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation, Skin Contact, Eye Contact, Ingestion
Target Organs Potentially Affected By Exposure:	Eyes, Central nervous system stimulation, Skin, GI Tract, Respiratory Tract
Chemical Interactions That Change Toxicity:	None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

Inhalation Toxicity: Harmful! Can cause systemic damage (see "Target Organs")Methanol can cause central nervous system depression and overexposure can cause damage to the optic nerve resulting in visual impairment or blindness.

Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.Highly toxic and may be fatal if swallowed.

Ingestion Toxicity: Toxic if swallowed. May cause target organ failure and/or death.May be fatal if swallowed.

Long-Term (Chronic) Health Effects:

Carcinogenicity: Contains a probable or known human carcinogen.

Reproductive and Developmental Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs)

Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Ingestion: Toxic if swallowed. May cause target organ failure and/or death.

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Methanol	67-56-1	Inhalation LC50 Rat 22500 ppm 8 h

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.
No data available	

ACGIH:

Chemical Name	CAS No.
No data available	

NIOSH:

Chemical Name	CAS No.
No data available	

NTP:

Chemical Name	CAS No.
No data available	

IARC:

Chemical Name	CAS No.	Group No.
Monograph 53 [1991] (listed under DDT and associated compounds)	72-54-8	Group 2B

12. ECOLOGICAL INFORMATION

Overview: Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Mobility: No data

Persistence: No data

Bioaccumulation: No data

Degradability: Biodegrades slowly.

Ecological Toxicity Data: No data available

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product: Spent or discarded material is a hazardous waste. Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures.

Disposal Methods: Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Waste Disposal of Packaging: Comply with all Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORTATION INFORMATION

United States:
DOT Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3
Packing Group: II

International:
IATA Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3(6.1)
Packing Group: II

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available			

15. REGULATORY INFORMATION

United States:	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
methanol	67-56-1	X	X	-	X

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
DDD	72-54-8	Prop 65 Cancer
Methanol	67-56-1	Prop 65 Develop Tox

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
methanol	67-56-1	X	X	X	X
4,4'-DDD	72-54-8	X	X	X	X

16. OTHER INFORMATION

Prior Version Date: 12/21/16

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.



Safety Data Sheet

Revision Date: 03/23/18

www.restek.com

2 Letter ISO country code/language code: US/EN

1. IDENTIFICATION

Catalog Number / Product Name: 32202 / 4,4'-DDE Standard
Company: Restek Corporation
Address: 110 Benner Circle
Bellefonte, Pa. 16823
Phone#: 814-353-1300
Fax#: 814-353-1309
Emergency#: 800-424-9300 (CHEMTREC)
703-527-3887 (Outside the US)
Email: www.restek.com
Revision Number: 10
Intended use: For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:

GHS Hazard
Symbols:



GHS Classification: Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1
Flammable Liquid Category 2
Acute Toxicity - Inhalation Dust / Mist Category 3
Acute Toxicity - Dermal Category 3
Acute Toxicity - Oral Category 3

GHS Signal Word: Danger

GHS Hazard: Highly flammable liquid and vapour.
Toxic if swallowed, in contact with skin or if inhaled.
Causes damage to organs.

GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilation and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Specific treatment see section 4.
Rinse mouth.
Take off immediately all contaminated clothing and wash it before reuse.
In case of fire: Use extinguishing media in section 5 for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: Specific target organ toxicity - Single exposure - STOT SE 1: H370 Causes damage to organs. (C >= 10 %; No information to prove exclusion of certain routes of exposure); Specific target organ toxicity - Single exposure - STOT SE 2: H371 May cause damage to organs. (3 % <= C <10 %; Concentration limits for acute toxicity cannot be translated into GHS from the DSD especially when minimum classifications are given)

Repeated Exposure Target Organs: No data available

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
methanol	67-56-1	200-659-6	99.9
4,4'-DDE	72-55-9	200-784-6	0.1

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

5. FIRE- FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire and/or Explosion Hazards: Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions: Toxic or severely irritating material. Avoid contacting and avoid

Storage Technical Measures and Conditions:

breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment
Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**United States:**

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
methanol	67-56-1	6000 ppm IDLH	250 ppm STEL	200 ppm TWA	200 ppm TWA; 260 mg/m3 TWA

Personal Protection:**Engineering Measures:**

Local exhaust ventilation is recommended when generating excessive levels of vapours from handling or thermal processing.

Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. If an exposure limit is exceeded or if an operator is experiencing symptoms of inhalation overexposure as explained in Section 3, provide respiratory protection.

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	No data available
Odor:	Mild
Physical State:	Liquid
pH:	Not applicable
Vapor Pressure:	No data available
Vapor Density:	1.1 (air = 1)
Boiling Point (°C):	64.7 °C at 760 mmHg (HSDB)
Melting Point (°C):	-98 °C
Flash Point (°F):	52
Flammability:	Highly Flammable
Upper Flammable/Explosive Limit, % in air:	36
Lower Flammable/Explosive Limit, % in air:	6
Autoignition Temperature (°C):	464 deg C
Decomposition Temperature (°C):	No data available
Specific Gravity:	0.791 - 0.792 g/cm3 at 20 °C
Evaporation Rate:	No data available
Odor Threshold:	No data available
Solubility:	Moderate; 50-99%
Partition Coefficient: n-octanol in water:	No data available
VOC % by weight:	0
Molecular Weight:	32.04

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation, Skin Contact, Eye Contact, Ingestion
Target Organs Potentially Affected By Exposure:	Eyes, Central nervous system stimulation, Skin, GI Tract, Respiratory Tract
Chemical Interactions That Change Toxicity:	None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

Inhalation Toxicity: Harmful! Can cause systemic damage (see "Target Organs)Methanol can cause central nervous system depression and overexposure can cause damage to the optic nerve resulting in visual impairment or blindness.

Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.Highly toxic and may be fatal if swallowed.

Ingestion Toxicity: Toxic if swallowed. May cause target organ failure and/or death.May be fatal if swallowed.

Long-Term (Chronic) Health Effects:

Carcinogenicity: Contains a probable or known human carcinogen.

Reproductive and Developmental Toxicity: Contains a known human reproductive and/or developmental hazard.

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs)

Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Ingestion: Toxic if swallowed. May cause target organ failure and/or death.

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Methanol	67-56-1	Inhalation LC50 Rat 22500 ppm 8 h

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.
No data available	

ACGIH:

Chemical Name	CAS No.
No data available	

NIOSH:

Chemical Name	CAS No.
No data available	

NTP:

Chemical Name	CAS No.
No data available	

IARC:

Chemical Name	CAS No.	Group No.
Monograph 53 [1991] (listed under DDT and associated compounds)	72-55-9	Group 2B

12. ECOLOGICAL INFORMATION

Overview: Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Mobility: No data

Persistence: No data

Bioaccumulation: No data

Degradability: Biodegrades slowly.

Ecological Toxicity Data: No data available

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product: Spent or discarded material is a hazardous waste. Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures.

Disposal Methods: Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Waste Disposal of Packaging: Comply with all Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORTATION INFORMATION

United States:
DOT Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3
Packing Group: II

International:
IATA Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3(6.1)
Packing Group: II

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available			

15. REGULATORY INFORMATION

United States: Chemical Name	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
methanol	67-56-1	X	X	-	X

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
DDE	72-55-9	Prop 65 Cancer
1,1-Dichloro-2,2-bis(p-chlorophenyl)ethylene	72-55-9	Prop 65 Develop Tox
Methanol	67-56-1	Prop 65 Develop Tox
1,1-Dichloro-2,2-bis(p-chlorophenyl)ethylene	72-55-9	Prop 65 Rep Male

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
methanol	67-56-1	X	X	X	X
4,4'-DDE	72-55-9	X	X	X	X

16. OTHER INFORMATION

Prior Version Date: 12/23/16

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions,

data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.



Safety Data Sheet

Revision Date: 12/23/16

www.restek.com

1. IDENTIFICATION

Catalog Number / Product Name: 32203 / 4,4'-DDT Standard
Company: Restek Corporation
Address: 110 Benner Circle
Bellefonte, Pa. 16823
Phone#: 814-353-1300
Fax#: 814-353-1309
Emergency#: 800-424-9300 (CHEMTREC)
703-527-3887 (Outside the US)
Email: www.restek.com
Revision Number: 8
Intended use: For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:

GHS Hazard
Symbols:



GHS Classification: Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1
Flammable Liquid Category 2
Acute Toxicity - Inhalation Dust / Mist Category 3
Acute Toxicity - Dermal Category 3
Acute Toxicity - Oral Category 3

GHS Signal Word: Danger

GHS Hazard: Highly flammable liquid and vapour.
Toxic if swallowed, in contact with skin or if inhaled.
Causes damage to organs.

GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilation and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF exposed: Call a POISON CENTER or doctor/physician.
Call a POISON CENTER or doctor/physician.
Call a POISON CENTER or doctor/physician if you feel unwell.
Specific treatment see section 4.
Rinse mouth.
Take off immediately all contaminated clothing and wash it before reuse.
In case of fire: Use extinguishing media in section 5 for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: No data available.

Repeated Exposure Target Organs: No data available.

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
methanol	67-56-1	200-659-6	99.900000
4,4'-DDT	50-29-3	200-024-3	0.100000

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

5. FIRE- FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire and/or Explosion Hazards: Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions:	Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment
Storage Technical Measures and Conditions:	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

United States:

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
methanol	67-56-1	6000 ppm IDLH	250 ppm STEL	200 ppm TWA	200 ppm TWA; 260 mg/m3 TWA
4,4'-DDT	50-29-3	500 mg/m3 IDLH		1 mg/m3 TWA	1 mg/m3 TWA (listed under Dichlorodiphenyltric hloroethane)

Personal Protection:

Engineering Measures:

Local exhaust ventilation is recommended when generating excessive levels of vapors from handling or thermal processing.

Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. If an exposure limit is exceeded or if an operator is experiencing symptoms of inhalation overexposure as explained in Section 3, provide respiratory protection.

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	No data available.
Odor:	Mild
Physical State:	No data available.
pH:	No data available.
Vapor Pressure:	No data available.
Vapor Density:	1.1 (air = 1)
Boiling Point:	No data available.
Melting Point:	-98 °C
Flash Point:	52
Flammability:	Highly Flammable
Upper Flammable/Explosive Limit, % in air:	36
Lower Flammable/Explosive Limit, % in air:	6
Autoignition Temperature:	464 deg C
Decomposition Temperature:	No data available.
Specific Gravity:	0.791 - 0.792 g/cm3 at 20 °C
Evaporation Rate:	No data available.
Odor Threshold:	No data available.
Solubility:	Moderate; 50-99%
Partition Coefficient: n-octanol in water:	No data available.
VOC % by weight:	99.9
Molecular Weight:	32.04

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	No data available.
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry: Inhalation, Skin Contact, Eye Contact, Ingestion
Target Organs Potentially Affected By Exposure: Eyes, Central nervous system stimulation, Skin, GI Tract, Respiratory Tract
Chemical Interactions That Change Toxicity: None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Inhalation Toxicity: Harmful! Can cause systemic damage (see "Target Organs)Methanol can cause central nervous system depression and overexposure can cause damage to the optic nerve resulting in visual impairment or blindness.
Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.Highly toxic and may be fatal if swallowed.
Ingestion Toxicity: Toxic if swallowed. May cause target organ failure and/or death.May be fatal if swallowed.

Long-Term (Chronic) Health Effects:

Carcinogenicity: Contains a probable or known human carcinogen.
Reproductive and Developmental Toxicity: Contains a known human reproductive and/or developmental hazard.
Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs)
Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Ingestion: Toxic if swallowed. May cause target organ failure and/or death.

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Methanol	67-56-1	Inhalation LC50 Rat 22500 ppm 8 h
DDT	50-29-3	Dermal LD50 Rabbit 300 - 2820 mg/kg

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.	
DDT	50-29-3	Present

ACGIH:

Chemical Name	CAS No.	
DDT	50-29-3	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

NIOSH:

Chemical Name	CAS No.	
DDT	50-29-3	potential occupational carcinogen

NTP:

Chemical Name	CAS No.
No data available.	

IARC:

Chemical Name	CAS No.	Group No.
No data.		Group 1
DDT	50-29-3	Group 2A
No data.		Group 2B

12. ECOLOGICAL INFORMATION

Overview: Moderate ecological hazard. This product may be dangerous

Mobility: to plants and/or wildlife.
Persistence: No data
Bioaccumulation: No data
Degradability: Biodegrades slowly.
Ecological Toxicity Data: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product: Spent or discarded material is a hazardous waste.
Disposal Methods: Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Waste Disposal of Packaging: Comply with all Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORTATION INFORMATION

United States:
DOT Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3
Packing Group: II

International:
IATA Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3(6.1)
Packing Group: II

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available.			

15. REGULATORY INFORMATION

United States:	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
methanol	67-56-1	X	X	-	X
4,4'-DDT	50-29-3	X	-	-	X

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
DDT	50-29-3	Prop 65 Cancer
Methanol	67-56-1	Prop 65 Develop Tox
p,p"-DDT	50-29-3	Prop 65 Develop Tox
p,p"-DDT	50-29-3	Prop 65 Rep Female
p,p"-DDT	50-29-3	Prop 65 Rep Male

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
methanol	67-56-1	X	X	X	X
4,4'-DDT	50-29-3	X	X	X	X

16. OTHER INFORMATION

Prior Version Date: 09/30/14
Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.
References: No data available.
Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose

prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.

Material Safety Data Sheet

HAZARD WARNINGS	RISK PHRASES	PROTECTIVE CLOTHING
 	Toxic compound, do not ingest or inhale. Avoid all contact with this material. CARCINOGEN. MINIMIZE EXPOSURE.	   

Section I. Chemical Product and Company Identification

Chemical Name	Benz[a]anthracene		
Catalog Number	B0017	Supplier	TCl America 9211 N. Harborgate St. Portland OR 1-800-423-8616
Synonym	Tetraphene		
Chemical Formula	C ₁₈ H ₁₂		
CAS Number	56-55-3	In case of Emergency Call	Chemtrec® (800) 424-9300 (U.S.) (703) 527-3887 (International)

Section II. Composition and Information on Ingredients

Chemical Name	CAS Number	Percent (%)	TLV/PEL	Toxicology Data
Benz[a]anthracene	56-55-3	Min. 99.0 (GC)	This chemical is classified as a carcinogen. There is no acceptable exposure limit for a carcinogen.	Rat LD ₅₀ (intravenous) >200 mg/kg

Section III. Hazards Identification

Acute Health Effects	Toxic if ingested or inhaled. Avoid prolonged contact with this material. Overexposure may result in serious illness or death. Follow safe industrial hygiene practices and always wear proper protective equipment when handling this compound.
Chronic Health Effects	CARCINOGENIC EFFECTS : Possible carcinogen. (sufficient evidence in animals, no adequate data in humans) Tumorigenic: Mouse (dermal) 18mg/kg. Neoplastic by RTECS criteria. Tumorigenic: Mouse (implant) 80 mg/kg. Carcinogenic by RTECS criteria. Tumorigenic: Mouse (subcutaneous) 2 mg/kg. Equivocal tumorigenic by RTECS criteria. MUTAGENIC EFFECTS : Not available. TERATOGENIC EFFECTS : Not available. DEVELOPMENTAL TOXICITY Not available. The substance is toxic to kidneys. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure to an highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

Section IV. First Aid Measures

Eye Contact	Check for and remove any contact lenses. DO NOT use an eye ointment. Flush eyes with running water for a minimum of 15 minutes, occasionally lifting the upper and lower eyelids. Seek medical attention. Treat symptomatically and supportively.
Skin Contact	After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cover the irritated skin with an emollient. Seek medical attention. Treat symptomatically and supportively. Wash any contaminated clothing before reusing.
Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform artificial respiration. WARNING: It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention and, if possible, show the chemical label. Treat symptomatically and supportively.
Ingestion	INDUCE VOMITING by sticking finger in throat. Lower the head so that the vomit will not reenter the mouth and throat. Loosen tight clothing such as a collar, tie, belt, or waistband. If the victim is not breathing, administer artificial respiration. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Seek immediate medical attention and, if possible, show the chemical label. Treat symptomatically and supportively.

Section V. Fire and Explosion Data			
Flammability	Combustible.	Auto-Ignition	Not available.
Flash Points	Not available.	Flammable Limits	Not available.
Combustion Products	These products are toxic carbon oxides (CO, CO ₂).		
Fire Hazards	No specific information is available regarding the flammability of this compound in the presence of various materials.		
Explosion Hazards	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available. No additional information is available regarding the risks of explosion.		
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemicals, CO ₂ , water spray or foam. LARGE FIRE: Use water spray, fog or foam. DO NOT use water jet.		

Section VI. Accidental Release Measures	
Spill Cleanup Instructions	Toxic solid. Harmful solid. Stop leak if without risk. DO NOT get water inside container. DO NOT touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all sources of ignition. Consult federal, state, and/or local authorities for assistance on disposal.

Section VII. Handling and Storage	
Handling and Storage Information	TOXIC. POSSIBLE CARCINOGEN. Handle with caution and minimize exposure. Keep away from heat and sources of ignition. Mechanical exhaust required. When not in use, tightly seal the container and store in a dry, cool place. Avoid excessive heat and light. DO NOT ingest. DO NOT breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Treat symptomatically and supportively. Avoid contact with skin and eyes. Always store away from incompatible compounds such as oxidizing agents.

Section VIII. Exposure Controls/Personal Protection	
Engineering Controls	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.
Personal Protection	Splash goggles. Lab coat. Dust respirator. Boots. Gloves. A MSHA/NIOSH approved respirator must be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product. 
Exposure Limits	This chemical is classified as a carcinogen. There is no acceptable exposure limit for a carcinogen.

Section IX. Physical and Chemical Properties			
Physical state @ 20°C	Light yellow to tan powder.	Solubility	Soluble in diethyl ether, acetone. Very slightly soluble in methanol, n-octanol. Insoluble in cold water, hot water.
Specific Gravity	Not available.	Partition Coefficient	0
Molecular Weight	228.29	Vapor Pressure	Not available.
Boiling Point	437.6°C (819.7°F)	Vapor Density	Not available.
Melting Point	157 to 159°C (314.6 to 318.2°F)	Volatility	Not available.
Refractive Index	Not available.	Odor	Not available.
Critical Temperature	Not available.	Taste	Not available.
Viscosity	Not available.		

Section X. Stability and Reactivity Data	
Stability	This material is stable if stored under proper conditions. (See Section VII for instructions)
Conditions of Instability	Avoid excessive heat and light.
Incompatibilities	Reactive with oxidizing agents.

Section XI. Toxicological Information

RTECS Number	CV9275000
Routes of Exposure	Ingestion. Inhalation. Eye contact. Skin contact.
Toxicity Data	Rat LD ₅₀ (intravenous) >200 mg/kg
Chronic Toxic Effects	CARCINOGENIC EFFECTS : Possible carcinogen. (sufficient evidence in animals, no adequate data in humans) Tumorigenic: Mouse (dermal) 18mg/kg. Neoplastic by RTECS criteria. Tumorigenic: Mouse (implant) 80 mg/kg. Carcinogenic by RTECS criteria. Tumorigenic: Mouse (subcutaneous) 2 mg/kg. Equivocal tumorigenic by RTECS criteria. MUTAGENIC EFFECTS : Not available. TERATOGENIC EFFECTS : Not available. DEVELOPMENTAL TOXICITY Not available. The substance is toxic to kidneys. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure to an highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.
Acute Toxic Effects	Toxic if ingested or inhaled. Avoid prolonged contact with this material. Overexposure may result in serious illness or death. Follow safe industrial hygiene practices and always wear proper protective equipment when handling this compound.

Section XII. Ecological Information

Ecotoxicity	Not available.
Environmental Fate	The pattern of benz(a)anthracene (BA) release into air and water is quite general since it is a universal product of combustion of organic matter. Both in air and water it is largely associated with particulate matter. When released into water it will rapidly become adsorbed to sediment or particulate matter in the water column, and bioconcentrate into aquatic organisms. In the unadsorbed state, it will degrade by photolysis in a matter of hours to days. Its slow desorption from sediment and particulate matter will maintain a low concentration of BA in the water. Because it is strongly adsorbed to soil it will remain in the upper few centimeters of soil and not leach into groundwater. BA will very slowly biodegrade when colonies of microorganisms are acclimated but this is too slow a process (half-life ca 1 yr to be significant). Benz(a)anthracene in the atmosphere will be transported long distances and will probably be subject to photolysis and photooxidation although there is little documentation about the rate of these processes in the literature. Humans will be exposed to benz(a)anthracene in ambient air, particularly in industrial areas, from stoves, cigarette smoke, food (particularly when smoked or charcoal broiled), and drinking water.(HSDB)

Section XIII. Disposal Considerations

Waste Disposal	Recycle to process, if possible. Consult your local or regional authorities. You may be able to dissolve or mix material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber system. Observe all federal, state, and local regulations when disposing of this substance.
----------------	--

Section XIV. Transport Information

DOT Classification	DOT CLASS 6.1: Poisonous material.
PIN Number	UN2811
Proper Shipping Name	Toxic solids, organic, n.o.s.
Packing Group (PG)	II
DOT Pictograms	

Section XV. Other Regulatory Information and Pictograms

TSCA Chemical Inventory (EPA)	This compound is ON the EPA Toxic Substances Control Act (TSCA) inventory list.
WHMIS Classification (Canada)	WHMIS CLASS D-2B: Material causing other toxic effects (TOXIC).
EINECS Number (EEC)	200-280-6
EEC Risk Statements	R45- May cause cancer.
Japanese Regulatory Data	Not available.

Section XVI. Other Information**Version 1.0****Validated on 11/3/1997.****Printed 1/20/2005.****Notice to Reader**

TCl laboratory chemicals are for research purposes only and are NOT intended for use as drugs, food additives, households, or pesticides. The information herein is believed to be correct, but does not claim to be all inclusive and should be used only as a guide. Neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All chemical reagents must be handled with the recognition that their chemical, physiological, toxicological, and hazardous properties have not been fully investigated or determined. All chemical reagents should be handled only by individuals who are familiar with their potential hazards and who have been fully trained in proper safety, laboratory, and chemical handling procedures. Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist. Our MSDS sheets are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated MSDS sheets for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective goggles, protective clothing, breathing equipment, facial mask, fume hood). For proper handling and disposal, always comply with federal, state, and local regulations.

Printed 1/20/2005.

SAFETY DATA SHEET

Revision Date 19-Jan-2018

Revision Number 3

1. Identification

Product Name Benzo[a]pyrene, 98%
Cat No. : AC105600010; AC105601000
CAS-No 50-32-8
Synonyms Benzo[def]chrysene.; 3,4-Benzopyrene; 3,4-Benzpyrene
Recommended Use Laboratory chemicals.
Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Sensitization	Category 1
Germ Cell Mutagenicity	Category 1A
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1A

Label Elements

Signal Word

Danger

Hazard Statements

May cause an allergic skin reaction
May cause genetic defects
May cause cancer
May damage fertility or the unborn child

**Precautionary Statements****Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves

Response

IF exposed or concerned: Get medical attention/advice

Skin

IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse

Storage

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects

WARNING. Cancer - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Benzo[a]pyrene	50-32-8	> 96

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes.
Inhalation	Move to fresh air.
Ingestion	Do not induce vomiting.
Most important symptoms and effects	May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Unsuitable Extinguishing Media	No information available
Flash Point Method -	No information available
Autoignition Temperature	No information available

Explosion Limits

Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

None known

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	0	0	N/A

6. Accidental release measures**Personal Precautions**

Ensure adequate ventilation. Use personal protective equipment.

Environmental Precautions

See Section 12 for additional ecological information. Avoid release to the environment. Collect spillage.

Methods for Containment and Clean Up No information available.

Up

7. Handling and storage**Handling**

Ensure adequate ventilation.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls / personal protection**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Benzo[a]pyrene		TWA: 0.2 mg/m ³		

Legend

OSHA - Occupational Safety and Health Administration

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment**Eye/face Protection**

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Powder Solid
Appearance	Dark yellow
Odor	aromatic
Odor Threshold	No information available
pH	
Melting Point/Range	175 179 °C
Boiling Point/Range	°C @ 760 mmHg
Flash Point	
Evaporation Rate	No information available
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	No information available
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C20H12
Molecular Weight	252.31

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	None under normal use conditions
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Component Information

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Benzo[a]pyrene	50-32-8	Group 1	Reasonably Anticipated	A2	X	Not listed

Mutagenic Effects No information available

Reproductive Effects	No information available.
Developmental Effects	No information available.
Teratogenicity	No information available.
STOT - single exposure	None known
STOT - repeated exposure	None known
Aspiration hazard	No information available
Symptoms / effects, both acute and delayed	Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing
Endocrine Disruptor Information	No information available

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Benzo[a]pyrene	Group III Chemical	Not applicable	Not applicable

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

Mobility No information available.

Component	log Pow
Benzo[a]pyrene	6.06

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Benzo[a]pyrene - 50-32-8	U022	-

14. Transport information

DOT

UN-No UN3077
Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Hazard Class 9
Packing Group III

TDG

UN-No UN3077
Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Hazard Class 9
Packing Group III

IATA

UN-No UN3077
Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Hazard Class 9
Packing Group III

IMDG/IMO

UN-No UN3077
 Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 Hazard Class 9
 Packing Group III

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Benzo[a]pyrene	X	X	-	200-028-5	-		X	-	-	X	X

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Benzo[a]pyrene	50-32-8	> 96	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Benzo[a]pyrene	-	-	X	X

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration
Not applicable

CERCLA Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
Benzo[a]pyrene	1 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Benzo[a]pyrene	50-32-8	Carcinogen	0.06 µg/day	Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Benzo[a]pyrene	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Revision Date 19-Jan-2018

Print Date 19-Jan-2018

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS



Safety Data Sheet

Revision Date: 12/08/16

www.restek.com

1. IDENTIFICATION

Catalog Number / Product Name: 31272 / Benzo(b)fluoranthene Standard
Company: Restek Corporation
Address: 110 Benner Circle
Bellefonte, Pa. 16823
Phone#: 814-353-1300
Fax#: 814-353-1309
Emergency#: 800-424-9300 (CHEMTREC)
703-527-3887 (Outside the US)
Email: www.restek.com
Revision Number: 9
Intended use: For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:

GHS Hazard
Symbols:



GHS Classification: Flammable Liquid Category 2
Serious Eye Damage/Eye Irritation Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

GHS Signal Word: Danger

GHS Hazard: Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.

GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilation and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Call a POISON CENTER or doctor/physician if you feel unwell.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use extinguishing media in section 5 for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: No data available.

Repeated Exposure Target Organs: No data available.

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
Acetone	67-64-1	200-662-2	99.900000
benzo (b) fluoranthene	205-99-2	205-911-9	0.100000

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

5. FIRE- FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Fire and/or Explosion Hazards: Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment

Storage Technical Measures and Conditions: Store in a cool dry ventilated location. Isolate from

incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

United States:

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
Acetone	67-64-1	2500 ppm IDLH (10% LEL)	500 ppm STEL 750 ppm STEL; 1782 mg/m3 STEL	250 ppm TWA 500 ppm TWA; 1188 mg/m3 TWA	1000 ppm TWA; 2400 mg/m3 TWA
benzo (b) fluoranthene	205-99-2	ND		No TLV	No data available.

Personal Protection:

Engineering Measures:

Local exhaust ventilation is recommended when generating excessive levels of vapors from handling or thermal processing.

Respiratory Protection:

No respiratory protection required under normal conditions of use. Provide general room exhaust ventilation if symptoms of overexposure occur as explained Section 3. A respirator is not normally required.

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

Medical Conditions Aggravated By Exposure: Respiratory disease including asthma and bronchitis

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	Depends upon product selection
Odor:	Strong
Physical State:	No data available.
pH:	No data available.
Vapor Pressure:	No data available.
Vapor Density:	2.0 (air = 1)
Boiling Point:	No data available.
Melting Point:	-95.4 °C Melting Point
Flash Point:	39
Flammability:	Highly Flammable
Upper Flammable/Explosive Limit, % in air:	No data available.
Lower Flammable/Explosive Limit, % in air:	No data available.
Autoignition Temperature:	465 deg C
Decomposition Temperature:	No data available.
Specific Gravity:	0.7845 g/cm3 at 25 °C
Evaporation Rate:	No data available.
Odor Threshold:	ND
Solubility:	Complete; 100%
Partition Coefficient: n-octanol in water:	No data available.
VOC % by weight:	0
Molecular Weight:	58.08

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	No data available.
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents Strong acids
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation, Skin Contact, Eye Contact, Ingestion
Target Organs Potentially Affected By Exposure:	Eyes, Central nervous system stimulation, Respiratory Tract, Skin
Chemical Interactions That Change Toxicity:	None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.
Skin Contact: Can cause minor skin irritation, defatting, and dermatitis.
Eye Contact: Can cause minor irritation, tearing and reddening.
Ingestion Irritation: May be harmful if swallowed.
Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity: Contains a probable or known human carcinogen.
Reproductive and Developmental Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Inhalation: Upon prolonged and/or repeated exposure, can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.
Skin Contact: Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Acetone	67-64-1	Dermal LD50 Rabbit >15700 mg/kg; Oral LD50 Rat 5800 mg/kg; Inhalation LC50 Rat 50100 mg/m3 8 h

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.	
Benzo(b)fluoranthene	205-99-2	Present

ACGIH:

Chemical Name	CAS No.	
Acetone	67-64-1	A4 - Not Classifiable as a Human Carcinogen
Benzo[b]fluoranthene	205-99-2	A2 - Suspected Human Carcinogen

NIOSH:

Chemical Name	CAS No.
No data available.	

NTP:

Chemical Name	CAS No.
No data available.	

IARC:

Chemical Name	CAS No.	Group No.
No data.		Group 1
No data.		Group 2A
Benzo(b)fluoranthene	205-99-2	Group 2B

12. ECOLOGICAL INFORMATION

Overview:	This material is not expected to be harmful to the ecology.
Mobility:	No data
Persistence:	No data
Bioaccumulation:	No data
Degradability:	No data
Ecological Toxicity Data:	No data available.

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product:	Spent or discarded material is a hazardous waste.
Disposal Methods:	Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Waste Disposal of Packaging:	Comply with all Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORTATION INFORMATION

United States:	
DOT Proper Shipping Name:	Acetone

UN Number: UN1090
 Hazard Class: 3
 Packing Group: II

International:
 IATA Proper Shipping Name: Acetone
 UN Number: UN1090
 Hazard Class: 3
 Packing Group: II

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available.			

15. REGULATORY INFORMATION

United States:

Chemical Name	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
Acetone	67-64-1	X	-	-	X
benzo (b) fluoranthene	205-99-2	X	X	-	-

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
Benzo[b]fluoranthene	205-99-2	Prop 65 Cancer

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
Acetone	67-64-1	X	X	X	X
benzo (b) fluoranthene	205-99-2	X	X	X	X

16. OTHER INFORMATION

Prior Version Date: 03/23/15

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available.

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.



Material Safety Data Sheet

Benzo[k]fluoranthene, 99+% (tlc)

MSDS# 54641

Section 1 - Chemical Product and Company Identification

MSDS Name: Benzo[k]fluoranthene, 99+% (tlc)
Catalog Numbers: AC279730000, AC279732500
Synonyms: 8,9-Benzofluoranthene.
Company Identification: Acros Organics BVBA
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium
Company Identification: (USA) Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
For information in the US, call: 800-ACROS-01
For information in Europe, call: +32 14 57 52 11
Emergency Number, Europe: +32 14 57 52 99
Emergency Number US: 201-796-7100
CHEMTREC Phone Number, US: 800-424-9300
CHEMTREC Phone Number, Europe: 703-527-3887

Section 2 - Composition, Information on Ingredients

CAS#: 207-08-9
Chemical Name: Benzo[k]fluoranthene, 99+% (TLC)
%: 99%
EINECS#: 205-916-6

Hazard Symbols: T



Risk Phrases: 45

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Danger! May be fatal if swallowed. May be fatal if absorbed through the skin. Toxic. Carcinogen. May cause lung damage.
Causes eye and skin irritation. Causes digestive and respiratory tract irritation. Cancer hazard. May be fatal if inhaled.
Target Organs: Lungs, respiratory system.

Potential Health Effects

Eye: Causes eye irritation.
Skin: Causes skin irritation. May be fatal if absorbed through the skin.
Ingestion: May be fatal if swallowed. Causes gastrointestinal irritation with nausea, vomiting and diarrhea.
Inhalation: May be fatal if inhaled. Causes respiratory tract irritation.
Chronic: May cause cancer according to animal studies.

Section 4 - First Aid Measures

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower

eyelids. Get medical aid immediately.

Skin: Get medical aid. Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Ingestion: Call a poison control center. If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical aid.

Inhalation: Get medical aid immediately. Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Notes to Physician:

Section 5 - Fire Fighting Measures

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or chemical foam.

Autoignition Temperature: Not available

Flash Point: Not available

Explosion Limits: Lower: Not available

Explosion Limits: Upper: Not available

NFPA Rating: Not published

Section 6 - Accidental Release Measures

General Information: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Vacuum or sweep up material and place into a suitable disposal container. Clean up spills immediately, observing precautions in the Protective Equipment section.

Section 7 - Handling and Storage

Handling: Wash thoroughly after handling. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Use only in a well-ventilated area. Do not breathe dust, mist, or vapor. Do not get on skin or in eyes. Do not ingest or inhale.

Storage: Store in a cool, dry place. Store in a tightly closed container.

Section 8 - Exposure Controls, Personal Protection

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Benzo[k]fluoranthene, 99+% (TLC)	none listed	none listed	none listed

OSHA Vacated PELs: Benzo[k]fluoranthene, 99+% (TLC): None listed

Engineering Controls:

Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Exposure Limits

Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Respirators: Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Section 9 - Physical and Chemical Properties

Physical State: Solid

Color: yellow

Odor: Not available

pH: Not available

Vapor Pressure: Not available

Vapor Density: Not available

Evaporation Rate: Not available

Viscosity: Not available

Boiling Point: 480 deg C @ 760.00mm Hg (896.00°F)

Freezing/Melting Point: 216 - 218 deg C

Decomposition Temperature: Not available

Solubility in water: Not available

Specific Gravity/Density:

Molecular Formula: C₂₀H₁₂

Molecular Weight: 252.32

Section 10 - Stability and Reactivity

Chemical Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Incompatible materials, dust generation.

Incompatibilities with Other Materials: Not available

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.

Hazardous Polymerization: Has not been reported.

Section 11 - Toxicological Information

RTECS#: CAS# 207-08-9: DF6350000

LD50/LC50: RTECS: Not available.

Carcinogenicity: Benzo[k]fluoranthene, 99+% (TLC) - California: carcinogen, initial date 7/1/87 NTP: Suspect carcinogen
IARC: Group 2B carcinogen

Other: See actual entry in RTECS for complete information.

Section 12 - Ecological Information

Ecotoxicity: Not available

Section 13 - Disposal Considerations

Dispose of in a manner consistent with federal, state, and local regulations.

Section 14 - Transport Information

US DOT

Shipping Name: Not regulated as a hazardous material

Hazard Class:

UN Number:

Packing Group:

Canada TDG

Shipping Name: Not available

Hazard Class:

UN Number:

Packing Group:

USA RQ: CAS# 207-08-9: 5000 lb final RQ; 2270 kg final RQ

Section 15 - Regulatory Information

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: T

Risk Phrases:

R 45 May cause cancer.

Safety Phrases:

S 53 Avoid exposure - obtain special instructions before use.

S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

WGK (Water Danger/Protection)

CAS# 207-08-9: Not available

Canada

Canadian WHMIS Classifications: Not available

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

CAS# 207-08-9 is not listed on Canada's Ingredient Disclosure List.

US Federal

TSCA

CAS# 207-08-9 is not listed on the TSCA Inventory. It is for research and development use only.

Section 16 - Other Information

MSDS Creation Date: 9/02/1997

Revision #6 Date 7/20/2009

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages.



Material Safety Data Sheet

Chrysene, 98%

MSDS# 95251

Section 1 - Chemical Product and Company Identification

MSDS Name: Chrysene, 98%
Catalog Numbers: AC224140000, AC224140010, AC224140050, AC224145000
Synonyms: 1,2-Benzophenanthrene; Benzo(a)phenanthrene; 1,2,5,6-Dibenzonaphthalene.

Company Identification: Acros Organics BVBA
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium

Company Identification: (USA) Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

For information in the US, call: 800-ACROS-01

For information in Europe, call: +32 14 57 52 11

Emergency Number, Europe: +32 14 57 52 99

Emergency Number US: 201-796-7100

CHEMTREC Phone Number, US: 800-424-9300

CHEMTREC Phone Number, Europe: 703-527-3887

Section 2 - Composition, Information on Ingredients

CAS#: 218-01-9
Chemical Name: Chrysene
%: 98
EINECS#: 205-923-4

Hazard Symbols: T



Risk Phrases: 45 50/53

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Caution! May cause respiratory tract irritation. May cause eye and skin irritation. May cause cancer in humans. Target Organs: Liver, skin.

Potential Health Effects

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Ingestion: May cause gastrointestinal irritation with nausea, vomiting and diarrhea.

Inhalation: May cause respiratory tract irritation.

Chronic: May cause cancer according to animal studies.

Section 4 - First Aid Measures

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin: Get medical aid. Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse.

Ingestion: Do not induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid immediately.

Inhalation: Get medical aid immediately. Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Notes to Physician:

Section 5 - Fire Fighting Measures

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. This material in sufficient quantity and reduced particle size is capable of creating a dust explosion.

Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or chemical foam.

Autoignition Temperature: Not available.

Flash Point: Not applicable.

Explosion Limits: Lower: Not available

Explosion Limits: Upper: Not available

NFPA Rating: health: ; flammability: 1; instability: ;

Section 6 - Accidental Release Measures

General Information: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Vacuum or sweep up material and place into a suitable disposal container. Clean up spills immediately, observing precautions in the Protective Equipment section. Wear a self contained breathing apparatus and appropriate personal protection. (See Exposure Controls, Personal Protection section). Provide ventilation.

Section 7 - Handling and Storage

Handling: Wash thoroughly after handling. Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Avoid breathing dust.

Storage: Store in a tightly closed container. Store in a cool, dry area away from incompatible substances.

Section 8 - Exposure Controls, Personal Protection

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Chrysene	0.2 mg/m3 TWA (as benzene soluble aerosol) (listed under Coal tar pitches).	0.1 mg/m3 TWA	0.2 mg/m3 TWA (benzene soluble fraction) (listed under Coal tar pitches).

OSHA Vacated PELs: Chrysene: 0.2 mg/m3 TWA (benzene soluble fraction) (listed under Coal tar pitches)

Engineering Controls:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels.

Exposure Limits

Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Respirators: Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Section 9 - Physical and Chemical Properties

Physical State: Solid

Color: very light beige

Odor: Not available

pH: Not available

Vapor Pressure: Not available

Vapor Density: Not available

Evaporation Rate: Not available

Viscosity: Not available

Boiling Point: 448 deg C @ 760 mm Hg (838.40°F)

Freezing/Melting Point: 250-255 deg C

Decomposition Temperature: Not available

Solubility in water: insoluble

Specific Gravity/Density:

Molecular Formula: C₁₈H₁₂

Molecular Weight: 228.29

Section 10 - Stability and Reactivity

Chemical Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Dust generation.

Incompatibilities with Other Materials: Not available

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.

Hazardous Polymerization: Has not been reported.

Section 11 - Toxicological Information

RTECS#: CAS# 218-01-9: GC0700000

LD50/LC50: RTECS: Not available.

Carcinogenicity: Chrysene - ACGIH: A1 - Confirmed Human Carcinogen (Coal tar pitches). California: carcinogen, initial date 1/1/90 NTP: Known carcinogen (Coal tar pitches). IARC: Group 1 carcinogen (Coal tar pitches).

Other: See actual entry in RTECS for complete information.

Section 12 - Ecological Information

Ecotoxicity: Water flea LC50 = 1.9 mg/L; 2 Hr.; Unspecified

Section 13 - Disposal Considerations

Dispose of in a manner consistent with federal, state, and local regulations.

Section 14 - Transport Information

US DOT

Shipping Name: Please contact Fisher Scientific for shipping information

Hazard Class:

UN Number:

Packing Group:

Canada TDG

Shipping Name: Not available

Hazard Class:

UN Number:

Packing Group:

USA RQ: CAS# 218-01-9: 100 lb final RQ; 45.4 kg final RQ

Section 15 - Regulatory Information

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: T

Risk Phrases:

R 45 May cause cancer.

R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrases:

S 53 Avoid exposure - obtain special instructions before use.

S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S 60 This material and its container must be disposed of as hazardous waste.

S 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

WGK (Water Danger/Protection)

CAS# 218-01-9: Not available

Canada

CAS# 218-01-9 is listed on Canada's DSL List

Canadian WHMIS Classifications: D2A

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

CAS# 218-01-9 is listed on Canada's Ingredient Disclosure List

US Federal

TSCA

CAS# 218-01-9 is listed on the TSCA Inventory.

Section 16 - Other Information

MSDS Creation Date: 6/30/1999

Revision #6 Date 7/20/2009

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages.

SAFETY DATA SHEET

Revision Date 23-Jan-2018

Revision Number 3

1. Identification

Product Name Dibenz[a,h]anthracene, 99% (UV-Vis)
Cat No. : AC406430010; AC406432500
Synonyms 1,2:5,6-Dibenz(a)anthracene.
Recommended Use Laboratory chemicals.
Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity

Category 1B

Label Elements

Signal Word

Danger

Hazard Statements

May cause cancer



Precautionary Statements

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Response

IF exposed or concerned: Get medical attention/advice

Storage

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects

WARNING. Cancer - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Dibenzo(a,h)anthracene	53-70-3	99

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes.
Inhalation	Move to fresh air.
Ingestion	Do not induce vomiting.
Most important symptoms and effects	No information available.
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Unsuitable Extinguishing Media	No information available
Flash Point	
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

None known

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
1	1	0	N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment.
Environmental Precautions	See Section 12 for additional ecological information. Avoid release to the environment. Collect spillage.

Methods for Containment and Clean Up No information available.

7. Handling and storage

Handling	Ensure adequate ventilation.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls / personal protection

Exposure Guidelines	This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.
Engineering Measures	Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Solid
Appearance	Off-white
Odor	No information available
Odor Threshold	No information available
pH	
Melting Point/Range	265 °C
Boiling Point/Range	
Flash Point	
Evaporation Rate	No information available
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	No information available
Solubility	No information available
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C ₂₂ H ₁₄
Molecular Weight	278.34

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	None under normal use conditions
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Component Information	
Toxicologically Synergistic Products	No information available
<u>Delayed and immediate effects as well as chronic effects from short and long-term exposure</u>	

Irritation	No information available
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Dibenzo(a,h)anthracene	53-70-3	Group 2A	Reasonably Anticipated	Not listed	X	Not listed

Mutagenic Effects	No information available
Reproductive Effects	No information available.
Developmental Effects	No information available.
Teratogenicity	No information available.
STOT - single exposure	None known
STOT - repeated exposure	None known
Aspiration hazard	No information available
Symptoms / effects, both acute and delayed	No information available
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Persistence and Degradability	No information available
--------------------------------------	--------------------------

Bioaccumulation/ Accumulation No information available.

Mobility No information available.

Component	log Pow
Dibenzo(a,h)anthracene	6.50

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Dibenzo(a,h)anthracene - 53-70-3	U063	-

14. Transport information

DOT Not regulated
TDG Not regulated
IATA Not regulated
IMDG/IMO Not regulated

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Dibenzo(a,h)anthracene	X	-	X	200-181-8	-		-	-	-	X	-

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Dibenzo(a,h)anthracene	53-70-3	99	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Dibenzo(a,h)anthracene	-	-	-	X

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration
Not applicable

CERCLA Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
Dibenzo(a,h)anthracene	1 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Dibenzo(a,h)anthracene	53-70-3	Carcinogen	0.2 µg/day	Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Dibenzo(a,h)anthracene	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Revision Date 23-Jan-2018

Print Date 23-Jan-2018

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 6.0
Revision Date 04/15/2019
Print Date 06/28/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Dibenzofuran
Product Number : 236373
Brand : Aldrich
CAS-No. : 132-64-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATES
Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

2.2 GHS Label elements, including precautionary statements

Not a hazardous substance or mixture.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Diphenylene oxide
Formula : C₁₂H₈O
Molecular weight : 168.19 g/mol
CAS-No. : 132-64-9

EC-No. : 205-071-3

No components need to be disclosed according to the applicable regulations.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

In case of skin contact

Wash off with soap and plenty of water.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapours, mist or gas.

For personal protection see section 8.

6.2 Environmental precautions

No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Storage class (TRGS 510): 13: Non Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

General industrial hygiene practice.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This

recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: powder, finocrystalline Colour: white, beige
b) Odour	No data available
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 80 - 82 °C (176 - 180 °F) - lit.
f) Initial boiling point and boiling range	154 - 155 °C 309 - 311 °F at 27 hPa - lit.
g) Flash point	130 °C (266 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapour pressure	No data available
l) Vapour density	No data available
m) Relative density	1.3 g/cm ³ at 20 °C (68 °F)
n) Water solubility	insoluble
o) Partition coefficient: n-octanol/water	log Pow: 4.12 - (Lit.), Potential bioaccumulation
p) Auto-ignition temperature	No data available
q) Decomposition	No data available

- temperature
- r) Viscosity No data available
 - s) Explosive properties No data available
 - t) Oxidizing properties No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Hazardous properties cannot be excluded.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No ecological problems are to be expected when the product is handled and used with due care and attention.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Dibenzofuran)
Reportable Quantity (RQ): 100 lbs
• Marine pollutant: yes Poison Inhalation Hazard: No

IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Dibenzofuran)
Marine pollutant : yes

IATA

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Dibenzofuran)

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Dibenzofuran	132-64-9	2007-07-01

SARA 311/312 Hazards

No SARA Hazards

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Dibenzofuran	132-64-9	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Dibenzofuran	132-64-9	2007-07-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information**Further information**

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.0

Revision Date: 04/15/2019

Print Date: 06/28/2019



Material Safety Data Sheet

Fluoranthene, 93%

MSDS# 01667

Section 1 - Chemical Product and Company Identification

MSDS Name: Fluoranthene, 93%
Catalog Numbers: AC345980000, AC345980010, AC345982500
Synonyms:

Company Identification: Acros Organics BVBA
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Company Identification: (USA)
For information in the US, call: 800-ACROS-01
For information in Europe, call: +32 14 57 52 11
Emergency Number, Europe: +32 14 57 52 99
Emergency Number US: 201-796-7100
CHEMTREC Phone Number, US: 800-424-9300
CHEMTREC Phone Number, Europe: 703-527-3887

Section 2 - Composition, Information on Ingredients

CAS#: 206-44-0
Chemical Name: Fluoranthene
%: 93%
EINECS#: 205-912-4

Hazard Symbols: XN



Risk Phrases: 22

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Not available Target Organs: None known.

Potential Health Effects

Eye: May cause eye irritation.
Skin: May cause skin irritation.
Ingestion: Harmful if swallowed. May cause irritation of the digestive tract.
Inhalation: May cause respiratory tract irritation.
Chronic:

Section 4 - First Aid Measures

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin: Get medical aid. Flush skin with plenty of water for at least 15 minutes while removing contaminated

clothing and shoes.

Ingestion: Get medical aid. Wash mouth out with water.

Inhalation: Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

Notes to Physician:

Section 5 - Fire Fighting Measures

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

Extinguishing Media: In case of fire, use water, dry chemical, chemical foam, or alcohol-resistant foam.

Autoignition Temperature: Not available

Flash Point: > 100 deg C (> 212.00 deg F)

Explosion Limits: Lower: Not available

Explosion Limits: Upper: Not available

NFPA Rating: Not published

Section 6 - Accidental Release Measures

General Information: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Vacuum or sweep up material and place into a suitable disposal container.

Section 7 - Handling and Storage

Handling: Avoid breathing dust, mist, or vapor. Avoid contact with skin and eyes.

Storage: Store in a cool, dry place. Store in a tightly closed container.

Section 8 - Exposure Controls, Personal Protection

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Fluoranthene	none listed	none listed	none listed

OSHA Vacated PELs: Fluoranthene: None listed

Engineering Controls:

Use adequate ventilation to keep airborne concentrations low.

Exposure Limits

Personal Protective Equipment

Eyes: Not available

Skin: Wear appropriate protective gloves and clothing to prevent skin exposure.

Clothing: Wear appropriate protective clothing to minimize contact with skin.

Respirators: Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

Section 9 - Physical and Chemical Properties

Physical State: Crystalline powder

Color: yellow

Odor: odorless

pH: Not available

Vapor Pressure: Not available

Vapor Density: Not available

Evaporation Rate: Not available

Viscosity: Not available

Boiling Point: 380 - 34.0 deg C @

Freezing/Melting Point: 109.00 - 111

Decomposition Temperature: Not available

Solubility in water: insoluble

Specific Gravity/Density:

Molecular Formula: C16H10

Molecular Weight: 202.07

Section 10 - Stability and Reactivity

Chemical Stability:	Stable under normal temperatures and pressures.
Conditions to Avoid:	Incompatible materials.
Incompatibilities with Other Materials	Not available
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide.
Hazardous Polymerization	Has not been reported.

Section 11 - Toxicological Information

RTECS#: CAS# 206-44-0; LL4025000

RTECS:

LD50/LC50: **CAS# 206-44-0**: Oral, rat: LD50 = 2 gm/kg;
Skin, rabbit: LD50 = 3180 mg/kg;

Carcinogenicity: Fluoranthene - IARC: Group 3 (not classifiable)

Other: The toxicological properties have not been fully investigated. See actual entry in RTECS for complete information.

Section 12 - Ecological Information

Other: No information available.

Section 13 - Disposal Considerations

Dispose of in a manner consistent with federal, state, and local regulations.

Section 14 - Transport Information

US DOT

Shipping Name: Please contact Fisher Scientific for shipping information

Hazard Class:

UN Number:

Packing Group:

Canada TDG

Shipping Name: Not available

Hazard Class:

UN Number:

Packing Group:

USA RQ: CAS# 206-44-0: 100 lb final RQ; 45.4 kg final RQ

Section 15 - Regulatory Information

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: XN

Risk Phrases:

R 22 Harmful if swallowed.

Safety Phrases:

WGK (Water Danger/Protection)

CAS# 206-44-0: Not available

Canada

CAS# 206-44-0 is listed on Canada's NDSL List

Canadian WHMIS Classifications: Not available

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

CAS# 206-44-0 is listed on Canada's Ingredient Disclosure List

US Federal

TSCA

CAS# 206-44-0 is listed on the TSCA
Inventory.

Section 16 - Other Information

MSDS Creation Date: 10/27/1999

Revision #5 Date 7/20/2009

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages.



Safety Data Sheet

Revision Date: 03/22/18

www.restek.com

2 Letter ISO country code/language code: US/EN

1. IDENTIFICATION

Catalog Number / Product Name: 31279 / Indeno(1,2,3-c,d)pyrene Standard
Company: Restek Corporation
Address: 110 Benner Circle
Bellefonte, Pa. 16823
Phone#: 814-353-1300
Fax#: 814-353-1309
Emergency#: 800-424-9300 (CHEMTREC)
703-527-3887 (Outside the US)
Email: www.restek.com
Revision Number: 10
Intended use: For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:



GHS Hazard
Symbols:

GHS Classification: Carcinogenicity Category 2

GHS Signal Word: Warning

GHS Hazard: Suspected of causing cancer.

GHS Precautions:

Safety Precautions: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: No data available

Repeated Exposure Target Organs: No data available

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
Dichloromethane	75-09-2	200-838-9	99.9
indeno (1,2,3-c,d) pyrene	193-39-5	205-893-2	0.1

4. FIRST-AID MEASURES

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately
Eyes:	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Serious harm (damage) may result if treatment is delayed. Continue to flush eyes while awaiting medical attention
Skin Contact:	Wash with soap and water. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS. Never give anything by mouth to an unconscious person

5. FIRE- FIGHTING MEASURES

Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do Not direct a stream of water into the hot burning liquid. Use methods suitable to fight surrounding fire.
Fire and/or Explosion Hazards:	No data.
Fire Fighting Methods and Protection:	Use methods for the surrounding fire.
Hazardous Combustion Products:	Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:	Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.
Methods for Clean-up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions:	Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material.
Storage Technical Measures and Conditions:	Store in a cool dry place. Isolate from incompatible materials. Keep container closed when not in use

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

United States:					
Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
Dichloromethane	75-09-2	2300 ppm IDLH	None Known	50 ppm TWA	25 ppm TWA; 125 ppm STEL (15 min. TWA)
indeno (1,2,3-c,d) pyrene	193-39-5	Not established	None Known	Not established	No data available

Personal Protection:

Engineering Measures:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to

Eye Protection:	eliminate symptoms. Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection:	Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Medical Conditions Aggravated By Exposure:	Eye disease Skin disease including eczema and sensitization Respiratory disease including asthma and bronchitis

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	Colorless
Odor:	Strong
Physical State:	No data available
pH:	Not applicable
Vapor Pressure:	No data available
Vapor Density:	2.93 (air = 1)
Boiling Point (°C):	530 °C
Melting Point (°C):	-96.7 °C
Flash Point (°F):	No data available
Upper Flammable/Explosive Limit, % in air:	No data available
Lower Flammable/Explosive Limit, % in air:	No data available
Autoignition Temperature (°C):	556 deg C
Decomposition Temperature (°C):	No data available
Specific Gravity:	1.3254 - 1.3258 g/cm ³ at 20 °C
Evaporation Rate:	No data available
Odor Threshold:	ND
Solubility:	Moderate; 50-99%
Partition Coefficient: n-octanol in water:	No data available
VOC % by weight:	0
Molecular Weight:	No data available

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known. Contamination High temperatures
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents Caustics (bases)
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation Absorption Ingestion Skin contact Eye contact
Target Organs Potentially Affected By Exposure:	Skin, Cardiovascular System, Eyes, Liver
Chemical Interactions That Change Toxicity:	None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs") Inhalation may cause severe central nervous system depression (including unconsciousness).
Skin Contact:	Contact causes severe skin irritation and possible burns.
Skin Absorption:	Harmful if absorbed through the skin. May cause severe irritation and systemic damage.
Eye Contact:	Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.
Ingestion Irritation:	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.
Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity:	Contains a probable or known human carcinogen.
Reproductive and Developmental Toxicity:	No data available to indicate product or any components

Inhalation: present at greater than 0.1% may cause birth defects. Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")

Skin Absorption: Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Methane, dichloro-	75-09-2	Inhalation LC50 Rat 53 mg/L 6 h

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.	
Indeno[1,2,3-cd]pyrene	193-39-5	Present
Methylene chloride	75-09-2	25 ppm TWA (8 hr.); 125 ppm STEL (15 min.); 12.5 ppm Action Level (see 29 CFR 1910.1051); effective date for respiratory protection for certain employers to achieve the 8-hour TWA PEL is August 31, 1998; the start up date to install engineering controls is December 10, 1998.; {OSHA - 29 CFR 1910 Specifically Regulate

ACGIH:

Chemical Name	CAS No.	
Dichloromethane	75-09-2	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

NIOSH:

Chemical Name	CAS No.	
Methylene chloride	75-09-2	potential occupational carcinogen

NTP:

Chemical Name	CAS No.	
No data available		

IARC:

Chemical Name	CAS No.	Group No.
Monograph 110 [in preparation]; Monograph 71 [1999]	75-09-2	Group 2A
Monograph 92 [2010]; Supplement 7 [1987]; Monograph 32 [1983]	193-39-5	Group 2B

12. ECOLOGICAL INFORMATION

Overview:	Moderate ecological hazard. This product may be dangerous to plants and/or wildlife. Keep out of waterways.
Mobility:	No data
Persistence:	No data
Bioaccumulation:	No data
Degradability:	No data
Ecological Toxicity Data:	No data available

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product:	Spent or discarded material is a hazardous waste. Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures.
Disposal Methods:	Incinerate spent or discarded material a permitted hazardous waste facility.
Waste Disposal of Packaging:	Comply with all Local, State, Federal, and Provincial

14. TRANSPORTATION INFORMATION

United States:
DOT Proper Shipping Name: Dichloromethane
UN Number: UN1593
Hazard Class: 6.1
Packing Group: III

International:
IATA Proper Shipping Name: Dichloromethane
UN Number: UN1593
Hazard Class: 6.1
Packing Group: III

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available			

15. REGULATORY INFORMATION

United States:

Chemical Name	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
Dichloromethane	75-09-2	X	X	-	X
indeno (1,2,3-c,d) pyrene	193-39-5	X	X	-	X

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
Indeno[1,2,3-cd]pyrene	193-39-5	Prop 65 Cancer
Dichloromethane Dichloromethane (Methylene chloride)	75-09-2	Prop 65 Cancer

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
Dichloromethane	75-09-2	X	X	X	X
indeno (1,2,3-c,d) pyrene	193-39-5	X	X	X	X


16. OTHER INFORMATION

Prior Version Date: 08/03/16

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.



Health	2
Fire	1
Reactivity	0
Personal Protection	E

Material Safety Data Sheet Phenanthrene MSDS

Section 1: Chemical Product and Company Identification

Product Name: Phenanthrene

Catalog Codes: SLP1318

CAS#: 85-01-8

RTECS: SF7175000

TSCA: TSCA 8(b) inventory: Phenanthrene

CI#: Not available.

Synonym:

Chemical Name: Not available.

Chemical Formula: C₁₄H₁₀

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Phenanthrene	85-01-8	100

Toxicological Data on Ingredients: Phenanthrene: ORAL (LD50): Acute: 700 mg/kg [Mouse].

Section 3: Hazards Identification

Potential Acute Health Effects:

Hazardous in case of skin contact (irritant, sensitizer), of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Do not use an eye ointment. Seek medical attention.

Skin Contact:

After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cover the irritated skin with an emollient. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

Inhalation: Allow the victim to rest in a well ventilated area. Seek immediate medical attention.

Serious Inhalation: Not available.

Ingestion:

Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: Not available.

Flash Points: OPEN CUP: 171°C (339.8°F).

Flammable Limits: Not available.

Products of Combustion: These products are carbon oxides (CO, CO₂).

Fire Hazards in Presence of Various Substances: Not available.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill:

Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system.

Section 7: Handling and Storage

Precautions:

Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe dust. Wear suitable protective clothing In

case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.

Storage:

Keep container dry. Keep in a cool place. Ground all equipment containing material. Keep container tightly closed. Keep in a cool, well-ventilated place. Combustible materials should be stored away from extreme heat and away from strong oxidizing agents.

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection:

Splash goggles. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: Not available.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid.

Odor: Not available.

Taste: Not available.

Molecular Weight: 178.22 g/mole

Color: Not available.

pH (1% soln/water): Not available.

Boiling Point: 340°C (644°F)

Melting Point: 101°C (213.8°F)

Critical Temperature: Not available.

Specific Gravity: 1.179 (Water = 1)

Vapor Pressure: Not applicable.

Vapor Density: 6.14 (Air = 1)

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Very slightly soluble in cold water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Not available.

Incompatibility with various substances: Not available.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity: Not available.

Special Remarks on Corrosivity: Not available.

Polymerization: No.

Section 11: Toxicological Information

Routes of Entry: Eye contact. Inhalation. Ingestion.

Toxicity to Animals: Acute oral toxicity (LD50): 700 mg/kg [Mouse].

Chronic Effects on Humans: Not available.

Other Toxic Effects on Humans:

Hazardous in case of skin contact (irritant, sensitizer), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are more toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Section 14: Transport Information

DOT Classification: Not a DOT controlled material (United States).

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

Section 15: Other Regulatory Information

Federal and State Regulations: TSCA 8(b) inventory: Phenanthrene

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications:

WHMIS (Canada): Not controlled under WHMIS (Canada).

DSCL (EEC):

R36/38- Irritating to eyes and skin. R43- May cause sensitization by skin contact.

HMIS (U.S.A.):

Health Hazard: 2

Fire Hazard: 1

Reactivity: 0

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 2

Flammability: 1

Reactivity: 0

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Splash goggles.

Section 16: Other Information


References: Not available.

Other Special Considerations: Not available.

Created: 10/10/2005 11:16 AM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.



Health	2
Fire	1
Reactivity	0
Personal Protection	C

Material Safety Data Sheet Pyrene MSDS

Section 1: Chemical Product and Company Identification

Product Name: Pyrene

Catalog Codes: SLP3868

CAS#: 129-00-00

RTECS: UR2450000

TSCA: TSCA 8(b) inventory: Pyrene

CI#: Not available.

Synonym: Benzo(D,E,F)phenanthrene

Chemical Name: Pyrene

Chemical Formula: C16-H10

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Pyrene	129-00-00	100

Toxicological Data on Ingredients: Pyrene: ORAL (LD50): Acute: 2700 mg/kg [Rat]. 800 mg/kg [Mouse].

Section 3: Hazards Identification

Potential Acute Health Effects:

Hazardous in case of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (irritant, permeator).

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: 3 (Not classifiable for human.) by IARC. MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin Contact:

In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation: Not available.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: Not available.

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: These products are carbon oxides (CO, CO₂).

Fire Hazards in Presence of Various Substances:

Slightly flammable to flammable in presence of heat, of combustible materials. Non-flammable in presence of shocks.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Slightly explosive in presence of heat. Non-explosive in presence of open flames and sparks.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill:

Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system.

Section 7: Handling and Storage

Precautions:

Keep locked up.. Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe dust. Avoid contact with eyes. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested,

seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents.

Storage:

Keep container tightly closed. Keep container in a cool, well-ventilated area. Do not store above 24°C (75.2°F). Preferably refrigerate.

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Synthetic apron. Gloves (impervious).

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: Not available.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid. (Crystalline solid. Powdered solid.)

Odor: Not available.

Taste: Not available.

Molecular Weight: 202.26 g/mole

Color: Yellow.

pH (1% soln/water): Not applicable.

Boiling Point: 404°C (759.2°F)

Melting Point: 151.2°C (304.2°F)

Critical Temperature: Not available.

Specific Gravity: 1.271 @ 23 C (Water = 1)

Vapor Pressure: Not applicable.

Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: The product is more soluble in oil; $\log(\text{oil/water}) = 4.9$

Ionicity (in Water): Not available.

Dispersion Properties:

Is not dispersed in cold water, hot water. See solubility in diethyl ether.

Solubility:

Soluble in diethyl ether. Insoluble in cold water, hot water. Pyrene is fairly soluble in organic solvents. It is soluble in alcohol, benzene, carbon disulfide, ether, petroleum ether, and toluene

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Excess heat, incompatible materials

Incompatibility with various substances: Reactive with oxidizing agents.

Corrosivity: Not available.

Special Remarks on Reactivity: Not available.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Inhalation. Ingestion.

Toxicity to Animals: Acute oral toxicity (LD50): 800 mg/kg [Mouse].

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: 3 (Not classifiable for human.) by IARC. MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Mutagenic for bacteria and/or yeast.

Other Toxic Effects on Humans:

Hazardous in case of ingestion, of inhalation. Slightly hazardous in case of skin contact (irritant, permeator).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

May affect genetic material (mutagenic). May cause cancer (tumorigenic) according to animal data.

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: May cause skin irritation. May be absorbed through skin. Eyes: May cause eye irritation. Conjunctival irritation may be noted. Inhalation: May cause respiratory tract irritation. Ingestion: May cause gastrointestinal tract irritation. May affect behavior/Central Nervous System (excitation and muscle spasticity), liver and urinary system, and immune system, and blood.

Section 12: Ecological Information

Ecotoxicity: Ecotoxicity in water (LC50): 1.8 mg/l 48 hours [Water flea].

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: Not a DOT controlled material (United States).

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

Section 15: Other Regulatory Information

Federal and State Regulations:

Connecticut carcinogen reporting list.: Pyrene Illinois chemical safety act: Pyrene New York release reporting list: Pyrene Pennsylvania RTK: Pyrene Massachusetts RTK: Pyrene Massachusetts spill list: Pyrene New Jersey: Pyrene New Jersey spill list: Pyrene Louisiana RTK reporting list: Pyrene Louisiana spill reporting: Pyrene California Director's list of Hazardous Substances: Pyrene TSCA 8(b) inventory: Pyrene TSCA 8(a) CAIR: Pyrene TSCA 8(d) H and S data reporting: Pyrene: June 1, 1987-June1, 1997 SARA 302/304/311/312 extremely hazardous substances: Pyrene CERCLA: Hazardous substances.: Pyrene: 5000 lbs. (2268 kg)

Other Regulations: EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada): Not controlled under WHMIS (Canada).

DSCL (EEC):

R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. S2- Keep out of the reach of children. S36/37- Wear suitable protective clothing and gloves. S46- If swallowed, seek medical advice immediately and show this container or label.

HMIS (U.S.A.):

Health Hazard: 2

Fire Hazard: 1

Reactivity: 0

Personal Protection: C

National Fire Protection Association (U.S.A.):

Health: 2

Flammability: 1

Reactivity: 0

Specific hazard:

Protective Equipment:

Gloves (impervious). Synthetic apron. Not applicable. Safety glasses.

Section 16: Other Information

References: Not available.

Other Special Considerations: Not available.

Created: 10/09/2005 06:14 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for

lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.



CAMEO Chemicals



Chemical Datasheet

POLYCHLORINATED BIPHENYLS (PCB)



Chemical Identifiers

CAS Number	UN/NA Number	DOT Hazard Label	USCG CHRIS Code
11096-82-5	2315 (liquid)	Class 9	PCB
11097-69-1	3432 (solid)		
11104-28-2			
11141-16-5			
12672-29-6			
12674-11-2			
1336-36-3			
53469-21-9			

NIOSH Pocket Guide

Chlorodiphenyl (54% chlorine)

International Chem Safety Card

POLYCHLORINATED BIPHENYL (AROCOLOR 1254)

NFPA 704

Diamond	Hazard	Value	Description
1 2 0	Health	2	Can cause temporary incapacitation or residual injury.
	Flammability	1	Must be preheated before ignition can occur.
	Instability	0	Normally stable, even under fire conditions.
	Special		

Note: NFPA ratings shown are for polychlorinated biphenyls, CAS number 1336-36-3.

(NFPA, 2010)

General Description

PCBs are colorless oily liquids. Much denser than water and insoluble in water. May burn under exposure to intense heat or flames for prolonged periods of time. Primary hazard is persistence in the environment and potential for long term chronic environmental and health risks. Immediate steps should be taken to limit spread to the environment. As liquids, easily penetrate the soil to contaminate groundwater and nearby waterways.

Hazards

Reactivity Alerts

none

Air & Water Reactions

Insoluble in water.

Fire Hazard

Special Hazards of Combustion Products: Irritating gases are generated in fires. (USCG, 1999)

Health Hazard

Acne from skin contact. (USCG, 1999)

Reactivity Profile

POLYCHLORINATED BIPHENYLS are incompatible with the following: Strong oxidizers (NIOSH, 2016).

Belongs to the Following Reactive Group(s)

- Aryl Halides

Potentially Incompatible Absorbents

No information available.

Response Recommendations

Isolation and Evacuation

Excerpt from ERG Guide 171 [Substances (Low to Moderate Hazard)]:

As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.

SPILL: Increase, in the downwind direction, as necessary, the isolation distance shown above.

FIRE: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. (ERG, 2016)

Firefighting

Excerpt from ERG Guide 171 [Substances (Low to Moderate Hazard)]:

SMALL FIRE: Dry chemical, CO₂, water spray or regular foam.

LARGE FIRE: Water spray, fog or regular foam. Do not scatter spilled material with high-pressure water streams. Move containers from fire area if you can do it without risk. Dike fire-control water for later disposal.

FIRE INVOLVING TANKS: Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. (ERG, 2016)

Non-Fire Response

Excerpt from ERG Guide 171 [Substances (Low to Moderate Hazard)]:

Do not touch or walk through spilled material. Stop leak if you can do it without risk. Prevent dust cloud. Avoid inhalation of asbestos dust.

SMALL DRY SPILL: With clean shovel, place material into clean, dry container and cover loosely; move containers from spill area.

SMALL SPILL: Pick up with sand or other non-combustible absorbent material and place into containers for later disposal.

LARGE SPILL: Dike far ahead of liquid spill for later disposal. Cover powder spill with plastic sheet or tarp to minimize spreading. Prevent entry into waterways, sewers, basements or confined areas. (ERG, 2016)

Protective Clothing

Skin: Wear appropriate personal protective clothing to prevent skin contact.

Eyes: Wear appropriate eye protection to prevent eye contact.

Wash skin: The worker should immediately wash the skin when it becomes contaminated.

Remove: Work clothing that becomes wet or significantly contaminated should be removed and replaced.

Change: Workers whose clothing may have become contaminated should change into uncontaminated clothing before leaving the work premise.

Provide: Eyewash fountains should be provided in areas where there is any possibility that workers could be exposed to the substance; this is irrespective of the recommendation involving the wearing of eye protection. Facilities for quickly drenching the body should be provided within the immediate work area for emergency use where there is a possibility of exposure. [Note: It is intended that these facilities provide a sufficient quantity or flow of water to quickly remove the substance from any body areas likely to be exposed. The actual determination of what constitutes an adequate quick drench facility depends on the specific circumstances. In certain instances, a deluge shower should be readily available, whereas in others, the availability of water from a sink or hose could be considered adequate.] (NIOSH, 2016)

DuPont Tychem® Suit Fabrics

Normalized Breakthrough Times (in Minutes)

Chemical	CAS Number	State	QS	QC	SL	C3	TF	TP	BR	RC	TK	RF
PCB 1254 (90%)	11097-69-1	Liquid		55	>480					>480		
Polychlorinated biphenyl 1254 (90%)	11097-69-1	Liquid		55	>480					>480		

> indicates greater than.

A blank cell indicates the fabric has not been tested. The fabric may or may not offer barrier.

Special Warnings from DuPont

1. Serged and bound seams are degraded by some hazardous liquid chemicals, such as strong acids, and should not be worn when these chemicals are present.
2. CAUTION: This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability...

(DuPont, 2018)

First Aid

Eye: If this chemical contacts the eyes, immediately wash the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.

Skin: If this chemical contacts the skin, immediately wash the contaminated skin with soap and water. If this chemical penetrates the clothing, immediately remove the clothing, wash the skin with soap and water, and get medical attention promptly.

Breathing: If a person breathes large amounts of this chemical, move the exposed person to fresh air at once. If breathing has stopped, perform mouth-to-mouth resuscitation. Keep the affected person warm and at rest. Get medical attention as soon as possible.

Swallow: If this chemical has been swallowed, get medical attention immediately. (NIOSH, 2016)

Physical Properties

Chemical Formula: data unavailable

Flash Point: greater than 286 ° F (USCG, 1999)

Lower Explosive Limit (LEL): data unavailable

Upper Explosive Limit (UEL): data unavailable

Autoignition Temperature: data unavailable

Melting Point: 50 ° F (NIOSH, 2016)

Vapor Pressure: 6e-05 mm Hg (NIOSH, 2016)

Vapor Density (Relative to Air): data unavailable

Specific Gravity: 1.3 to 1.8 at 68 ° F (USCG, 1999)

Boiling Point: Very high (USCG, 1999)

Molecular Weight: 326 (approx) (NIOSH, 2016)

Water Solubility: Insoluble (NIOSH, 2016)

Ionization Potential: data unavailable

IDLH: 5 mg/m³ ; A potential occupational carcinogen. (NIOSH, 2016)

AEGLs (Acute Exposure Guideline Levels)

No AEGL information available.

ERPGs (Emergency Response Planning Guidelines)

No ERPG information available.

PACs (Protective Action Criteria)

Chemical	PAC-1	PAC-2	PAC-3
Polychlorinated biphenyl (Aroclor 1260); (Chlorodiphenyl (60% Cl)) (11096-82-5)	0.41 mg/m ³	4.5 mg/m ³	260 mg/m ³
Polychlorinated biphenyl (Aroclor 1254); (Chlorodiphenyl (54% Cl)) (11097-69-1)	1.5 mg/m ³	68 mg/m ³	200 mg/m ³
Polychlorinated biphenyl (Aroclor 1221); (Chlorodiphenyl (21% Cl)) (11104-28-2)	12 mg/m ³	130 mg/m ³	790 mg/m ³

Chemical	PAC-1	PAC-2	PAC-3
Polychlorinated biphenyl (Aroclor 1232); (Chlorodiphenyl (32% Cl)) (11141-16-5)	13 mg/m3	150 mg/m3	890 mg/m3
Polychlorinated biphenyl (Aroclor 1248); (Chlorodiphenyl (48% Cl)) (12672-29-6)	6.6 mg/m3	72 mg/m3	2200 mg/m3
Polychlorinated biphenyl (Aroclor 1016); (Chlorodiphenyl (41% Cl)) (12674-11-2)	5.6 mg/m3	62 mg/m3	460 mg/m3
Polychlorinated biphenyl; (Aroclor; PCBs) (1336-36-3)	13 mg/m3	140 mg/m3	840 mg/m3
Polychlorinated biphenyl (Aroclor 1242); (Chlorodiphenyl (42% Cl)) (53469-21-9)	3 mg/m3	140 mg/m3	840 mg/m3

(DOE, 2016)

Regulatory Information

EPA Consolidated List of Lists

Regulatory Name	CAS Number/ 313 Category Code	EPCRA 302 EHS TPQ	EPCRA 304 EHS RQ	CERCLA RQ	EPCRA 313 TRI	RCRA Code	CAA 112(r) RMP TQ
Aroclor 1016	12674-11-2			1 pound			
Aroclor 1221	11104-28-2			1 pound			
Aroclor 1232	11141-16-5			1 pound			
Aroclor 1242	53469-21-9			1 pound			
Aroclor 1248	12672-29-6			1 pound			
Aroclor 1254	11097-69-1			1 pound			
Aroclor 1260	11096-82-5			1 pound			
PCBs	1336-36-3			1 pound	X		
Polychlorinated biphenyls	1336-36-3			1 pound	313		

"X" indicates that this is a second name for an EPCRA section 313 chemical already included on this consolidated list. May also indicate that the same chemical with the same CAS number appears on another list with a different chemical name.

(EPA List of Lists, 2015)

DHS Chemical Facility Anti-Terrorism Standards (CFATS)

No regulatory information available.

OSHA Process Safety Management (PSM) Standard List

No regulatory information available.

Alternate Chemical Names

- A 1248
- AROCHLOR

- AROCLOR 1016
- AROCLOR 1221
- AROCLOR 1232
- AROCLOR 1242
- AROCLOR 1248
- AROCLOR 1254
- AROCLOR 1260
- AROCLOR® 1254
- CHLORINATED BIPHENYL
- CHLORODIPHENYL (54% CHLORINE)
- HALOGENATED WAXES
- PCB
- PCBS
- POLYCHLORINATED BIPHENYL
- POLYCHLORINATED BIPHENYLS
- POLYCHLORINATED BIPHENYLS (PCB)
- POLYCHLOROPOLYPHENYLS

SAFETY DATA SHEET

Version 6.3
Revision Date 04/18/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Chloroform
Product Number : 288306
Brand : Sigma-Aldrich
CAS-No. : 67-66-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 4), H302
Acute toxicity, Inhalation (Category 3), H331
Skin irritation (Category 2), H315
Eye irritation (Category 2A), H319
Carcinogenicity (Category 2), H351
Reproductive toxicity (Category 2), H361
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336
Specific target organ toxicity - repeated exposure (Category 1), Liver, Kidney, H372
Short-term (acute) aquatic hazard (Category 3), H402
Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Sigma-Aldrich - 288306

Page 1 of 12

Pictogram



Signal word

Danger

Hazard statement(s)

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs (Liver, Kidney) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Trichloromethane
Methylidyne trichloride

Formula : CHCl₃

Sigma-Aldrich - 288306

Page 2 of 12

Molecular weight : 119.38 g/mol
CAS-No. : 67-66-3

Component	Classification	Concentration
Chloroform		
	Acute Tox. 4; Acute Tox. 3; Skin Irrit. 2; Eye Irrit. 2A; Carc. 2; Repr. 2; STOT SE 3; STOT RE 1; Aquatic Acute 3; H302, H331, H315, H319, H351, H361, H336, H372, H402 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %
ethanol		
	Flam. Liq. 2; Eye Irrit. 2A; H225, H319 Concentration limits: >= 50 %: Eye Irrit. 2A, H319;	>= 1 - < 5 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Hydrogen chloride gas

Not combustible.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Hygiene measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Chloroform	67-66-3	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Confirmed animal carcinogen with unknown relevance to humans		
		ST	2 ppm 9.78 mg/m ³	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen		
		C	50 ppm 240 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	2 ppm 9.78 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	1,000 ppm 1,900 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		STEL	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Confirmed animal carcinogen with unknown relevance to humans		
		TWA	1,000 ppm 1,900 mg/m ³	USA. NIOSH Recommended Exposure Limits
		PEL	1,000 ppm 1,900 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---------------------------------|---|
| a) Appearance | Form: liquid, clear
Color: colorless |
| b) Odor | sweet |
| c) Odor Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: -63 °C (-81 °F) - lit. |
| f) Initial boiling point | 60.5 - 61.5 °C 140.9 - 142.7 °F - lit. |

Sigma-Aldrich - 288306

Page 6 of 12

	and boiling range	
g)	Flash point	() - Regulation (EC) No. 440/2008, Annex, A.9 does not flash
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapor pressure	210 hPa at 20 °C (68 °F)
l)	Vapor density	4.12 - (Air = 1.0)
m)	Relative density	No data available
n)	Water solubility	8.7 g/l at 23 °C (73 °F) - OECD Test Guideline 105
o)	Partition coefficient: n-octanol/water	No data available
p)	Autoignition temperature	No data available
q)	Decomposition temperature	Distillable in an undecomposed state at normal pressure.
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available

9.2 Other safety information

Solubility in other solvents	organic solvent at 20 °C (68 °F) - miscible
Relative vapor density	4.12 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

Contains the following stabilizer(s):

ethanol (≥ 0.5 - ≤ 1 %)

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

various plastics, Rubber Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

Sigma-Aldrich - 288306

Page 7 of 12

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

LD50 Oral - Rat - male - 908 mg/kg
(OECD Test Guideline 401)

Inhalation: No data available

Acute toxicity estimate Inhalation - Expert judgment - 4 h - 3.1 mg/l

Dermal: No data available

Dermal: No data available

No data available

No data available

Skin corrosion/irritation

No data available

Skin - Rabbit

Result: Irritating to skin. - 24 h

Remarks: (ECHA)

Drying-out effect resulting in rough and chapped skin.

Skin - Rabbit

Result: slight irritation

Remarks: (IUCLID)

Serious eye damage/eye irritation

No data available

Eyes - Rabbit

Result: Irritating to eyes.

Remarks: (ECHA)

(Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitization

No data available

Maximization Test - Guinea pig

Result: negative

(Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

No data available

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: (ECHA)

Sigma-Aldrich - 288306

Page 8 of 12

Test Type: unscheduled DNA synthesis assay
Test system: Liver
Metabolic activation: without metabolic activation
Result: negative
Remarks: (ECHA)

Test Type: Micronucleus test
Species: Rat
Cell type: Red blood cells (erythrocytes)
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Test Type: unscheduled DNA synthesis assay
Species: Rat
Cell type: Liver cells
Application Route: Oral
Method: OECD Test Guideline 486
Result: negative

Test Type: in vivo assay
Species: Mouse

Application Route: Inhalation

Result: negative
Remarks: (ECHA)

Carcinogenicity

Suspected of causing cancer.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Chloroform)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Suspected of damaging the unborn child.

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - female - Oral - NOAEL (No observed adverse effect level) - 34 mg/kg
Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Vomiting, Cough, irritant effects, Shortness of breath, respiratory arrest, narcosis, Dizziness, Nausea, agitation, spasms, inebriation, Headache, Stomach/intestinal disorders, ataxia (impaired locomotor coordination), cardiovascular disorders
Drying-out effect resulting in rough and chapped skin.
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

No data available

Toxicity to algae static test ErC50 - Chlamydomonas reinhardtii (green algae) - 13.3 mg/l - 72 h
Remarks: (ECHA)
(Chloroform)

Toxicity to bacteria Remarks: (ECHA)
(Chloroform)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information**DOT (US)**

UN number: 1888 Class: 6.1 Packing group: III
Proper shipping name: Chloroform
Reportable Quantity (RQ): 10 lbs
Reportable Quantity (RQ): 10 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1888 Class: 6.1 Packing group: III EMS-No: F-A, S-A
Proper shipping name: CHLOROFORM

IATA

UN number: 1888 Class: 6.1 Packing group: III
Proper shipping name: Chloroform

SECTION 15: Regulatory information**SARA 302 Components**

The following components are subject to reporting levels established by SARA Title III, Section 302:

Chloroform	CAS-No. 67-66-3	Revision Date 2008-11-03
------------	--------------------	-----------------------------

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Chloroform	CAS-No. 67-66-3	Revision Date 2008-11-03
------------	--------------------	-----------------------------

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Reportable Quantity : D022 lbs

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.3

Revision Date: 04/18/2021

Print Date: 03/19/2022

Appendix D

SOPs – Cold Stress, Heat Stress, Wildlife, Plants and Insects

Cold Stress

1.0 Purpose and Scope

- 1.1 To protect employees from the severest effects of cold stress (hypothermia) and cold injury and to identify exposures to cold working conditions under which it is believed nearly all employees can be repeatedly exposed without adverse health effects.
- 1.2 This procedure applies to all AECOM Americas based employees and operations, and any other entity and its personnel contractually required to comply with this document's content, working outdoors in damp and cool (below 50 degrees Fahrenheit [°F] or 10 degrees Celsius [°C]) conditions or anytime temperatures are below 32°F or 0°C.

2.0 Terms and Definitions

- 2.1 **Cold Stress** – The production of physiological effects due to cold temperatures and/or wind chill.
- 2.2 **Equivalent Chill Temperature (ECT)** – Also known as Wind Chill (see below).
- 2.3 **Frostnip** – Superficial cooling of tissues without cellular destruction.
- 2.4 **Frostbite** – Freezing of tissue, resulting in tissue destruction.
- 2.5 **Hypothermia** – Condition of reduced core body temperature to 95°F (35°C) resulting in loss of dexterity, loss of mental alertness, collapse, and possible death.
- 2.6 **Wind Chill** – The combined effect of air temperature and wind. Also expressed as "equivalent chill temperature" (ECT), wind chill is defined as heat loss resulting from the effects of air temperature and wind velocity upon exposed skin.

3.0 References

- 3.1 S3AM-003-PR1 SH&E Training
- 3.2 S3AM-128-PR1 Medical Screening & Surveillance Program
- 3.3 S3AM-208-PR1 Personal Protective Equipment
- 3.4 S3AM-314-PR1 Working Alone
- 3.5 S3AM-315-PR1 Working On or Near Water
- 3.6 S3AM-333-PR1 Marine Safety & Vessel Operations

4.0 Procedure

4.1 Roles and Responsibilities

4.1.1 Manager

- Ensuring the safety of employees on their project sites, consistent with regulatory standards.
- Implement cold stress prevention measures as applicable at each work site.
- Develop/coordinate a work-warning regimen, as applicable.
- Confirm cold stress hazard assessments/evaluations were completed for the planned activities.
- Assign employees physically capable of performing the assigned tasks. Consider acclimation to cold weather when evaluating employee capability.

- Confirm employees are properly trained to recognize the symptoms of cold stress.

4.1.2 Safety, Health and Environment (SH&E) Manager

- Conduct/support cold stress assessments/evaluations.
- Conduct/support incident investigations related to potential cold stress-related illnesses.
- Assist project teams develop appropriate work-warming regimens.
- Provide cold stress awareness training.

4.1.3 Supervisor

- Identify the tasks that may be most impacted by cold stress and communicate the hazard to the assigned employees.
- Confirm that employees have been trained on the recognition of cold stress-related illnesses.
- Confirm that adequate supplies of warm fluids/drinks are readily available to employees.
- Confirm that a warm/sheltered rest area is available, as applicable.
- Conduct cold stress monitoring, as applicable.
- Implement the work-warming regimen.
- Confirm that first aid measures are implemented once cold stress symptoms are identified.
- Confirm that employees are physically capable of performing the assigned tasks and are not in a physically compromised condition.

4.1.4 Employee

- Observe each other for the early symptoms of cold stress-related illnesses.
- Maintain an adequate intake of available fluids.
- Report to work in a properly rested condition.
- Report all suspected cold stress-related illnesses.

4.2 Requirements

- 4.2.1 Carefully plan work anticipated to be performed in cool or cold conditions. If possible, heavy work should be scheduled during the warmer parts of the day or when the wind is most calm. Include costs in project budgets for specialized equipment and supplies needed to complete the field activities.
- 4.2.2 Staff working in extreme cold (wind chill or ECT below 10°F or -12°C) shall not work alone. The Buddy System shall be utilized to keep an eye on each other and to watch for signs of cold stress. Refer to *S3AM-314-PR1 Working Alone*. Watch for symptoms and signs of hypothermia
- 4.2.3 Monitor weather forecasts and weather conditions such as ambient temperature, wind speed, and precipitation. Use observations prior to entering and while in the field to ensure appropriate protections are in place:
- If possible, move the work to a warm location.
 - If possible and as applicable, erect shelters or screens around the work area.
 - If possible, heat the work area.
 - If possible, adjust schedule according to the cold conditions, work level and worker acclimatization.
 - Implement a work-warming regimen by taking breaks out of the cold. As applicable, consult *S3AM-112 ATT1 Temperature Thresholds* to determine wind chill and work-warming schedule.
 - Take frequent short breaks in warm dry shelters to allow your body to warm up. Limit time of exposure to the cold. If shelter is not readily available, consider supplying temporary shelters.

- Provide assistance to prevent body heat loss, such as:
 - Providing appropriate sources of heat (e.g. warm packs, portable heaters, etc.).
 - Use of insulating materials on equipment handles when temperatures drop below 30°F (-1°C).

4.2.4 All staff working in extreme cold or snow conditions should understand the following guidelines for preventing and detecting hypothermia and frostbite; refer to *S3AM-112-ATT2 Symptoms & Treatment*.

- Ensure appropriate PPE requirements are established and adhered to.
- Avoid exhaustion or fatigue because energy is needed to keep muscles warm.
- Because prolonged exposure to cold air or to immersion in cold water at temperatures even well above freezing can lead to dangerous hypothermia, whole-body protection shall be used.
- Eat high calorie snacks to help maintain body metabolism.
- Confirm extra blankets or sleeping bags are on-site.
- Drink plenty of warm liquids. It is easy to become dehydrated in cold weather.
- Avoid caffeine and alcohol, which can act as diuretics. Alcohol consumption, depending upon quantity, can dilate blood vessels enhancing body heat loss or constrict blood vessels decreasing heat delivery to extremities.
- NEVER IGNORE SHIVERING. Persistent or violent shivering is a clear warning that you are on the verge of hypothermia.
- If you experience frost bite or hypothermia, find shelter and warmth and contact a medical practitioner if symptoms persist, refer to *S3AM-128-PR1 Medical Screening & Surveillance*.

4.3 Training

Before they begin work in a cold environment, employees that might be exposed to cold stress will be informed of the potential for cold stress and how to prevent cold stress. Employees that have not had the training within the twelve prior months shall repeat the training before exposure to cold stress, refer to *S3AM-003-PR1 SH&E Training*. Employees potentially exposed to cold stress will receive training including, but not limited to:

- 4.3.1 Sources of cold stress, the influence of protective clothing, and the importance of acclimatization.
- 4.3.2 How the body loses heat.
- 4.3.3 Recognition of cold-related illness symptoms.
- 4.3.4 Cold stress preventative/corrective measures including, but not limited to:
 - Weather monitoring.
 - Proper eating and drinking practices.
 - Work-warming schedules and proper re-warming techniques.
 - Buddy system.
 - Safe cold work practices appropriate to the work that is to be performed.
 - Proper use of cold environment personal protective clothing.
- 4.3.5 The harmful effects of excessive alcohol consumption in a cold stress environment.
- 4.3.6 The hazards associated with unstable snow or ice build ups.
- 4.3.7 First aid procedures for symptoms related to cold stress.

4.4 Personal Protective Equipment (PPE)

Wearing the right clothing is crucial to avoiding cold stress. The type of fabric also makes a difference. Cotton loses its insulation value when it becomes wet. Wool, on the other hand, retains its insulation even when wet. Adequate insulating dry clothing will be required in air or wind chill temperatures below 40 °F (4.4°C)

All PPE will comply with the requirements of *S3AM-208-PR1 Personal Protective Equipment* and consider the following requirements:

- 4.4.1 Wear at least 3 layers of clothing to help prevent cold stress. It is important to preserve the air space between the body and the outer layer of clothing to retain body heat.
 - Wear a middle layer of down, wool, or similar materials to provide insulation.
 - Avoid cotton, especially blue jeans.
 - Wear an outer layer to break the wind and allow some ventilation (e.g., Gortex® or nylon)
 - Do not wear tight clothing. Loose clothing allows better ventilation.
- 4.4.2 Wear proper clothing, including head coverings and gloves or mittens for cold, wet, and windy conditions.
- 4.4.3 Wear a hat or hardhat liner. Up to 40 percent of body heat can be lost when the head is left exposed.
- 4.4.4 Use insulated footwear with adequate traction to prevent slips and falls.
- 4.4.5 Wear insulated boots or other insulated footwear, and insulated gloves to help reduce the chance of frostbite.
- 4.4.6 Keep a change of dry clothing available in case work clothes become wet.
- 4.4.7 Eye and face protection for employees employed outdoors in a snow and/or ice-covered terrain should be supplied.
 - Sunglasses (with UVA and UVB protection) and sunscreen should be used when there is a persistent combination of snow and direct sun.
 - Special safety goggles to protect against blowing ice crystals and ultraviolet light and glare (which can produce temporary conjunctivitis and/or temporary loss of vision) should be required when there is an expanse of snow coverage causing a potential eye exposure hazard.
 - Ensure face guards are used to protect skin in cold, windy conditions, including riding on an unshielded vehicle.

4.5 General Cold Stress Prevention Measures

- 4.5.1 In order to prevent hypothermia:
 - Wear appropriate clothing and PPE as determined by the weather conditions.
 - When active, ventilate excess heat by opening or removing outer layers of clothing to avoid sweating.
 - Start with the mitten or gloves, unless protection from ice, snow, or cold metal surfaces is needed.
 - Next remove head gear and neck wrappings.
 - Then coats/parkas should be opened at the waist and sleeves.
 - Finally, layers of clothing should be taken off.
 - When resting or tired, or colder conditions are encountered, add additional layers of clothing/ close outer layers in the reverse of the above order, or get out of the cold. Have a sweet drink but do not indulge in heavy eating.

- Garments worn to keep out rain and spray should also allow water vapor to escape.
 - Take advantage of heat from the sun and stay out of the wind as much as possible.
 - Have available emergency shelter providing protection from wind and rain and insulation from the ground.
 - Replace wet clothing. If wet clothing cannot be replaced, then cover it with a layer of non-breathing material to prevent evaporation. Place an insulation layer over this non-breathing material.
 - Get adequate rest; conserve energy.
 - Get adequate nutrition to replenish energy stores; rest after meals.
 - Drink adequate fluids to avoid dehydration.
 - If any project / location staff member shows signs of hypothermia, stop and treat him/her.
- 4.5.2 In order to prevent frost bite:
- Dress to prevent hypothermia and protect the feet and hands.
 - Avoid obstruction of circulation by, for example, tight boots or tightly fitting clothing.
 - Avoid nicotine (particularly cigarettes) and do not consume alcohol.
 - Keep ears and nose covered and out of the wind.
 - Frostbite of the corneas of the eyes can be prevented by protective goggles.
 - Adopt a “buddy system” of constantly watching the faces of others in the party for white skin tissue, which is evidence of frostbite (frostnip).
 - Practice constant personal vigilance for signs of trouble in one’s own fingers and toes; when in doubt, investigate thoroughly before it is too late.
- 4.5.3 Adequate, insulating dry clothing that will help maintain core temperatures above 96.8°F (37°C) shall be provided to employees if work is performed in air temperatures below 40°F (4.4°C). Wind chill cooling rate and the cooling power of air are critical factors. The higher the wind speed and the lower the temperature in the work area, the greater the insulation value of the protective clothing required.
- 4.5.4 An Equivalent Chill Temperature (ECT) chart relating the actual dry bulb air temperature and the wind velocity is presented in *S3AM-112-ATT1 Temperature Thresholds*. Unless unusual or extenuating circumstances exist, cold injury to other than hands, feet, and head is not likely to occur without the development of the initial signs of hypothermia. Superficial or deep local tissue freezing will occur only at temperatures below 32°F (0°C) regardless of wind speed. However, older employees, those with circulatory problems and those with previous cold injuries require special precautionary protection against cold injury. The use of extra insulating clothing and/or a reduction in the duration of the exposure period are among the special precautions that should be considered.
- 4.5.5 Continuous exposure of skin should not be permitted when the air speed and temperature results in an ECT of –25°F (-32°C) or below.
- 4.5.6 At air temperatures of 40°F (4.4°C) or less, it is imperative that employees who become immersed in water or whose clothing becomes wet be immediately removed from the cold environment, provided a change of clothing, and be treated for hypothermia.
- 4.5.7 If the air velocity at the job site is increased by wind, draft, or artificial ventilating equipment, the cooling effect of the wind should be reduced by shielding the work area or by wearing an easily removable windbreak garment.
- 4.5.8 Adequate protection, such as general ventilation, shall be incorporated into any warming shelter design to prevent carbon monoxide poisoning.

- 4.5.9 Operation of internal combustion or similar devices within warming shelters is prohibited.
- 4.5.10 If the available clothing does not give adequate protection to prevent hypothermia or frostbite, work should be modified or suspended until adequate clothing is made available or until weather conditions improve.
- 4.5.11 Walking and working surfaces shall be cleared of ice and snow to prevent slips and falls.
- 4.5.12 Confirm that employees carry fire starter materials if working in remote areas.
- 4.5.13 Supplies such as PPE, fuels, enclosures, de-icing, traction aids, warm drinks, and batteries will be specified by the SH&E Manager and/or the Manager and made available. These supplies will be inspected at least weekly during cold weather projects and replaced when necessary.
- 4.6 Cold Stress Prevention Measures for the Hands
- 4.6.1 Special protection of the hands is required to maintain manual dexterity for the prevention of accidents including, but not limited to the following:
- If fine work is to be performed with bare hands for more than 10 to 20 minutes in an environment below 60°F (15°C), special provisions should be established for keeping the employees' hands warm. For this purpose, warm air jets, radiant heaters (fuel burner or electric radiator), or contact warm plates may be utilized. Metal handles of tools and control bars should be covered by thermal insulating material at temperatures below 30°F (-1° C).
 - If the air temperature falls below 60°F (15°C) for sedentary work, 40°F (4.4° C) for light work, or 20°F (-6°C) for moderate work, and fine manual dexterity is not required, employees should use gloves.
- 4.6.2 To prevent contact frostbite, employees should wear anti-contact gloves:
- When cold surfaces below 20°F (-6°C) are within reach, each employee should be warned to prevent inadvertent contact by bare skin.
 - If the air temperature is 0°F (-18°C) or less, employees should protect their hands with mittens or appropriate gloves. Machine controls and tools for use in cold conditions should be designed so that they can be handled without removing the mittens or gloves.
 - Ensure an adequate supply of dry gloves is available to replace wet gloves.
- 4.6.3 Provisions for additional total body protection are required if work is performed in an environment at or below 40°F (4.4°C). The employees should wear cold protective clothing appropriate for the level of cold and physical activity.
- 4.6.4 Additional Cold Stress Prevention Measures:
- For work practices at or below 10°F (-12°C) ECT, the following will apply:
- The employee should be under constant protective observation (buddy system or supervision).
 - The work rate should not be so high as to cause heavy sweating that will result in wet clothing. If heavy work is being performed, rest periods should be taken in heated shelters and opportunities to change into dry clothing should be provided.
 - New employees should not be required to work full time in the cold during the first days of employment until they become acclimated to the working conditions and required protective clothing. Refer to *S3AM-112-ATT1 Temperature Thresholds* for guidance.
 - The weight and bulkiness of clothing should be included in estimating the required work performance and weights to be lifted by the employee.
 - The work should be arranged in such a way that sitting still or standing still for long periods is minimized. Unprotected metal chair seats should not be used. The employee should be protected from drafts to the greatest extent possible.

- 4.6.5 Employees handling evaporative liquid (gasoline, alcohol, or cleaning fluids) at air temperatures below 40°F should take special precautions to avoid soaking of clothing or gloves with the liquids because of the added danger of cold injury due to evaporative cooling. Special note should be taken of the particularly acute effects of splashes of “cryogenic fluids” or those liquids with a boiling point that is just above ambient temperature.
- 4.6.6 Trauma sustained in freezing or subzero conditions requires special attention, because an injured employee is predisposed to cold injury. Special provisions should be made to prevent hypothermia and freezing of damaged tissue in addition to providing for first aid treatment.

4.7 Hypothermia in Water

4.7.1 Loss of body heat to the water is a major cause of deaths in boating and working near water incidents. Often the cause of death is listed as drowning; however, the primary cause is often hypothermia. It should also be noted that alcohol lowers the body temperature around 2 to 3 degrees by dilating the blood vessels. Do not drink alcohol around cold water. The following table shows the effects of hypothermia in water:

WATER TEMPERATURE	EXHAUSTION	SURVIVAL TIME
32.5°F (0°C)	Under 15 minutes	Under 15 to 45 minutes
32.5 to 40°F (0 to 4°C)	15 to 30 minutes	30 to 90 minutes
40 to 50°F (4 to 10°C)	30 to 60 minutes	1 to 3 hours
50 to 60°F (10 to 16°C)	1 to 2 hours	1 to 6 hours
60 to 70°F (16 to 21°C)	2 to 7 hours	2 to 40 hours
70 to 80°F (21 to 27°C)	3 to 12 hours	3 hours to indefinite
Over 80°F (27°C)	Indefinite	Indefinite

4.7.2 Some points to remember when water is a potential hazard:

- Wear a personal flotation device when drowning is a potential hazard. Refer to *S3AM-315-PR1 Working On or Near Water*, and *S3AM-333-PR1 Marine Safety & Vessel Operations*.
- If the water is less than 50°F (10°C), wear a wet suit or dry suit for work in water (e.g., wading, or if a significant potential to fall in water exists).
- While in the water, do not attempt to swim unless to reach nearby safety. Unnecessary swimming increases the rate of body heat loss. Keep the head out of the water. This will increase survival time.
- Keep a positive attitude about rescue. This will increase chances of survival.
- If there is more than one person in the water, huddling is recommended to conserve body heat.

4.7.3 If an employee or equipment is to work on ice and the water beneath the ice is or may be more than ¾ feet (1m) deep at any point:

- Test the ice prior to commencing to ensure it will support the load to be placed on it. Ongoing testing may be necessary.
- If there is any risk of falling through the ice employees must wear personal protective equipment that will ensure buoyancy and protect against hypothermia at all times while on the ice.

4.8 Work-Warming Regimen

4.8.1 If work is performed continuously in the cold at an equivalent chill temperature (ECT) at or below 19°F (-7°C), heated warming shelters (tents, cabins, rest rooms, etc.) should be made available nearby. The employees should be encouraged to use these shelters at regular intervals; the frequency will depend on the severity of the environmental exposure. Refer to *S3AM-112-ATT1 Temperature Thresholds* for guidance.

- 4.8.2 The onset of heavy shivering, minor frostbite (frostnip), the feeling of excessive fatigue, drowsiness, irritability, or euphoria are indications for immediate return to the shelter.
- 4.8.3 When entering the heated shelter, the outer layer of clothing should be removed and the remainder of the clothing should be loosened to permit sweat evaporation or a change of dry work clothing provided.
- 4.8.4 A change of dry work clothing should be provided as necessary to prevent employees from returning to the cold environment with wet clothing.

5.0 Records

- 5.1 Exposure assessments will be documented in the location's files.

6.0 Attachments

- 6.1 [S3AM-112-ATT1 Temperature Thresholds](#)
- 6.2 [S3AM-112-ATT2 Symptoms & Treatment](#)

Heat Stress

1.0 Purpose and Scope

- 1.1 Establishes a Heat Illness Prevention Program to guide employees in preventing heat illness, recognition of the symptoms of heat stress-related illnesses and in taking the appropriate corrective action.
- 1.2 This procedure applies to all AECOM Americas-based employees and operations and any other entity and its personnel contractually required to comply with this document's content.

2.0 Terms and Definitions

- 2.1 **Acclimated** – Employees who have developed physiological adaptation to hot environments characterized by increased sweating efficiency, circulation stability, and tolerance of high temperatures without stress. Acclimatization occurs after 7 to 10 consecutive days of exposure to heat and much of its benefit may be lost if exposure to hot environments is discontinued for a week.
- 2.2 **Chemical Protective Clothing (CPC)** – Apparel that is constructed of relatively impermeable materials intended to act as a barrier to physical contact of the Employee with potentially hazardous materials in the workplace. Such materials include Tyvek® coveralls (all types) and polyvinyl chloride coveralls and rain suits.
- 2.3 **Heat Cramps** – A form of heat stress brought on by profuse sweating and the resultant loss of salt from the body.
- 2.4 **Heat Exhaustion** – A form of heat stress brought about by the pooling of blood in the vessels of the skin and in the extremities.
- 2.5 **Heat Rash** – A heat-induced condition characterized by a red, bumpy rash with severe itching.
- 2.6 **Heat Stress** – The combination of environmental and physical work factors that constitute the total heat load imposed on the body.
- 2.7 **Heat Stroke** – The most serious form of heat stress, which involves a profound disturbance of the body's heat-regulating mechanism.
- 2.8 **Sunburn** – Caused by unprotected exposure to ultraviolet radiation present in sunlight that is damaging to the skin (Refer to *S3AM-121-PR1 Non-Ionizing Radiation*). The injury is characterized by red painful skin, blisters, and/or peeling.
- 2.9 **Unacclimated** – Employees who have not been exposed to hot work conditions for one week or more or who have become heat-intolerant due to illness or other reasons.

3.0 References

- 3.1 S3AM-003-PR1 SH&E Training
- 3.2 S3AM-004-PR1 Incident Reporting, Notifications & Investigation
- 3.3 S3AM-010-PR1 Emergency Response Planning
- 3.4 S3AM-121-PR1 Non-Ionizing Radiation
- 3.5 S3AM-208-PR1 Personal Protective Equipment
- 3.6 S3AM-209-PR1 Risk Assessment & Management

4.0 Procedures

4.1 Roles and Responsibilities

4.1.1 Managers

- Evaluate the need for heat illness prevention measures and incorporate as appropriate into the Safe Work Plan or Task Hazard Analysis.
- Allocate sufficient resources for the management of heat illness in the field including the provision of water, a shaded break area, and sufficient schedule to allow for breaks.

4.1.2 Safety, Health and Environment (SH&E) Manager

- Provide heat illness awareness training.
- Assist in developing appropriate work-rest schedules.
- Conduct/support incident investigations related to potential heat stress-related illnesses.

4.1.3 Supervisor

- Identify those tasks that may be most impacted by heat stress and communicate the hazard to the assigned Employees.
- Confirm that Employees have been trained on the recognition of heat illness.
- Confirm that this procedure, along with any applicable Safe Work Plan and/or Task Hazard Analysis (and heat exposure control plan that may be contained therein) are made available to affected Employees.
- Confirm that adequate supplies of appropriate fluids are readily available to Employees.
- Confirm that a proper rest area is available.
- Conduct heat illness monitoring, as applicable.
- Implement the work-rest schedule.
- Confirm that first aid measures are implemented once heat stress symptoms are identified.
- Confirm personnel are physically capable of performing the assigned tasks and are not in a physically compromised condition.
- Report all suspected heat illnesses.

4.1.4 Employee

- Observe each other for the early symptoms of heat illnesses.
- Maintain an adequate intake of available fluids.
- Be familiar with heat stress hazards, predisposing factors, and preventative measures.
- Report to work in a properly vested and hydrated condition.
- Report all suspected heat stress-related illnesses.

4.2 Restrictions

4.2.1 The Buddy System is required when working in high heat conditions; Employees shall not work alone.

4.2.2 Employees shall not be exposed to levels exceeding those specified for the given work level and work-rest regimen as listed in *S3AM-113-ATT1 Heat Stress – Temperature Thresholds*.

4.2.3 Clothing corrections shall be applied in accordance with the tables provided in *S3AM-113-ATT1 Heat Stress – Temperature Thresholds*.

4.3 Exposure Controls

4.3.1 It shall be determined whether Employees are or may be exposed to hazardous heat levels. The Supervisor shall:

- Conduct a heat stress assessment to determine the potential for hazardous exposure of Employees. Assessment shall include, but not limited to:
 - Ambient temperature.
 - Amount of sunshine (cloudy, clear). Refer to *S3AM-121-PR1 Non-Ionizing Radiation* additional direction concerning ultraviolet radiation exposures.
 - Other radiant heat sources (e.g. motor, fire, etc.).
 - Humidity.
 - Air flow.
 - Amount or type of physical labor being performed,
 - Physical condition of the Employees (e.g., acclimated/not)
 - Protective clothing in use.
 - Referral to *S3AM-113-ATT1 Heat Stress – Temperature Thresholds* to assist in determining whether hazardous heat exposures may exist.
- If potential for hazardous exposure is identified, the Supervisor shall develop and implement a heat stress exposure control plan within the Safe Work Plan and/or Task Hazard Analysis. Refer to *S3AM-209-PR1 Risk Assessment & Management*.

4.3.2 If Employees are or may be exposed, the Supervisor shall implement engineering controls (e.g., shelters, cooling devices, etc.) to reduce the exposure of Employees to levels below those specified for the given work level and work-rest regimen as listed in *S3AM-113-ATT1 Heat Stress – Temperature Thresholds*.

4.3.3 If engineering controls are not practicable, the Supervisor shall reduce the exposure of Employees to levels below those listed in *S3AM-113-ATT1 Heat Stress – Temperature Thresholds* by providing administrative controls, including a work-rest cycle or personal protective equipment, if the equipment provides protection equally effective as administrative controls.

4.3.4 If Employees are or may be exposed, the Supervisor shall provide and maintain an adequate supply of cool, fresh, potable water close to the work area for the use of a heat exposed Employee. Water shall be provided (paid) by the project or program; if Employees purchase their own drinking water because water is not otherwise available on site, they shall be reimbursed.

4.3.5 If an Employee shows signs or reports symptoms of heat stress or strain, they shall be removed from the hot environment and treated by an appropriate first aid attendant on site, if available, or by a physician, refer to *S3AM-113-ATT2 Heat Stress – Symptoms & Treatment* for more specifics.

4.4 Heat Stress Planning

4.4.1 Heat stress can be a significant site hazard, especially for Employees wearing CPC. To prepare for emergency response planning, refer to *S3AM-010-PR1 Emergency Response Planning* procedure.

4.4.2 The project and site-specific heat related risks shall be identified. Appropriate prevention and control measures shall be developed and documented in the project's SH&E Plan or included as a supplement to the SH&E Plan (e.g., *S4[DCS]AM-113-FM1 Heat Illness Prevention Plan – DCS Americas*) and the Task Hazard Assessments (THA). Refer to the *S3AM-209-PR1 Risk Assessment & Management* procedure.

4.4.3 The heat a worker is exposed to may be a combination of air temperature, radiant heat, and humidity. The WBGT (wet-bulb globe thermometer) is a useful index of the environmental

contribution to heat stress. Because WBGT is only an index of the environment, the contributions of work demands, clothing, and state of acclimatization shall also be accounted for, as described in the following steps.

- Monitor ambient temperatures and conduct heat stress monitoring in accordance with the location specific SH&E Plan. Revise the heat stress monitoring and controls if there are any reports of discomfort due to heat stress.
- Monitor temperatures in each unique environment in which workers perform work (e.g., take WBGT measurements inside truck cabs for truck drivers, and take separate WBGT measurements in the outdoor area where field employees work, etc.). Follow manufacturer’s instructions on proper use of the WBGT.
- Determine if individual workers are acclimatized or un-acclimatized. Full heat acclimatization requires up to 3 weeks of continued physical activity under heat-stress conditions similar to those anticipated for the work. Its loss begins when the activity under those heat-stress conditions is discontinued, or when there is a sustained increase in temperatures of 10 °F (5.6 °C) or more, and a noticeable loss occurs after 4 days. A worker can be considered acclimatized for the purpose of this procedure when they have been exposed to the site conditions (including level of activity) for 5 of the last 7 days.
- Determine the approximate workload of each worker or group of workers. The following examples (Table 1) can be used for comparison:

Table 1
Examples of Activities within Workload Categories

Categories	Example Activities
Resting	Sitting quietly
	Sitting with moderate arm movements
Light	Sitting with moderate arm and leg movements
	Standing with light work at machine or bench while using mostly arms
	Using a table saw
	Standing with light or moderate work at machine or bench and some walking about
Moderate	Scrubbing in a standing position
	Walking about with moderate lifting or pushing
	Walking on level at 3.5 miles/hr (6 km/hr) while carrying 6.6 lbs (3kg) weight load
Heavy	Carpenter sawing by hand
	Shoveling dry sand
	Heavy assembly work on a non-continuous basis
	Intermittent heavy lifting with pushing or pulling (e.g., pick-and-shovel work)
Very Heavy	Shoveling wet sand

- Determine the approximate proportion of work within an hour during a typical shift. Typically, the initial work schedule will be 60 minutes of work per hour (100 percent work) with a small break in the morning and afternoon, as appropriate, and a 30-minute lunch break mid-day.
- For workers wearing cloth coveralls (e.g., Nomex fire resistant clothing), add 3 to the measured WBGT. For impermeable clothing, such as Tyvek or Saranex, the WBGT procedures cannot be used. For these situations, workers should begin physiological monitoring as soon as the temperature in the work area exceeds 70°F (21°C).
- Use the collected information to develop appropriate work to rest schedules as detailed in *S3AM-113-ATT1 Heat Stress – Temperature Threshold*. Work-rest schedules and water provision shall be documented in the applicable SH&E Plan or supplementary Health Illness Prevention Plan and may be additionally documented using logs such as *S3AM-113-FM2 Daily Heat Illness Prevention Log*.

- 4.4.4 Given the work demands (light, moderate, heavy or very heavy), heat of the work environment, and such aspects as PPE in use, workload will be adjusted appropriately to allow for proper acclimation.
- This is the process by which the body "gets used to" hot work environments. This is achieved by slowly increasing workloads.
 - New and returning Employees (absent one week or more) who have not had time to acclimatize may be more susceptible to heat related illnesses, even in seemingly low risk heat exposures.
 - All Employees shall be allowed time to acclimatize in the event of a heat wave. All Employees assigned to a new process with additional heat exposures shall be allowed to acclimatize.
 - Minimize workload and gradually increase as tolerance is built up. Allow for more frequent breaks.
 - While acclimatization normally takes approximately 5 to 7 days, heightened monitoring of these Employees will be maintained for the first 14 days.
- 4.4.5 Employees shall be instructed in the recognition of heat stress symptoms, the first aid treatment procedures for severe heat stress, and the prevention of heat stress injuries. Employees shall be encouraged to immediately report any heat stress that they may experience or observe in fellow Employees. Supervisors shall use such information to adjust the work-rest schedule to accommodate such problems.
- 4.4.6 Wherever possible, a designated break area should be established in an air-conditioned space, or in shaded areas where air conditioning is impractical. The break area should be equipped to allow Employees to loosen or remove protective clothing, and sufficient seating should be available for all Employees. During breaks, Employees shall be encouraged to drink plenty of water or other liquids, even if not thirsty, to replace lost fluids and to help cool off. Cool water should be available at all times in the break area, and in the work area itself unless hygiene/chemical exposure issues prevent it.
- 4.5 Symptoms and Treatment
- 4.5.1 Refer to *S3AM-113-ATT2 Heat Stress – Symptoms & Treatment*.
- 4.5.2 Employees who exhibit ANY signs of significant heat stress (e.g., profuse sweating, confusion and irritability, pale, clammy skin) shall be relieved of all duties at once, made to rest in a cool location, and provided with large amounts of cool water.
- 4.5.3 Severe heat stress (heat stroke) is a life-threatening condition requiring immediate emergency medical care (e.g., call 911). Anyone exhibiting symptoms of heat stroke (slurred speech, unconsciousness, etc.) shall be taken immediately to the nearest medical facility. Steps shall be taken to cool the person during transportation (clothing removal, wet the skin, air conditioning, etc.).
- 4.6 Prevention
- 4.6.1 Requirements for working in extreme heat may be triggered by regulatory established criteria (e.g. CAL/OSHA requires high heat procedures when temperature equals or exceeds 95°F) or as a result of a hazard analysis assessing various contributory factors (refer to *S3AM-113-ATT1 Heat Stress – Temperature Thresholds*). Employees working in extreme heat or sun should understand and apply the following guidelines for preventing and detecting heat exhaustion and heat stroke.
- When possible, begin hydrating at least three days prior to working in high heat conditions.
 - Review the heat stress exposure control plan within the SH&E Plan, and/or Task Hazard Analysis.
 - If the supervisor is not immediately available confirm a reliable method of communication is in place to allow for contact with supervision. In the absence of cellular reception, a satellite phone or similar device may be required.

- Take frequent short breaks in areas sheltered from direct sunlight; eat and drink small amounts frequently.
- Try to schedule work for the coolest part of the day, early morning and evening.
- Avoid strenuous physical activity outdoors during the hottest part of the day.
- Avoid sudden changes of temperature. Refer to *S3AM-113-ATT1 Heat Stress – Temperature Thresholds*.
- Air out a hot vehicle before getting into it.
- Obtain medical direction if taking diuretics during hot weather (a lower dose may be necessary).
- When working in heat, drink 1 quart of water per hour of work.
- Avoid caffeine and alcohol as they increase dehydration.
- Monitor urine frequency and color to detect dehydration. Refer to the *S3AM-113-ATT3 Dehydration Chart*.
- The Buddy System is required when working in high heat conditions to enable effective communication and cross-observation for indications of heat stress.
- Initiate emergency response procedures when necessary, including contacting emergency medical services as appropriate and in accordance with the Emergency Response Plan.

4.6.2 Personal Protective Equipment

- Review the *S3AM-208-PR1 Personal Protective Equipment* procedure.
- Wear a hat and light-colored, loose-fitting clothing to reflect the sun.
- Apply sunscreen to exposed skin (SPF 30 or greater, follow directions on label).
- Wear sunglasses with UV protection.
- Pack extra water to avoid dehydration (try freezing water in bottles overnight to help keep the water cooler for longer during the day).

4.7 Work-Rest Schedule Practices

- 4.7.1 Intake of fluid will be increased beyond that which satisfies thirst, and it is important to avoid "fluid debt," which will not be made up as long as the individual is sweating.
- Two 8-ounce glasses of water should be taken prior to beginning work, then up to 32 ounces (1 quart) per hour during the work shift; fluid replacement at frequent intervals is most effective.
 - The best fluid to drink is water; liquids like coffee or soda do not provide efficient hydration and may increase loss of water.
 - If commercial electrolyte drinks (e.g., Gatorade) are used, the drink should be diluted with water, or 8 ounces of water should be taken with each 8 ounces of electrolyte beverage.
- 4.7.2 Additional salt is usually not needed and salt tablets should not be taken.
- 4.7.3 Fluids for drinking should be cool and fresh, but not cold.
- 4.7.4 Breaks will be taken in a cool, shaded location, and any impermeable clothing should be opened or removed.
- A relatively cool, shaded area shall be provided for breaks when working in hot environments. For hazardous waste sites, the rest area should be located in the support zone adjacent to the contamination reduction zone, situated so that part of it is in the decontamination area so workers can take breaks without going through full decontamination.

- If shade is not available, shaded areas shall be constructed. This same type of canopy can be set up to shade personnel performing various types of work in hot weather.
- Cooling measures other than shade (e.g., misting, air-conditioned break areas, air conditioned vehicles, etc.) can be used in lieu of shade provided it can be demonstrated that they are at least as effective in cooling employees.
- Employees should have access to these rest areas at break times and at any other time when suffering from heat illness or believing a preventive recovery period is needed.

4.7.5 Dry clothing or towels should be available to minimize chills when taking breaks.

4.7.6 Manual labor will not be performed during breaks, other than paperwork or similar light tasks.

4.7.7 Other controls that may be used include:

- Scheduling work at night or during the cooler parts of the day (6 am–10 am, 3 pm–7 pm).
- Erecting a cover or partition to shade the work area.
- Auxiliary cooling - wearing cooling devices beneath protective garments, but over any underclothing.
 - If cooling devices are worn, only physiological monitoring will be used to determine work activity.
 - These vests typically provide cooling via one of two methods: the use of ice or other frozen media, or the use of a vortex cooler. Each method has its advantages and disadvantages.
 - The frozen media vest requires a means for freezing the media, and the media (usually water or "blue ice") will melt, requiring replacement.
 - The vortex cooler tends to cool more uniformly. Instead of frozen media, this vest uses the expansion of compressed air to cool the wearer. The drawback is the compressed air requirement, but this is negated when the wearer is already using an airline respirator supplied by a compressor. A vortex cooler should not be supplied from air cylinders, as this will draw down the cylinders rapidly.
- Auxiliary cooling should be considered when the following conditions exist:
 - Ambient temperature over 80°F (26°C).
 - Workers are wearing impermeable garments (i.e., Tyvek, Saranex, Chemrel, etc.).
 - It is desirable to have long work shifts with minimum interruption.

4.8 Evaluating the Work-Rest Schedule’s Effectiveness

4.8.1 Once a work-rest schedule is established, the Supervisor shall continually evaluate its effectiveness through observation of Employees for signs/symptoms of heat stress. Have workers assess themselves and their body’s reaction to the heat and work conditions (self-assessment), and report any signs or symptoms of heat illness. These can include nausea or dizziness, heat cramps, extreme thirst, or very dark urine.

4.8.2 Measurement or physiological monitoring of each Employee’s vitals (e.g., pulse, blood pressure, and temperature) can provide additional information in determining if the schedule is adequate. Refer to *S3AM-113-ATT1 Heat Stress – Temperature Thresholds* for additional guidance on when physiological monitoring should be conducted.

4.8.3 Frequency of physiological monitoring is increased or decreased depending upon such factors as worker fitness, acclimatization, temperature of the work environment, type of PPE, etc.

Based on the results of the physiological monitoring and on the workers’ self-assessments, the work period may be adjusted as follows:

- The work period may be increased (generally, by 5- to 10-minute intervals, up to a maximum of 4 hours) if the results of the first 2 hours of the physiological monitoring and the workers' self-assessments indicate that workers are recovering adequately (see below), and on the judgment of the SH&E Manager.
 - The work period shall be decreased if the results of the physiological monitoring and the workers' self-assessment indicate that workers are NOT recovering adequately (see below).
- 4.8.4 If physiological monitoring is conducted, the Employee and/or the SH&E Manager (or appropriate designate) shall measure and record body temperature and pulse rate as described below.
- 4.8.5 Monitor body temperature to determine if Employees are adequately dissipating heat build-up. Ear probe thermometers which are adjusted to oral temperature (aural temperature) are convenient and the preferred method of measurement. Determine work/rest regimen as follows:
- Measure oral body temperature at the end of the work period. Oral body temperatures are to be obtained prior to the employee drinking water or other fluids.
 - If temperature exceeds 99.6°F (37.5°C), shorten the following work period by 1/3 without changing the rest period.
 - If, at the next rest period, temperature still exceeds 99.6°F (37.5°C), the worker should not be allowed to continue work until repeated temperature measurements are in the acceptable range (i.e., less than 99.6°F). Do not leave the worker alone during the recovery time. Watch for signs of heat illness and be prepared to implement emergency response as necessary.
 - Do not allow a worker to wear impermeable PPE when his/her oral temperature exceeds 100.6°F (38.1°C).
- 4.8.6 At the start of the workday each Employee's baseline pulse rate (in beats per minute [bpm]) is determined by taking a pulse count for 15 seconds and multiplying the result by four or by using an automated pulse count device. Pulse rates can then be measured at the beginning of each break period and two minutes thereafter to determine if the rest period allows for adequate recovery.
- Take the radial (wrist) pulse as early as possible in the rest period and determine the worker's heart rate in beats per minute. The heart rate is determined by counting the pulse for ten seconds and multiplying the number by 6 to get the beats per minute. Record this as P1.
 - Wait 2 minutes and repeat the pulse measurement. Record this as P2.
 - If P1 is greater than or equal to 110 beats per minute (bpm) and if (P1 – P2) is less than or equal to 10 bpm (indicating that workers are not recovering adequately), shorten the next work cycle by 1/3 without changing the rest period.
 - At the next rest period, if P1 is still equal to or greater than 110 bpm, and if (P1 – P2) is still less than or equal to 10 bpm, shorten the following work cycle by 1/3 without changing the rest period.
 - At the third rest period, if P1 is still equal to or greater than 110 bpm and (P1 – P2) is still less than or equal to 10 bpm, the worker should not be allowed to continue work until repeated pulse measurements are in the acceptable range (i.e., P1 is less than 110 bpm and (P1 – P2) is greater than 10 bpm). Do not leave the worker alone during the recovery time. Watch for signs of heat illness and be prepared to implement emergency response as necessary.
- 4.8.7 Use of an automated or similar blood pressure device will be used to assess each Employee's blood pressure at the beginning and end of each break period to determine if the rest period allows adequate cooling by applying the following criteria:
- If the blood pressure of an Employee is outside of 90/60 to 150/90, then the Employee will not be allowed to begin or resume work; extend the break period by at least five minutes, at the end of which blood pressure rates will be re-measured and the end-of-break criteria again applied.

4.8.8 All physiological monitoring of heat stress will be documented using *S3AM-113-FM1 Heat Stress Monitoring Log*.

4.9 Training

4.9.1 Employees and their Supervisors that may be exposed to the hazard will be trained and oriented to the hazard and the controls prior to work commencing.

4.9.2 Those Employees, including Supervisors, potentially exposed to heat stress will receive training, refer to the *S3AM-003-PR1 SH&E Training* procedure. Training will include, but is not limited to:

- Sources of heat stress (environmental and personal), influence of protective clothing, and importance of acclimatization;
- How the body handles heat and acclimatization;
- Recognition of heat-related illness symptoms;
- Preventative/corrective measures including, but not limited to;
 - Employees will be informed of the harmful effects of excessive alcohol consumption in the prevention of heat stress.
 - All Employees will be informed of the importance of adequate rest and proper diet in the prevention of heat stress.
- First aid procedures for heat stress-related illnesses; and
- Immediate reporting of any heat-related incident (injury, illness, near-miss), refer to the *S3AM-004-PR1 Incident Reporting, Notifications & Investigation* procedure.

5.0 Records

5.1 None

6.0 Attachments

6.1 [S3AM-113-ATT1 Heat Stress - Temperature Thresholds](#)

6.2 [S3AM-113-ATT2 Heat Stress - Symptoms & Treatment](#)

6.3 [S3AM-113-ATT3 Dehydration Chart](#)

6.4 [S3AM-113-FM1 Heat Stress Monitoring Log](#)

6.5 [S3AM-113-FM2 Daily Heat Illness Prevention Log](#)

6.6 [S3\[DCS\]AM-113-FM1 Heat Illness Prevention Plan – DCS Americas](#)

1.0 Purpose and Scope

- 1.1 Communicates the requirements and precautions to be taken by AECOM employees to protect against the biological hazards associated with insects, arachnids, snakes, poisonous plants, and other animals referred to herein collectively as “biological hazards”.
- 1.2 This procedure applies to all AECOM Americas-based employees and operations and any other entity and its personnel contractually required to comply with this document’s content.

2.0 Terms and Definitions

- 2.1 **Field Work** – Any activity conducted at a site that contains brush, overgrown grass, leaf litter, poisonous plants, or is located near mosquito breeding areas and includes work in structures where animals might exist that harbor fleas or ticks or where spiders and mites could be present. Field work includes, but is not limited to, Phase I, Phase II, Operations Monitoring & Maintenance, biological surveys, and other work that meets the definition of field work.
- 2.2 **Poisonous** – Capable of harming or killing by or as if by poison; toxic or venomous.
- 2.3 **Phase I Environmental Site Assessment** – Investigation of real property to determine the possibility of contamination, based on visual observation and property history, but no physical testing. Under new Environmental Protection Agency regulations that went into effect on November 1, 2006, a Phase I, as it is called for short, will be mandatory for all investors who wish to take advantage of Comprehensive Environmental Response, Compensation, and Liability Act defenses that will shield them from liability for future cleanup, should that prove necessary. The new Phase I rules, called “All Appropriate Inquiry” or AAI, also require more investigation than previously mandated. Investors can expect to see dramatic price increases over prior experiences.
- 2.4 **Phase II Environmental Site Assessment** – Investigation of real property through physical samplings and analyses to determine the nature and extent of contamination and, if indicated, a description of the recommended remediation method.

3.0 References

- 3.1 RS2-001-PR1 Firearms Standard
- 3.2 S3AM-004-PR1 Incident Reporting, Notifications & Investigation
- 3.3 S3AM-008-PR1 Fitness for Duty
- 3.4 S3AM-113-PR1 Heat Stress
- 3.5 S3AM-208-PR1 Personal Protective Equipment
- 3.6 S3AM-209-PR1 Risk Assessment & Management

4.0 Procedure

- 4.1 Roles and Responsibilities
 - 4.1.1 **Managers / Supervisors**
 - Responsible for managing field work.

- Work with employees to see that a Task Hazard Analysis (THA) for the work to be conducted has been performed prior to the beginning of the field work and that it includes an assessment of potential biological hazards.
- Implement control measures at the location to reduce the potential for employees to be exposed to injuries and illnesses from biological hazards while working.
- If the exposures cannot be eliminated or managed with engineering controls, approve the use and cost of Personal Protective Equipment (PPE) and protective repellents and lotions and confirm that exposed employees have and use these products.

4.1.2 SH&E Manager

- Confirm training and guidance is provided to employees consistent with this procedure.
- During the performance of site visits, assess the precautions being taken against biological hazards for compliance with this procedure.
- Assist AECOM personnel in identifying hazards and selecting appropriate control measures.
- As applicable, review and approve relevant SH&E Plans for locations that have biological hazards.

4.1.3 Employees

- Participate in required training related this procedure.
- Participate in the development of THAs for the task, identify control measures to limit exposure and request PPE, repellents, and protective lotions identified by this procedure.
- Update the applicable THA when a new, unaccounted for biological hazard is identified. Employee shall stop work to identify appropriate elimination or control measures (and obtain any necessary guidance) before continuing work.
- Obtain approval from Managers and/or Supervisors to purchase selected PPE prior to purchasing.
- Implement the precautions appropriate to prevent exposure to the hazardous wildlife, insects and plants.
- Observe requirements for reporting (e.g. tick bites, skin irritations, etc.) as detailed within the procedure and attachments.

4.2 Training

4.2.1 Employees shall be trained to recognize organisms that represent a threat in the regions in which they work – experienced field staff shall provide on the job training to assist staff with hazard recognition.

4.2.2 Employees shall be properly trained to the anticipated tasks and the associated required PPE.

4.3 Overview

4.3.1 The procedures discussed below are detailed because these hazards have historically posed the most significant risk to AECOM employees. Note that this discussion is not a fully encompassing list of hazards. As part of the SH&E Plan and THA developed by the AECOM personnel, in accordance with *S3AM-209-PR1 Risk Assessment & Management*, additional consideration shall be given to other biological hazards.

4.3.2 Departments of Public Health local to the worksite, as well as the Centers for Disease Control (CDC) can serve as a resource for identifying biological hazards not discussed in this procedure.

4.3.3 If additional biological hazards are identified, employees should stop work and contact the SH&E Manager to discuss the hazards and identify effective control measures. Those control measures shall be implemented at the location prior to restarting work.

4.4 Employee Sensitivity

- 4.4.1 Sensitivity to toxins generated by plants, insects and animals varies according to dosage and the ability of the victim to process the toxin; therefore, it is difficult to predict whether a reaction will occur, or how severe the reaction will be. Employees should be aware that there are a large number of organisms capable of causing serious irritations and allergic reactions. Some reactions will only erupt if a secondary exposure to sunlight occurs. Depending on the severity of the reaction, the result can be severe scarring, blindness or even death.
- 4.4.2 Employees also need to consider whether they are sensitive to the use of insect repellents.

4.5 Planning and Hazard Assessment

- 4.5.1 AECOM personnel shall confirm that the potential for exposure to specific biological hazards are assessed prior to the commencement of work and that the procedures specified by this procedure are integrated into the THA planning process and conveyed to employees conducting the field work. This information shall be communicated in the location-specific SH&E plan, the THA, pre-project kickoff meetings, and tailgate meetings at the location.
- 4.5.2 It is important to note that the precautions to be taken by employees to decrease the risk of exposure to biological hazards can directly increase the risk of heat-related illness due to thermal stresses. Therefore, heat stress monitoring and precautions shall be included as a critical component of the task-specific THA in accordance with *S3AM-511-PR1 Heat Stress*.
- 4.5.3 During the preparation of the location-specific SH&E plan and task specific THA, Managers, Supervisors, and employees shall determine what biological hazards might be encountered during the task or operations and shall prescribe the precautions to be taken to reduce the potential for exposure and the severity of resulting illnesses. Consideration will be given to conditions such as weather, proximity to breeding areas, host animals, and published information discussing the presence of the hazards.
- 4.5.4 It should be assumed that at least one of the biological hazards exists whenever working on undeveloped property. This can include insect activity any time that local temperatures exceed 40 degrees Fahrenheit (4.5 degrees Celsius) for a period of more than 24 hours. The stubble and roots of poisonous plants can be a hazard any time of year, including when some plants are dormant or mown.
- 4.5.5 The hazard assessments shall also consider the additional hazards posed by vegetative clearing such as the increased risk of coming in contact with poison ivy, oak or sumac and hazards associated with the use of tools and equipment to remove vegetation.
- 4.5.6 Employees in the field where biological hazards exist shall not enter the hazard areas unless they are wearing the appropriate protective clothing, repellents, and barrier creams specified below. If the hazard is recognized in the field but was not adequately assessed during the THA, the field staff shall stop work and not proceed until the THA has been amended and approved and protective measures implemented.
- 4.5.7 Employees who have severe allergic reactions are strongly recommended to notify their Manager, field Supervisor and co-workers of the potential for a reaction and demonstrate what medication they might need, where they keep it and how it is administered.
- 4.5.8 A decision flow chart and table for determining the potential for biological hazards in the Americas has been provided in *S3AM-313-ATT1 Biological Hazard Assessment Flow Chart*.

4.5.9 Restrictions:

- No firearms or weapons are allowed to be used without express permission by the Region Executive and Chief Resilience Officer, refer to the *RS2-001-PR1 Firearms Standard*.
- No weapons related work shall occur without an assessment that includes appropriate hazard control measures and training.

- Staff with life-threatening reactions shall not undertake work in areas infested with the allergen (e.g., wasps, poison ivy), unless precautions are met which satisfy a medical practitioner's requirements. Refer to *S3AM-008-PR1 Fitness for Duty*.

4.5.10 Precautions

- Be aware of the potential irritants in your area and know how to recognize them.
- Modify activities to avoid encounters (diurnal rhythms, seasonal rhythms).
- Avoid wearing perfume and cologne and strong smelling deodorants, lotions, soaps, and shampoos.
- When working in areas where there may be small insects that “hitchhike” (e.g., ticks, spiders, scorpions), it is recommended that clothes are turned inside out and shaken at the end of day; do not wear same clothes two days in a row.
- Staff should always be aware of where they are placing their hands, or where they are sitting in order to avoid contact with potential toxins. Avoid reaching into areas where visibility is limited.

4.6 Wildlife Hazards (Wild Animals, Reptiles and Birds)

4.6.1 Employees shall not work alone in areas where the risk of an encounter with dangerous wildlife is high. Wildlife handling shall only be completed under direct supervision of an experienced individual. Refer to the following work instructions for more specifics:

- *S3AM-313-ATT13 Alligators*
- *S3AM-313-ATT9 Large Carnivores & Ungulates*
- *S3AM-313-ATT10 Bear Safety*
- *S3AM-313-ATT11 Small Mammals*
- *S3AM-313-ATT12 Snakes & Scorpions*

4.7 Ticks, Spiders and other Insects

4.7.1 Insects for which precautionary measures should be taken include but are not limited to: mosquitoes (potential carriers of disease aside from dermatitis), black flies, wasps, bees, ticks, fire ants and European fire ants.

4.7.2 Employees with known allergies to insect stings should consult their personal physician for advice on any immediate medications that they should carry with them. Epi-pens¹ shall be carried at all times in the field by employees who are aware that anaphylactic shock is a possibility for them. AECOM highly recommends that employees with known allergies inform their co-workers of the allergy and the location of the medications they might carry for the allergy.

4.7.3 Habitat Avoidance, Elimination and/or Control

- The most effective method to manage worker safety and health is to eliminate, avoid and/or control hazards. Clearing the location of brush, high grass and foliage reduces the potential for exposure to biological hazards. Clearing will not eliminate the exposure to flying insects and there might be an increased exposure to ticks and spiders during the clearing process.
- Projects such as subsurface environmental assessment or remediation are often candidates for brush and overgrown grass to be cleared. In these instances, the Manager shall either request that the client eliminate vegetation, or request approval from the client to have vegetation clearing added to the scope of work.
 - It should be noted that vegetation clearance may unintentionally serve to spread noxious and poisonous plant materials around the site.

¹ *Epi-pens must be prescribed by a personal physician. Renew epi-pens on a regular schedule to ensure effectiveness and make sure your field companions know where it is and how to use it if you cannot self-administer the dose.*

- As applicable, measures should be taken to prevent spread, such as but not limited to, confirming equipment and materials are not placed on affected areas, and equipment is decontaminated after use and before removal from site.
- When work shall be conducted in areas that cannot or may not be cleared of foliage, personal precautions and protective measures shall be prescribed.
- Mosquitoes breed in stagnant water and typically only travel a quarter mile (less than half a kilometer) from their breeding site. Whenever possible, stagnant water should be drained to eliminate breeding areas. Managers and client site managers should be contacted to determine whether water can be drained and the most appropriate method for draining containers, containment areas, and other objects of standing water.
- If water cannot be drained, products similar to Mosquito Dunks® can be placed in the water to control mosquitoes. Once wet, the Mosquito Dunks® kill the immature, aquatic stage of the mosquito. The active ingredient is a beneficial organism that is lethal to mosquito larvae, but harmless to fish, humans, and other animals. Mosquito Dunks® provide long-term protection for 30 days or more.

4.7.4 Ticks

- Ticks can be encountered when walking in tall grass or shrubs. They crawl up clothing searching for exposed skin where they will attach themselves. The most serious concern is a possibility of contracting a disease.
- Data from the CDC indicates that tick-borne diseases have become increasingly prevalent. At the same time, tick repellents have become both safe and effective so it is possible to prevent the vast majority of bites and, therefore, most related illnesses. The use of permethrin is strongly advised.
- The most common and severe tick-borne illnesses in the U.S. are Lyme disease, Ehrlichiosis, and Rocky Mountain spotted fever. A summary table listing CDC informational resources for these diseases is provided in *S3AM-313-ATT2 Ticks* along with a listing of CDC information resources and maps showing the distribution of common tick-borne diseases in the U.S.
- When working in areas where ticks may occur, it is recommended that clothes are turned inside out and shaken at the end of day; do not wear the same clothes two days in a row.
- Employees should conduct a thorough full body tick check upon exiting the field. Shower within two hours of coming indoors to help wash away loose ticks. Clothes should be laundered in hot water or tumble dry clothes in a dryer on high heat for 10 minutes to kill ticks.
- To remove ticks that are embedded in skin, utilize a tick key. Alternatively use tweezers or fingers to carefully grasp the tick as close to the skin as possible and pull slowly upward, avoiding twisting or crushing the tick. Do not try to burn or smother the tick. Cleanse the bite area with soap and water, alcohol, or household antiseptic. Note the date and location of the bite and save the tick in a secure container such as an empty pill vial or film canister. A bit of moistened paper towel placed inside the container will keep ticks from drying out. Follow AECOM incident reporting guidelines to report the tick bite within 4 hours and notify the Manager or Supervisor.
- Familiarize yourself with the characteristic bulls-eye pattern of Lyme disease infection surrounding the bite. If you notice this type of pattern or rash resulting from a tick bite, immediately report the issue to your supervisor and follow the incident reporting requirements for your business group.
- If you experience symptoms such as fever, headache, fatigue, and a skin rash, you should immediately visit a medical practitioner as Lyme disease is treated easily with antibiotics in the early stages, but can spread to the heart, joints, and nervous system if left untreated.

4.7.5 Chiggers

- Chiggers are mite larvae, approximately ½ millimeter in size, and typically invisible to the naked eye. While chiggers are not known to carry infectious diseases, their bites and resulting rashes and itching can lead to dermatitis and a secondary infection.
- Chiggers are typically active from the last hard freeze in the winter or spring to the first hard freeze. They are active all year in the Gulf Coast and tropical areas.

4.7.6 Spiders

- Spiders can be found in derelict buildings, sheltered areas, basements, storage areas, well heads and even on open ground. Spiders can be found year round in sheltered areas and are often present in well heads and valve boxes.
- Most spider bites produce wounds with localized inflammation and swelling. The Black Widow and Brown Recluse spiders in the U.S. and others outside the U.S. inject a toxin that causes extensive tissue damage and intense pain.
- Additional information on spider identification can be found in attachment *S3AM-313-ATT3 Poisonous Spider Identification*.

4.7.7 Mosquitoes

- When a mosquito bites, it injects an enzyme that breaks down blood capillaries and acts as an anticoagulant. The enzymes induce an immune response in the host that results in itching and local inflammation. The tendency to scratch the bite sites can lead to secondary infections.
- CDC data indicates that mosquito-borne illnesses, including the strains of encephalitis, are a health risk. At least one of the Encephalitis strains listed below is known to exist in every area of the U.S. and in many other countries as well:
 - Eastern Equine encephalitis
 - Western Equine encephalitis
 - West Nile Virus
 - St. Louis encephalitis
 - La Crosse encephalitis
- Mosquitoes can transmit the West Nile Virus and other forms of encephalitis after becoming infected by feeding on the blood of birds which carry the virus.
- Most people infected with the virus experience no symptoms or they have flu-like symptoms. Sometimes though, the virus can cause severe illness, resulting in hospitalization and even death, so proper precautions should be taken. Consult a medical practitioner if you suspect you have West Nile Virus. Other diseases including Dengue Fever and Malaria are spread by mosquitoes in the sub-tropic and tropical parts of the world. See *S3AM-313-ATT4 Mosquito Borne Diseases* for information on the locations where mosquito borne diseases are known to be present.

4.7.8 Bees, Wasps and Hornets

- Wasps and bees will cause a painful sting to anyone if they are harassed. They are of most concern for individuals with allergic reactions who can go into anaphylactic shock. Also, instances where an individual is exposed to multiple stings can cause a serious health concern for anyone. These insects are most likely to sting when their hive or nest is threatened.
- Bees, hornets, and wasps may be found in derelict buildings, sheltered areas, behind covers or lids and even on open ground. Other protective measures are not normally effective against aggressive, flying insects. Be aware of the potential areas for these types of insects, approach these locations cautiously. Avoid reaching into areas where visibility is limited.
- If you see a nest in the area you are working in stop work. Contact the Manager or Site Supervisor for procedures to have the nest removed.

- If stung by a wasp, bee or hornet, notify a co-worker or someone who can help should you have an allergic reaction. Stay calm and treat the area with ice or cold water. Follow AECOM incident reporting guidelines to report the sting within 4 hours and notify the Manager or Supervisor immediately. Seek medical attention if you have any reactions to the sting such as developing a rash, excessive swelling or pain at the site of the bite or sting, or any swelling or numbness beyond the site of the bite or sting.

4.7.9 Fire Ants

- The fire ant (southern and western U.S.) and the European fire ant (northeastern U.S. and eastern Canada) is often very abundant where it is established. It is very aggressive and commonly climbs up clothing and stings unprovoked when it comes into contact with skin. Painful irritations will persist for an hour or more.

4.7.10 Personal Protective Equipment (PPE)

- Chemically-treated field clothing, full-length clothing, or Tyvek® coveralls.
- Gloves shall also be worn consistent with the recommendations of the site-specific SWP and/or THA to minimize hand exposure.
- Where ticks, chiggers, and spiders are presumed to exist, the Tyvek® or chemically treated clothing will be taped to the work boots.
- See *S3AM-313-ATT2 Ticks* for configuration of clothing for protection against ticks and insects.
- Application of insect repellent to clothing and/or exposed skin. Oil of lemon eucalyptus, DEET, and Permethrin have been recommended by the CDC for effective protection against mosquitoes that may carry the West Nile virus and related diseases.
- Note that DEET will reduce the effectiveness of Fire Resistance Clothing (FRC) and should not be applied to this clothing. If working in FRC, employees can use Permethrin as it has been shown not to reduce the effectiveness of FRC. Permethrin will need to be applied to FRC well in advance of the planned work. If permethrin is unavailable employees can apply DEET to their skin and let dry prior to putting FRC on.
 - Oil of Lemon Eucalyptus is a plant-based insect repellent on the market as Repel Lemon Eucalyptus. The products have been proven to be effective against mosquitoes, deer ticks, and no-see-ums for up to six hours. Derived from Oil of Lemon Eucalyptus, this non-greasy lotion or spray has a pleasant scent and is not known to be toxic to humans. The spray or lotions will be effective for approximately two to six hours and should be reapplied every two hours to sustain protection. Lemon Eucalyptus products cannot be applied to fire retardant clothing.
 - Permethrin is an insecticide with repellent properties registered with the Environmental Protection Agency and recommended by the CDC.
 - Permethrin is highly effective in preventing tick bites when applied to clothing, but is not effective when applied directly to the skin. Two options are available for Permethrin treatment of clothing worn during field work: 1) pre-treatment of fabric by the clothing manufacturer; or 2) manual treatment of their personal clothing using Permethrin spray in accordance with manufacturers recommendations. This will likely require treatment at home or the office prior to field mobilization. Caution should be used when applying Permethrin as it is highly toxic to fish and house cats. AECOM strongly recommends the first option (employees obtaining pre-treated clothing) to avoid the time required, potential risk, and housekeeping issues involved with manually treating the clothing with spray. Purchase pre-treated clothing in accordance with *S3AM-208-PR1 Personal Protective Equipment* and with the approval of your Supervisor or Manager.
 - The Permethrin pre-treatment is odorless and retains its effectiveness for approximately 25 washings. After 25 washings, the pre-treated clothing will be

considered no longer effective and removed from service. Clothing that has been manually treated by employees will be considered effective for five wash cycles.

- Also, use of clothing that has been pre-treated with Permethrin offers a reduction in the use and application of other insect repellents that shall be applied directly to the skin. Supervisor or Manager approval is required prior to purchase.
- If the employee opts not to utilize chemically pre-treated clothing while potentially exposed to insects, spiders and/or ticks, they shall either: 1) wear Tyvek® coveralls taped to the boots, or 2) wear full-length clothing consisting of long-legged pants and long-sleeved shirts treated with an insect repellent containing Permethrin, DEET, or an oil of lemon eucalyptus to their work clothing.
- Safety Data Sheets (SDS) for the repellents, lotions, and cleansers discussed in this Procedure are not required because the repellents, lotion, and clothing are consumer products used in the manner intended for the general public. Although not required, a SDS should be obtained for the products used and placed into the office SDS library and site-specific safety plan.

4.8 Poisonous Plants

4.8.1 Habitat Avoidance, Elimination and/or Control

- If poisonous plants are identified in the work area, employees will mark the plants using either flags or marking paint, and discuss what the specific indicator will be to signal to other employees to avoid the designated area. If employees decide to use ground-marking paint to identify poisonous plants, they should discuss this tactic with the Manager (and Client as appropriate) for approval.
- If removal of the plants is considered, it should be subcontracted to a professional landscaping service that is capable and experienced in removing the plant. If herbicides are considered for use, a discussion shall need to occur with the Manager (and Client as appropriate) to determine whether it is acceptable to apply herbicides at the work site. Application of herbicides may require a license.
- Employees shall not attempt to physically remove poisonous plants from the work area unless a clearing procedure, including PPE, is prepared in advance and approved by the SH&E Manager. The clearing procedure should be included in the SH&E Plan and THA and the required PPE specified.

4.8.2 Poisonous plants that employees should recognize and take precautions to avoid include: poison sumac, poison ivy (terrestrial and climbing), poison oak, giant hogweed² (or giant cow parsnip), wild parsnip, devil's club and stinging nettle. Many others are extremely poisonous to eat (e.g., poison hemlock; water parsnip) – do not eat anything that has not been identified. Refer to *S3AM-313-ATT5 Plants of Concern* for information on locations where some of these poisonous plants are found in the U.S.

- Of the toxic plants in the cashew family, poison ivy (*Rhus radicans*) is most widespread. It grows in a variety of forms such as a low sprawling shrub, dense ground cover, or a thick woody vine that grows high into the tree canopy. Poison oak (*Rhus diversiloba*) is typically a low shrub in drier soils. Both of these plants have leaves of three and white berries. Poison sumac (*Rhus vernix*) is a tall shrub that is less prolific in distribution. It grows in wet areas, has a compound leaf with a red leaf stem (rachis), and white berries. All of these plants possess urushiol oils in all parts of the plant. Touching the plant causes an itchy skin rash that can show up within 4-72 hours following contact. People have a wide range of reactions including swelling, itching, rash and bumps, patches or blisters.
- Uroshiol oil can also transfer onto clothing and equipment. The oil can remain active on surfaces for up to 5 years and can be transferred to your skin.

² Phytodermatits producer: keep skin covered and wash well after exposure

- Wild parsnip is found throughout the U.S. and contains a poison that produces a rash similar to poison oak and ivy. Unlike poison oak and ivy, the active oil will not be present on unbroken leaves. See *S3AM-313-ATT6 Wild Parsnip Identification* for additional information and photos of wild parsnip.
 - Several plants in the carrot family contain toxic sap that causes severe dermatitis if it comes into contact with skin that is then exposed to sunlight. The most serious reaction is caused by the giant hogweed (*Heracleum mantegazzianum*), a plant that is spreading in southern Ontario and is also present in southwestern British Columbia. The plant is enormous, attaining up to 16 feet (5 meters) in height, which it does in one growing season. Contact causes painful blistering that can cause permanent disfigurement. It is to be avoided. Similar but less serious reactions can be caused by meadow parsnip (*Pastinaca sativa*) and cow parsnip (*Heracleum lanatum*). Meadow parsnip can be very abundant on disturbed sites.
 - Nettles, particularly stinging nettle (*Urtica dioica*) and wood nettle (*Laportea canadensis*) contain urticating hairs on the leaves and stems that cause sharp pain or itchiness on contact with skin. The irritation is immediate and normally lasts no more than an hour and there are no lasting consequences.
 - Some plants contain abundant stiff spines that can present a safety hazard, particularly if one is to fall into them. These include the cactus (*Opuntia spp.*), devils club (*Oplopanax horridum*), and prickly-ash (*Zanthoxylon americanum*).
- 4.8.3 A large number of plants are not harmful to touch but may contain poisonous berries or foliage that could cause serious complications or death if they are ingested. It goes without saying to not eat any berries or plants if you are unsure of their identity.
- Remember that in the fall and winter the hazard still exists in the form of stubble and roots.
- 4.8.4 Personal Protective Equipment (PPE)
- Employees conducting clearing, grubbing, or similarly disturbing work activities in areas where poisonous plants exist shall wear long-sleeve clothing or Tyvek® coveralls, and disposable cotton, leather or synthetic gloves. Employees shall not touch exposed skin (neck and face) with potentially contaminated gloves. Tyvek® and gloves worn to protect from exposure to poisonous plants shall be treated as contaminated, removed from the body in a manner that the contamination is not spread, and placed in plastic bags for disposal.
 - Personal clothing that has been exposed to poisonous plants shall be decontaminated with a poisonous plant cleanser such as Tecnu® or removed in a careful manner, bagged and washed separately from other clothing to remove urushiol.
 - Work boots will be decontaminated with either soap and water or a cleansing agent such as Tecnu® cleanser.
 - If foliage is being cleared and includes poisonous plants, exposed skin shall be treated with a dermal barrier cream such as Tecnu®'s Oak 'n Ivy Armor or Enviroderm's Ivy Block and either a full-face respirator or a half-face respirator (with goggles) fitted with a P-100 (HEPA) dust filter.
- 4.9 Bird Droppings and Biological Soil Hazards
- 4.9.1 Work in any area where pigeons or other flying animals (e.g. bats) may nest requires a written statement from the client which states the potential for, and extent of, accumulation of excrement on/in the structure from pigeons or other winged animals.
- 4.9.2 Substantial accumulations of droppings can pose physical and health risks as slippery surfaces (if wet) and if the material is disturbed and becomes airborne, it can be inhaled or ingested if personal hygiene practices are not implemented. Inhalation of airborne droppings can cause diseases such as histoplasmosis. Exposure to surfaces with bird droppings shall be safeguarded by implementing proper work practices, training employees for awareness and using PPE. See *S3AM-313-ATT8 Bird Droppings*.

- 4.9.3 Tularemia is a problem with contaminated soil in some locations. Tularemia is a disease of animals and humans caused by the bacterium *Francisella tularensis*. Rabbits, hares, and rodents are especially susceptible and often die in large numbers during outbreaks. Workers can contract Tularemia through tick and deer fly bites, but also through inhalation of contaminated aerosols or agricultural dusts. Check work areas for carcasses before disturbing the ground (e.g. mowing, brushing, grubbing, excavation, etc.).
- 4.10 Personal Hygiene and Body Checks
- 4.10.1 Tick-borne diseases typically require that the tick be imbedded for four hours to begin disease transfer. The oils from poisonous plants can take up to 4 hours after exposure to penetrate the skin and react with the live proteins under the skin.
- 4.10.2 It is recommended that exposed skin be checked frequently for the presence of ticks, insects, rashes, or discolorations. External clothing should also be checked for the presence of ticks and insects; these should be retained for identification and to determine if medical treatment is needed.
- 4.10.3 Employees shall shower as soon as practical after working in the field and examine their bodies for the presence of ticks, insect bites, rashes, or swollen areas. If imbedded ticks are found, they should be removed using the technique described in *S3AM-313-ATT2 Ticks*.
- 4.11 Employees shall immediately notify their Manager or Supervisor of the presence of an imbedded tick, bee, wasp or hornet sting, other insect bite, rash, or any abnormal reaction. Reporting shall occur within 4 hours for a significant incident and 24 hours for all other SH&E incidents, and in accordance with *S3AM-004-PR Incident Reporting, Notifications & Investigation*.
- 4.12 The Manager or Supervisor shall forward the report to the SH&E Manager for follow up.

5.0 Records

None

6.0 Attachments

- 6.1 [S3AM-313-ATT1 Biological Hazard Assessment Flow Chart](#)
- 6.2 [S3AM-313-ATT2 Ticks](#)
- 6.3 [S3AM-313-ATT3 Poisonous Spider Identification](#)
- 6.4 [S3AM-313-ATT4 Mosquito Borne Diseases](#)
- 6.5 [S3AM-313-ATT5 Plants of Concern](#)
- 6.6 [S3AM-313-ATT6 Wild Parsnip Identification](#)
- 6.7 [S3AM-313-ATT7 Alligators](#)
- 6.8 [S3AM-313-ATT8 Bird Droppings](#)
- 6.9 [S3AM-313-ATT9 Large Carnivores & Ungulates](#)
- 6.10 [S3AM-313-ATT10 Bear Safety](#)
- 6.11 [S3AM-313-ATT11 Small Mammals](#)
- 6.12 [S3AM-313-ATT12 Snakes & Scorpions](#)

Appendix E

Instrument Calibration Sheet and Air Monitoring Data Sheet

Air Monitoring Instrument Calibration Log

Instrument Type (Type, Model No., Serial No. etc.)		
Temperature (if applicable)	Calibration Source	Results
Calibration Gas Lot or Batch # Exp. Date	Location (On-Site. Off-Site, Office, etc.)	
Operator Initials	Date/Time	
Instrument Type (Type, Model No., Serial No. etc.)		
Temperature (if applicable)	Calibration Source	Results
Calibration Gas Lot or Batch # Exp. Date	Location (On-Site. Off-Site, Office, etc.)	
Operator Initials	Date/Time	
Operator Initials	Date/Time	

ADDITIONAL NOTES:

SIGNATURE _____

aecom.com